

The `cleveref` package*

Toby Cubitt
`toby-cleveref@dr-qubit.org`

25/05/2010

Abstract

The `cleveref` package enhances L^AT_EX's cross-referencing features, allowing the format of cross-references to be determined automatically according to the "type" of cross-reference (equation, section, etc.) and the context in which the cross-reference is used. The formatting for each cross-reference type can be fully customised in the preamble of your document. In addition, `cleveref` can typeset cross-references to lists of multiple labels, automatically formatting them according to their types, sorting them, and compressing sequences of numerically consecutive labels. Again, the multiple-reference formatting is fully customisable.

Contents

1	Introduction	3
2	Usage	4
3	Type-Setting Cross-References	5
4	Sorting and Compressing	6
5	Capitalising All Cross-Reference Names	7
6	Customising the Cross-Reference Format	8
6.1	Customising the Cross-Reference Components	8
6.1.1	Global Customisation	8
6.1.2	Customising Individual Cross-Reference Types	10
6.1.3	Automatic <code>\newtheorem</code> Definitions	12
6.2	Low-Level Customisation: Taking Full Control	12
6.2.1	Single Cross-References	13
6.2.2	Reference Ranges	14
6.2.3	Multiple Cross-References	14
6.3	Language and <code>babel</code> support	15

*This document corresponds to `cleveref` 0.16.3, dated 25/05/2010.

7 Overriding the Cross-Reference Type	16
8 Poor Man's <code>cleveref</code>	17
9 Interaction with Other Packages	18
10 Known Bugs and Possible Improvements	19
10.1 Known Bugs, Non-Bugs, and Work-Arounds	19
10.2 Possible Improvements	20
11 Thanks	20
12 Implementation	22
12.1 Redefinitions of L ^A T _E X kernel macros	22
12.2 Utility Macros	32
12.2.1 miscellaneous	32
12.2.2 aux file information	32
12.2.3 Stack data structures	34
12.2.4 Sorting and comparison of counters	37
12.2.5 Reference stack processing	43
12.3 Cross-Referencing Commands	47
12.4 Reference Format Customisation Commands	54
12.4.1 Format Component Commands	54
12.4.2 Cross-Reference Format Definition Commands	62
12.5 <code>hyperref</code> Support	67
12.6 <code>ntheorem</code> Support	71
12.7 <code>\newtheorem</code> Support	72
12.8 <code>amsthm</code> Support	73
12.9 <code>varioref</code> Support	75
12.10 Poor Man's <code>cleveref</code>	77
12.11 Sort and Compress options	90
12.12 Capitalise option	90
12.13 Language and <code>babel</code> Support	91
12.13.1 Default Cross-Reference Formats	132

1 Introduction

When “clever” is used in the name of a computer program, it usually signifies that the programmer is overly smug about his own achievements! But at the heart of the L^AT_EX philosophy is the idea that it is clever to delegate as much of the typesetting as possible to the computer, in order to achieve a beautiful — and above all consistent — visual appearance.

Both these probably apply to the `cleverref` package. Its goals are two-fold: to exploit everything that L^AT_EX inherently knows about labels as intelligently as possible (clever processing); and to enable you to produce an attractive, consistent formatting of cross-references throughout your document, with the minimum of effort (you’d be clever to use it!).

The `cleverref` package enhances L^AT_EX’s cross-referencing facilities by allowing cross-references to be formatted automatically according to the type of thing they refer to (chapter, section, equation, theorem, etc.) and the context in which the cross-reference is used. It can automatically format cross-references to multiple labels, sort lists of multiple cross-references, compress cross-references to consecutive labels into a reference range, and all kinds of other clever wizardry.

In standard L^AT_EX, you have almost certainly found yourself writing things like `Eq.~(\ref{eq1})` and `Theorems~\ref{thm1} to~\ref{thm3}` over and over again. Tedium isn’t the only downside to this. What happens if you later decide you want equation references to be type-set as `Equation~\ref{eq1}` instead (i.e. without the brackets)? What happens if you decide to change the theorem labelled `thm1` into a lemma? What if you move `thm3` so that it appears (and is numbered) before `thm1`, so that references to the sequence of theorems 1 through 3 should be ordered `Theorems~\ref{thm3} to~\ref{thm1}` (i.e. the other way around)? What if you decide you prefer references to multiple theorems to be written as `Theorems~\ref{thm1}--\ref{thm3}`? You have to search through the entire L^AT_EX source of your document, modifying all references to equations, updating all references to `thm1`, re-ordering all references to `thm1` and `thm3`, and changing all the formatting of references to multiple theorems!

The `cleverref` package allows you to define the format for cross-references once-and-for-all in the preamble of your document. If you later decide to change the format of equation references, you only have to change one preamble definition. If you change a theorem into a lemma, you don’t need to change any cross-references at all, because `cleverref` will automatically type-set cross-references to it using the appropriate formatting. This makes it far easier to type-set cross-references uniformly across your whole document, as well as avoiding repetitively typing similar text for each and every cross-reference.

Given how useful this is, there are naturally a number of other packages with similar goals, most notably `varioref`, `fancyref`, `hyperref`’s `\autoref` command, and (for theorem-like environments) `ntheorem` (with the `thref` option). (There are many others, but these come closest to providing similar features to `cleverref`.) However, all have certain deficiencies which `cleverref` attempts to overcome.

The `fancyref` package doesn’t automatically determine the type of thing being referred to. Instead, it relies on you adhering to a naming convention for labels.

This is usually a good idea in any case, but it can be inconvenient. For example, if you change a theorem into a lemma, you have to change the label name, and therefore also all cross-references to it. So you are back to searching and replacing through the entire document, not to mention missing out on all the other `cleveref` features.

The enhanced referencing feature provided by the `varioref` package's `\labelformat` command decides how to format cross-references when the label is *defined*, rather than when it is *referenced*. Often this isn't a problem. But it makes it impossible to format cross-references differently according the context in which they are referenced, which can sometimes be very useful. For example, if you want cross-references at the beginning of a sentence formatted any other way than by capitalising the first letter of the cross-reference text, it is impossible using `varioref`. Perhaps even more significantly, it makes it impossible to type-set multiple references automatically; you are back to typing `Eqs.~(\ref{eq1}) to~(\ref{eq3})` by hand. Not to mention missing out on automatic sorting and compressing of consecutive references, `ntheorem` support, precise control over hyper-links, etc. `cleveref` fully supports `varioref`, taking over responsibility for type-setting cross-references, whilst retaining all the `varioref` page-referencing magic.

The `hyperref` package's `\autoref` command type-sets a name before a cross-reference, determined by the cross-reference type. This is less flexible than `cleveref`'s fully customisable cross-reference formatting but, when combined with `varioref`, the two packages working together come close. However, even with `hyperref`, it is impossible to customise precisely which part of the cross-reference is made into a hyper-link in PDF documents; this is very easy with `cleveref`. And it still remains impossible to type-set multiple references, have consecutive references sorted and compressed automatically, etc.

The `ntheorem` package (with the `thref` option) does things right with regards how and when the format is defined...except that it only works for theorem-like environments. It is possible to use it for other environments, but only in a bastardized form, by manually supplying an optional argument to `\label` commands that specifies the label type. `cleveref` works equally well when referencing any type of thing, as well as fully supporting `ntheorem`. And again, `cleveref` also provides a number additional features over `ntheorem`, such as multiple cross-references, automatic sorting and compressing of consecutive cross-references, control over the placement of hyper-links, etc.

2 Usage

The `cleveref` package is loaded in the usual way, by putting the line

```
\usepackage{cleveref}
```

in your document's preamble. However, care must be taken when using `cleveref` in conjunction with other packages that modify L^AT_EX's referencing system (see Section 9). Basically, `cleveref` must be loaded *last*.

If you just want to get going quickly with `cleveref`, and come back later to read up on all the features it provides in more detail, here's what you need to do. Wherever you would previously have used `\ref`, use `\cref` instead. (Except at the beginning of a sentence, where you should use `\Cref`.) You no longer need to put the name of the thing you're referencing in front of the `\cref` command, because `cleveref` will sort that out for you: i.e. use `\cref{eq1}` instead of `eq.~(\ref{eq1})`. If you want to refer to a range of labels, use the `\crefrange` command: `\crefrange{eq1}{eq5}` gives `eqs.~(1) to~(5)`. Finally, if you want to refer to multiple things at once, you can now combine them all into one cross-reference and leave `cleveref` to sort it out: e.g. `\cref{eq2,eq1,eq3,eq5,thm2,def1}` produces: `eqs.~(1) to~(3) and~(5), theorem~5, and definition~1`.

3 Type-Setting Cross-References

`\cref` To automatically type-set a cross-reference according to the type of thing referred to, simply refer to it using `\cref{<label>}`. `cleveref` imposes just one extra restriction on the names of labels: they are no longer allowed to contain commas “,”. These are instead used to type-set multiple cross-references (see below).

`\Cref` As it is very difficult¹ for L^AT_EX to determine whether a cross-reference appears at the beginning of a sentence or not, a beginning-of-sentence variant exists: `\Cref{<label>}`. By default, this type-sets the cross-reference with the first letter capitalised, and without using an abbreviation in those cases where the standard variant does use one. (However, the formatting of the `\cref` and `\Cref` forms can be fully and independently customised, see Section 6.)

`\crefrange` To type-set a cross-reference range, e.g. `Eqs.~(1.1) to~(1.5)`, use `\crefrange` or `\Crefrange` (depending on the capitalisation you require), which take the beginning and end of the range as arguments:

```
\crefrange{<label1>}{<label2>}
```

`\cref` To type-set multiple cross-references, simply list the labels inside the `\cref` or `\Cref` command, separated by commas (you are not allowed to use commas in label names when using `cleveref`):

```
\cref{<label1>,<label2>,<label3>,...}
```

`\cref*` When `cleveref` is used along with the `hyperref` package (see Sections 6 and 9), additional starred variants of all the referencing commands are available. The standard referencing commands will make cross-references into hyper-links; the starred variants prevent this, producing the same type-set text but without creating hyper-links.

`\ref` `cleveref` does *not* modify the standard `\ref` command, so you can still use it to type-set the formatted label counter alone, without any additional text or formatting.

¹ Actually, very likely impossible!

`\namecref` Occasionally, it's useful to produce just the name of a reference, without the label itself. For example, if you want to refer to “this section”, but you're not sure whether you might later change the section into a chapter, it might be useful to produce just the name “section” associated with the section's label. If you later change the section into a chapter, the text will then automatically change to “this chapter”. The `\namecref` and `\nameCref` do exactly this:

```
\namecref{sec1}
```

is type-set as “section” (assuming `sec1` labels a section). The `\namecrefs` and `\nameCrefs` commands produce the plural forms.

There is a slight pitfall that you should be aware of when using the `\namecref` commands. They get the reference name from the names defined for the label's reference type using `\crefname` or `\Crefname` (see Section 6.1.2). The default reference formats provide these definitions. However, it is possible to customise reference formats using lower-level commands that do not create `\crefname` definitions (see Section 6.2). If the `\crefname` definitions are missing for a particular reference type, `\namecref` and `\nameCref` will produce errors for labels of that type. You can fix the error by adding explicit `\crefname` definitions for these types.

4 Sorting and Compressing

When `cleveref` type-sets lists of multiple cross-references, the default behaviour is to automatically sort the list and compress sequences of consecutive cross-references into a reference range. You can change this behaviour by supplying one of the following package options:

`sort` Sort lists of cross-references, but don't compress consecutive references.

`compress` Compress sequences of consecutive references into a reference range, but don't sort the list of cross-references.

`nosort` Neither sort lists of cross-references, *nor* compress consecutive references.

`sort&compress` Sort lists of cross-references, and compress sequences of consecutive references into a reference range (this is the default).

Occasionally, you may want to prevent a particular sequence of consecutive cross-references from being compressed to a reference range, without disabling this feature globally. To achieve this, you can separate the cross-references in the list by one or more empty references, at the point at which you want to prevent compression. For example,

```
\cref{eq1,eq2,eq3,,eq4}
```

will be type-set as

eqs. (1) to (3) and (4)

or

```
\cref{eq1, eq2, , eq3, eq4, eq5, , eq6, eq7, eq8}
```

will be type-set as

eqs. (1), (2), (3) to (5) and (6) to (8)

You can safely put an empty reference between cross-references that would never be compressed anyway; it will simply be ignored.

If lists of cross-references are also being sorted (the default), it can be a little confusing to work out where the empty reference should go in order to prevent compression of a particular consecutive sequence. It's best to think of the empty reference as being "attached" to the cross-reference preceding it. When the list is sorted, the empty reference will still appear after the same preceding reference, and will prevent it being compressed with any subsequent consecutive cross-references. In other words, an empty reference ensures that the preceding reference will appear explicitly in the final, type-set cross-reference:

```
\cref{eq3, , eq2, eq1, eq6, eq4, eq5}
```

will be type-set as

eqs. (1) to (3) and (4) to (6)

5 Capitalising All Cross-Reference Names

capitalise Many authors prefer to always capitalise cross-reference names, regardless of where they appear in the sentence, writing Theorem 1 and Equation 3 (as opposed to theorem 1 and equation 3). If you count yourself among this group, you can pass the `capitalise` option to the `cleveref` package (`capitalize` also works).

All the default cross-reference formats will then have the first letter capitalised, as will the automatically generated `\cref` variants (see Sections 6.1.2 and 6.2). (However, if you explicitly define a `\cref` variant to *not* be capitalised, `cleveref` will still honour your definition. In other words, you're responsible for defining the capitalisation correctly in your own format definitions.)

You should *still* use the `\Cref` variants at the beginning of sentences, for one thing, because abbreviations should not be used at the beginning of a sentence,² and for another, in case you later change your mind and remove the `capitalise` option.

²At least in English; I'm not sure about other languages.

6 Customising the Cross-Reference Format

The `cleveref` package allows you to take full control of the type-setting of cross-references, by allowing the formatting to be customised. Defaults appropriate for English documents are provided for the standard label types,³ and support for German, French, Spanish and Italian is provided via package options (see Section 6.3). But if you don’t like the defaults, or are writing in a different language,⁴ or you need to refer to something for which no default format is defined, then you can take charge and define your own formats.

If `cleveref` encounters a cross-reference to a type it does not know, it will produce a “reference type undefined” warning, and type-set the cross-reference as

```
?? \ref{<label>}
```

i.e. the label counter preceded by a double question mark. The error message indicates the name of the unknown cross-reference type, which you will then probably want to define. (References to undefined labels still produce a “reference undefined” warning and appear as a double question mark, as usual.)

The cross-reference formats are usually constructed out of components: the cross-reference name (different for each type of cross-reference), the format for the label itself, and the conjunctions used in reference ranges and lists of multiple cross-references. There are two levels of customisation: you can either customise the components, or you can take full control and override the component-derived format entirely.

6.1 Customising the Cross-Reference Components

6.1.1 Global Customisation

The global customisation commands affect all cross-reference formats, unless they are overridden by lower-level customisation commands.

`\crefdefaultlabelformat` The format for the label counter itself can be customised globally using

```
\crefdefaultlabelformat{<format>}
```

The `<format>` argument can be any valid L^AT_EX code, though you will need to `\protect` fragile commands. It can (and almost certainly should!) contain three arguments, `#1`, `#2` and `#3`. The first argument is the formatted version of the label counter (e.g. `\theequation`). The other two are used to mark the beginning and end of the part of the cross-reference that should form the hyper-link when the `hyperref` package is used (see Section 9). The hyper-link arguments `#2` and `#3` *must* appear in that order. (Leaving them out completely will not cause an error,

³For any pedantic classics scholars out there: “lemmas” is recognised as a valid plural form of “lemma” in all current versions of the Oxford English Dictionary. “Lemmata” was last heard in a mathematical debate that took place in a pub just around the corner from Hadrian’s wall... a few years before the Romans pulled out of Britain. `cleveref` might have “clever” in its name, but even that doesn’t make it pretentious enough to use “lemmata”.

⁴Any contributions of translations for missing languages are very welcome! See Section 12.13 for information on how to contribute translations.

`\crefrangeconjunction`

but in that case no hyper-link will be created when `hyperref` is used, and there are better ways to achieve this. See Sections 3 and 9.)

Note that the default format for equation cross-references already overrides `\crefdefaultlabelformat` in order to surround the label by brackets, so the redefining `\crefdefaultlabelformat` will have no effect on equations. The label format for equations must be customised separately if you want to change it (see Section 6.1.2).

The conjunction used in a reference range can be customised by defining `\crefrangeconjunction`:

```
\newcommand{\crefrangeconjunction}{<conjunction>}
```

It does not have to be an actual conjunction in the linguistic sense, e.g. it is perfectly reasonable to define it to be an emdash “—”. `\crefrangeconjunction` is used directly between the start and end references in a reference range, without any additional space surrounding it, e.g. `\crefrange{thm1}{thm2}` is type-set as

```
theorems~\ref{thm1}\crefrangeconjunction\ref{thm2}
```

so you may or may not want to include surrounding space, depending on the formatting you desire. For example,

```
\newcommand{\crefrangeconjunction}{ and~}
```

does require surrounding space, whereas

```
\newcommand{\crefrangeconjunction}{--}
```

does not.

There are two other “conjunction” commands available for customizing the formating for reference ranges. These are `\crefrangepreconjunction` and `\crefrangepostconjunction`, which insert text before the first label defining the range, and after the second label, respectively. For example, when these commands are defined, `\crefrange{thm1}{thm2}` is type-set as

```
theorems~\crefrangepreconjunction\ref{thm1}  
→ \crefrangeconjunction\ref{thm2}\crefrangepostconjunction■
```

These commands are not used in the default English format definitions, but they are needed in some languages to correctly express a range. For example, the Italian format defines `\crefrangepreconjunction` to be “da”, so that `\crefrange{thm1}{thm2}` produces

```
teorema da~\ref{thm1} a~\ref{thm2}
```

`\crefpairconjunction`
`\crefmiddleconjunction`
`\creflastconjunction`

The conjunctions used in lists of multiple cross-references can be customised by defining the commands `\crefpairconjunction`, `\crefmiddleconjunction` and `\creflastconjunction`:

```
\newcommand{\crefpairconjunction}{<conjunction>}  
\newcommand{\crefmiddleconjunction}{<conjunction>}  
\newcommand{\creflastconjunction}{<conjunction>}
```

`\crefpairconjunction` is used when there are only two cross-references in the list, `\creflastconjunction` is used between the penultimate and final cross-reference in a list of more than two, and `\crefmiddleconjunction` is used between all the others. Again, they do not have to be conjunctions in the linguistic sense, and the same considerations about surrounding space apply as in the case of `\crefrangeconjunction`. For example, the default definition of `\crefmiddleconjunction` is:

```
\newcommand{\crefmiddleconjunction}{, }
```

`\crefpairgroupconjunction` By default, the conjunctions used to separate sub-lists of different cross-reference types in a multi-reference are identical to those used to separate cross-references of the same type.⁵ You can override this by defining the conjunction commands `\crefpairgroupconjunction`, `\crefmiddlegroupconjunction` and `\creflastgroupconjunction`.

For example,

```
\cref{eq1,eq2,eq3,thm1,thm2,fig1,thm3}
```

is type-set as

```
eqs. (1)\crefrangeconjunction(3)\crefmiddlegroupconjunction  
theorems 1\crefpairconjunction2\crefmiddlegroupconjunction  
fig. 1\creflastgroupconjunction{}theorem 3
```

6.1.2 Customising Individual Cross-Reference Types

`\crefname` The cross-reference name for a given cross-reference type is customised using the `\crefname` and `\Crefname` commands:

```
\crefname{\langle type \rangle}{\langle singular \rangle}{\langle plural \rangle}  
\Crefname{\langle type \rangle}{\langle singular \rangle}{\langle plural \rangle}
```

used by the `\cref` and `\Cref` commands, respectively. You must supply both `\langle singular \rangle` and `\langle plural \rangle` forms of the name. If the corresponding `\Crefname` is undefined when `\crefname` is called, it will automatically define `\Crefname` to be a capitalised version of `\crefname`, using `\MakeUppercase`. Conversely, if the corresponding `\crefname` is undefined when `\Crefname` is called, it will automatically define `\crefname` to be a lower-case version of `\Crefname`, using `\MakeLowercase`. Obviously, this will only work properly if the names begin with a letter. If the first letter is a special character construct, such as an accented character, you will need to surround it by braces. If the first thing in the name is *not* a letter at all (e.g. if it is a L^AT_EX command), you *must* define both capitalisation variants explicitly. Otherwise you will get strange and fatal errors when processing the document.

⁵More accurately, if you redefine `\crefpairconjunction` etc. in your preamble, `\crefpairgroupconjunction` etc. are automatically redefined so that they match. (In some languages, the default definition of `\creflastgroupconjunction` has an additional comma lacking in `\creflastconjunction`.)

The cross-reference $\langle type \rangle$ is usually the name of the counter for the environment (equation, chapter, section, etc.). The exceptions are appendices, labels whose type has been overridden explicitly by supplying an optional argument (see Section 7), and theorem-like environments when the `ntheorem` package is loaded, for which $\langle type \rangle$ should instead be the environment name (lemma, corollary, definition, etc.) even when different environments are part of the same numbering sequence. (`ntheorem` provides extra information about the environment when different theorem-like environments share a common counter, which `cleveref` makes use of to distinguish between them automatically.) In the case of appendices, the $\langle type \rangle$ is “appendix” for the top-level sectioning command (`\chapter` or `\section`, depending on the document class), “subappendix” for the sectioning command one level below (`\section` or `\subsection`), “subsubappendix” for the next level of sectioning command, etc.

For convenience, if they have not been otherwise customised by the end of the preamble, the cross-reference name (and label format) for `subsection` is by default inherited from that of `section`, and that of `subsubsection` is inherited from `subsection` (which might itself have been inherited from `section`). Similarly for `subappendix`, `subsubappendix` and `subsubsubappendix`, and also for `enumii`, `enumiii`, `enumiv` and `enumv`. Finally, `subfigure` and `subtable` inherit from `figure` and `table`, respectively.

`\creflabelformat`

You may want the label format for a particular cross-reference type to differ from the global format set by `\crefdefaultlabelformat` (see Section 6.1.1). You can do this using

```
\creflabelformat{\langle type \rangle}{\langle format \rangle}
```

The $\langle type \rangle$ argument is the cross-reference type to customise, and the $\langle format \rangle$ argument defines the label format for cross-references of that type. As in the case of `\crefdefaultlabelformat`, the latter should contain the three arguments #1, #2 and #3, the first being the formatted version of the label counter, the others determining the beginning and end of the portion that becomes a hyper-link when the `hyperref` package is loaded (see Section 9). #2 and #3 *must* appear in that order.

`\crefrangelabelformat`

Normally, the start and end references in a reference range are type-set using the usual label format (as defined by `\crefdefaultlabelformat` or `\creflabelformat`) separated by `\crefrangeconjunction` (Section 6.1.1). You can override this for a given cross-reference type using

```
\crefrangelabelformat{\langle type \rangle}{\langle format \rangle}
```

The $\langle format \rangle$ argument should contain six arguments: #1, #2, #3, #4, #5, #6. The first two (#1 and #2) are the formatted versions of the two label counters defining the reference range. The next two (#3 and #4) denote the beginning and end of the hyper-link for the first reference, the final two (#5 and #6) the hyper-link for the second reference. The hyper-link arguments *must* appear in order. For example,

```
\crefrangelabelformat{equation}{(#3#1#4) to~(#5#2#6)}
```

6.1.3 Automatic \newtheorem Definitions

\newtheorem The standard L^AT_EX \newtheorem command for defining new theorem-like environments provides enough information to deduce a reasonable cross-reference name for the new environment. So cleverref automatically defines an appropriate cross-reference name for new theorem-like environments. This automatic definition is only used if no default definition is provided by cleverref itself, and if no \crefname or \Crefname definition is given explicitly (see Section 6.1.2).

The caveat with this automatic definition is that, although \newtheorem essentially provides the singular form of the cross-reference name, it doesn't provide the plural form. And there is no reliable way of constructing the plural form from the singular.⁶ Therefore, if the plural form is ever required, cleverref will produce a "reference type undefined" warning, and type-set the cross-reference where the plural form is required as:

```
?? \ref{\langle label\rangle} ...
```

In this case, you will have to provide an explicit \crefname or \Crefname definition yourself, to define the plural form as well as the singular form.

6.2 Low-Level Customisation: Taking Full Control

If you need more precise control over the cross-reference format than is possible by customising the individual components, then you can take full control of the format for any given type, overriding the component-derived format entirely. The formats for single cross-references, reference ranges and multi-references are customised separately. If you only customise some of these, the other formats will be constructed from components, as usual.

Note that when deciding which cross-references should be grouped together for sorting and/or compressing, cleverref does something slightly more complicated than simply checking whether the reference types match. In fact, it checks whether the reference *formats* match.⁷ This will always be the case for cross-references of the same type. But it could also be the case for cross-references that have different types, if the cross-reference formats happen to be identical.

The reason for doing this is to allow cross-references to e.g. sections and subsections to be grouped together if they have identical formats. The default formats for the sectioning commands, figures and subfigures, tables and subtables, and enumerated lists are set up in this way. If you change any of them using the low-level customisation commands, but still want them to be grouped together, then you must ensure that the formats are *identical*. (It is *not* sufficient for the formats to produce identical type-set text; the format definitions must contain identical L^AT_EX code.)

⁶If you're a native English-speaker, you might think that just adding an 's' would work, though a moment's thought will provide examples of words where this will fail. If you're a non-English speaker, it probably won't even occur to you to claim that plurals can reliably be constructed automatically!

⁷To be precise, cleverref checks whether the \crefformat definitions match.

Note that if you use the low-level customisation commands, you might still want to provide `\crefname` and `\Crefname` definitions too, so that the `\namecref` commands will work (see Section 3).

6.2.1 Single Cross-References

<code>\crefformat</code>	Cross-reference formats for <i>single</i> cross-references are defined or redefined using the
<code>\Crefformat</code>	<code>\crefformat</code> and <code>\Crefformat</code> commands, which are used by the <code>\cref</code> and <code>\Cref</code> commands respectively. These take two arguments: the cross-reference type, and the formatting code:

```
\crefformat{\langle type \rangle}{\langle format \rangle}
\Crefformat{\langle type \rangle}{\langle format \rangle}
```

The `\langle type \rangle` is usually the name of the counter, except for labels whose type has been overridden explicitly (see Section 7), theorem-like environments when `ntheorem` is loaded, in which case it is the environment name, and appendices. For the latter, the `\langle type \rangle` is “appendix” for the top-level sectioning command (`\chapter` or `\section`, depending on the document class), “subappendix” for the sectioning command one level below (`\section` or `\subsection`), “subsubappendix” for the next level of sectioning command, etc.

As in the case of the `\crefname` and `\Crefname` commands, if the corresponding `\Crefformat` is undefined when `\crefformat` is called, it will define the `\Crefformat` to produce a capitalised version of `\crefformat`, using `\MakeUppercase`. Conversely, if the corresponding `\crefformat` is undefined when `\Crefformat` is called, it will define the `\crefformat` to produce a lower-case version of `\Crefformat`, using `\MakeLowercase`. Obviously, this will only work properly if the format starts with a letter, and letter constructs (such as accented letter constructs) must be surrounded by braces (see Section 6.1.1).

The `\langle format \rangle` argument can be any valid L^AT_EX code, though you will need to `\protect` fragile commands. It should contain three arguments, #1, #2 and #3. The first argument is the formatted version of the label counter (e.g. `\theequation`). The other two are used to mark the beginning and end of the part of the cross-reference that forms the hyper-link when the `hyperref` package is used, and *must* appear in that order (see Section 9).

As an example,

```
\crefformat{equation}{Eq.~(\#2\#\#1\#\#3)}
```

will type-set equation references as

Eq. ((*counter*))

with the counter (excluding the brackets) forming the hyper-link.

Note that the hyper-link arguments are *not* letters, so if #2 appears at the beginning of `\langle format \rangle`, `cleveref` will not be able to automatically define the other capitalisation variant automatically using `\MakeUppercase` or `\MakeLowercase`.

In this case, you will have to define both variants separately. For example, if you wanted to the “Eq.” to be part of the hyper-link, you would have to define:

```
\crefformat{equation}{\#2eq.\~{#1}\#3}
\Crefformat{equation}{\#2Eq.\~{#1}\#3}
```

6.2.2 Reference Ranges

`\crefrangeformat` `\Crefrangeformat` The format for reference ranges is defined by `\crefrangeformat` and `\Crefrangeformat`. Like `\crefformat` and `\Crefformat`, the commands take two arguments: the cross-reference type, and the formatting code.

```
\crefrangeformat{\langle type \rangle}{\langle format \rangle}
\Crefrangeformat{\langle type \rangle}{\langle format \rangle}
```

The same comments apply as in the case of single cross-references: the `\langle type \rangle` is usually the name of the counter, except for appendices, labels with explicitly overridden types, and theorem-like environments when `ntheorem` is loaded. Again, if the other-capitalisation variant is not already defined, it will be defined automatically.

The `\langle format \rangle` argument can again be any valid L^AT_EX code, with fragile commands `\protected`. However, this time it should contain *six* arguments, #1–#6. The first two (#1 and #2) are the formatted versions of the label counters, the next two (#3 and #4) are used to mark the beginning and end of the hyper-link for the first cross-reference, and the final two (#5 and #6) mark the beginning and end of the second cross-reference’s hyper-link.

As an example,

```
\crefrangeformat{equation}{\text{eqs. } \text{\textlangle} \langle counter1 \rangle \text{\textrangle} \text{ to } \text{\textlangle} \langle counter2 \rangle \text{\textrangle}}
```

would type-set equation reference ranges as

```
eqs. (\langle counter1 \rangle) to (\langle counter2 \rangle)
```

with the counters (excluding the brackets) forming the hyper-links.

6.2.3 Multiple Cross-References

`\crefmultiformat` `\Crefmultiformat` `\crefrangemultiformat` `\Crefrangemultiformat` The format for multiple cross-references is defined by `\crefmultiformat` and `\Crefmultiformat`, and that of reference ranges within multiple cross-references by `\crefrangemultiformat` and `\Crefrangemultiformat`. Multi-references also require *all* the other cross-reference formats to be defined (see Sections 6.2.1 and 6.2.2), including the single reference range formats, even if you never use the `\crefrange` and `\Crefrange` commands.

The commands all take five arguments: the cross-reference type, the format for the first cross-reference in a list, the format for the second cross-reference in a list of two, the format for the middle cross-references in a list of more than two, and the format for the last cross-reference in a list of more than two.

```
\crefmultiformat{\type}{\first}{\second}{\middle}{\last}
\Crefmultiformat{\type}{\first}{\second}{\middle}{\last}
\crefrangemultiformat{\type}{\first}{\second}{\middle}{\last}■
\Crefrangemultiformat{\type}{\first}{\second}{\middle}{\last}■
```

The `\<type>` is, as ever, the counter name, except for appendices, explicitly overridden label types, and theorem-like environments then the `ntheorem` package is loaded. The same considerations apply to the formatting arguments `\<first>`, `\<second>`, `\<middle>` and `\<last>` as for the `\<format>` argument of `\crefformat` or `\crefrangeformat`, including the meaning of the arguments that should appear in the formatting code (#1, #2 and #3 for `\crefmultiformat` and `\Crefmultiformat`, #1–#6 for `\crefmultiformat` and `\Crefmultiformat`). However, when the corresponding other-capitalisation variant is automatically defined, only the first letter of the `\<first>` argument is upper- or lower-cased; the other arguments are defined to be identical for both variants.

Be careful to get the spaces at the beginning and end of the formatting code correct: the `\<first>` and `\<second>`, or `\<first>`, `\<middle>` and `\<last>`, L^AT_EX code is typeset one after another in a multi-reference, with no space separating them. You may or may not want spaces at the beginning and end of the formatting code, depending on the formatting you desire. For example, in the default equation format:

```
\crefmultiformat{equation}{eqs.\~{#2\#1\#3}}%
{ and\~{#2\#1\#3}}{, (\#2\#1\#3){ and\~{#2\#1\#3}}}
```

the `\<middle>` argument should *not* have a space at the beginning, whereas the `\<second>` and `\<last>` arguments *should* have a space.

6.3 Language and babel support

`cleveref` supports different languages via package options, in the usual way, though not all languages are supported yet.⁸ The `babel` package is also supported when it is loaded, allowing you to change language using the `babel` language switching commands such as `\selectlanguage` and `\foreignlanguage`.

The `babel` support works by redefining the cross-reference names and conjunctions for the default cross-reference types. Any customisations you make to the default cross-reference names and conjunctions *in the preamble* apply to the main language (i.e. the last language listed in the options). A `\selectlanguage` command or similar will override these customisations, replacing them with the defaults for the new language. If you later use `\selectlanguage` to switch back to the main language, your customisations will be restored. If you want to customise cross-reference names or conjunctions for any language other than the main one, you either have to explicitly redefine them after every language switching command, or hook the redefinitions into `babel`'s language switching mechanism. (See Section 12.13 and the `babel` package documentation.)

⁸Contributions of translations for missing languages are very welcome! See Section 12.13 for information on how to contribute translations.

If you have defined formats for new cross-reference types for which no defaults are provided, then you’re on your own. `cleveref` will not know how to redefine them for other languages, and again you will have to take care of it yourself, either by explicitly redefining them in your document after each language switch, or by hooking the redefinitions into `babel`’s language switching mechanism.

On the other hand, since the language switching commands only modify the cross-reference components, if you use the low-level customisation commands to take full control of the format for a particular cross-reference type, then (unless you’re careful) you take it out of the control of `babel` entirely. If you want to use the low-level customisation commands, but *do* still want the language switching commands to work, then you have to use the component macros in your customised formats. The cross-reference names are stored in macros called `\cref@\meta{type}@name`, `\Cref@\meta{type}@name`, `\cref@\meta{type}@name@plural`, and `\Cref@\meta{type}@name@plural`. (Note that since these macro names contain the “@” character, you must use `\makeatletter` and `\makeatother` to access them.)

For example, if you wanted to redefine the equation format so that the cross-reference name (“equation”) was also part of the hyper-link, but you still want to be able to switch language using `babel`, you would need something like:

```
\makeatletter
\crefformat{equation}{#2\cref@equation@name~(#1)#3}
...
\makeatother
```

and similarly for `\crefrangeformat`, `\crefmultiformat`, `\Crefformat`, etc.

7 Overriding the Cross-Reference Type

`\label` As described previously, a label’s “type” is usually determined by its counter, or in the case of `ntheorem` theorem-like environments by the environment name. Occasionally, you may want to override the cross-reference type for a particular label. You can do this by supplying the desired type as an optional argument to the `\label` command:

```
\label[<type>]{<label>}
```

One circumstance in which is useful is when you want to define a special cross-reference format for certain labels of a given type. By supplying a type that doesn’t already exist as the optional argument to `\label`, you can then define the cross-reference format for that new type in whatever way you like, without affecting other cross-references of the same type. For example, if a particular equation contains multiple expressions and you want it to always be referred to in the plural, you could use:

```
\crefname{pluralequation}{eqs.}{eqs.}
...
\label[pluralequation]{eq1}
```

You can of course reuse this format for other plural equations, too.

If you need to do this frequently, it can become tedious specifying the label explicitly each time. An alternative is to use the `aliascnt` package. This lets you define one counter to be an alias for another, so that effectively the same counter has two names. Since `cleverref` determines the label type from the counter name, the two counter aliases can have different cross-reference formats whilst really being the same counter. You have to somehow arrange for the correct counter alias to be used depending on which cross-reference format you want (probably by defining two variants of the environment in question). But the effort involved might be worth the convenience of not having to remember to pass an explicit optional argument to a large number of labels.

You can use this trick to get different cross-reference formats for different theorem-like environments, *without* using the `ntheorem` package.⁹ For example,

```
\usepackage{aliascnt}
\usepackage{cleverref}
\newaliascnt{lemma}{theorem}
\newtheorem{lemma}[lemma]{Lemma}
\aliascntresetthe{lemma}
\crefname{lemma}{lemma}{lemmas}
```

8 Poor Man's `cleverref`

Sometimes you may need to send your L^AT_EX source to someone who can't or won't install the `cleverref` package themselves. For example, many academic journals accept papers in L^AT_EX format, but only support a small subset of the packages available on CTAN. The `poorman` option was designed specifically to help in this situation.

When the `poorman` option is supplied, your document will be processed as normal. But in addition, a `sed` script will automatically be written, containing rules for replacing all the `\cref` commands with the L^AT_EX code that they would produce, and using the standard `\ref` command to produce the cross-references themselves. I.e. the script rewrites your document as you would have done if you had had to do it manually!

The advantage, of course, is that you *don't* have to do it manually. Instead, you can use all the features of `cleverref`, and once you've created a version of your document that you want to send elsewhere, you can process it through the `sed` script to completely remove the `cleverref` dependency. The recipient won't even realise you used `cleverref`!

The `sed` script is written to the same directory as the (main) L^AT_EX source file, and given the same name as that source file but with the extension `.sed`. To process your document through the script, all you need to do is run the following from your shell:

⁹This trick seems to belong to L^AT_EX mythology, and certainly isn't my own idea! But I haven't been able to definitively track down who originally came up with it.

```
sed -f <name>.sed <name>.tex ><newname>.tex
```

where `<name>` is the name of the file containing your L^AT_EX source file minus the `.tex` extension, and `<newname>` is whatever you want to call the new version. *Do not* make `<newname>` the same as `<name>`: it won't work. (It's in any case wise to keep the original L^AT_EX source file containing the `cleveref` commands, in case you need to produce an updated version of your document in the future. Think of the `<newname>.tex` file in the same way as a DVI file: something you can always reproduce from the original source.)

If your document is composed of a number of separate L^AT_EX source files, combined with `\include` commands, only one `sed` script will be generated, but you will need to run *each* source file through that *same* script (and probably modify the `\include` commands to match the new file names). However, using `babel`'s language switching commands in a document split across multiple separate source files is beyond the capabilities of the `poorman` option. You will almost certainly need to manually tweak the `sed` script in that case.

Note that the `poorman` script cannot fully reproduce the type-setting of the original `cleveref` cross-references in all cases.¹⁰ In particular, any customisation of hyper-links will be lost, and if you're using `varioref` with the `legacyvarioref` option (see Section 9, the spacing before the `\vref` command will not be correct.

9 Interaction with Other Packages

The `cleveref` package *must* be loaded *after* all other packages that don't specifically support it,¹¹ i.e. the

```
\usepackage{cleveref}
```

line should always be the last `\usepackage` command in your document's preamble.

Since `cleveref` redefines many internal commands involved in L^AT_EX's cross-referencing system, it can interact badly with other packages that do the same. `cleveref` implements a significantly enhanced version of the features found in the `fancyref` package, `ntheorem`'s `thref` option, and `varioref`'s `\labelformat` command. Although these features may (or may not) work correctly alongside `cleveref`, there is no good reason to use these when using `cleveref`, and their use is unsupported. (Note that `varioref` is fully supported by `cleveref`, just that `cleveref`'s features supersede `varioref`'s `\labelformat` feature.)

`\thref` In fact, if `ntheorem` is loaded with the `thref` option, `cleveref` redefines `ntheorem`'s `\thref` command for you, to be an alias for `\cref`. Similarly, if `varioref` is loaded, `cleveref` redefines the `\vref`, `\vrefrange`, `\fullref` commands and variants to instead use the `cleveref` features for cross-reference formatting, whilst retaining all the `varioref` page-referencing magic. You

¹⁰At least, not without resorting to inserting low-level L^AT_EX code in your document, which would somewhat defeat the purpose of the `poorman` option.

¹¹At the time of writing, I'm not aware of any that do.

can continue to use the other `variorref` and `ntheorem` commands (other than `\labelformat` and the `thref` option) whilst using `cleveref`, as long as `cleveref` is loaded *last*.

`\vref*`
`\Vref*`
`\vrefrange*`
`\Vrefrange*`
`\fullref*`
`\Fullref*`

Note that, whilst in the business of redefining the `variorref` commands, `cleveref` seizes the opportunity to get rid of the irritating spacing behaviour of the `\vref` and `\Vref` commands, instead making it consistent with the other `cleveref` cross-referencing commands. This also frees up the starred variants to be used to suppress hyper-links when the `hyperref` package is loaded, as usual. (Unfortunately, due to lack of support for this in `variorref`, the page references will still be hyper-links, even when using the starred variants. Go bug the `variorref` maintainer about this if you don't like it.)

`legacyvariorref`

However, the `cleveref` redefinitions break strict compatibility with the original `variorref` commands. If you need the original spacing behaviour for compatibility reasons, pass the `legacyvariorref` option to `cleveref`. If this option is supplied, only the original `variorref` commands `\vref`, `\vref*`, `\vrefrange` and `\fullref` will be provided, not any of the additional variants, and the starred variants will change the spacing around the commands as per the original `variorref` implementation, rather than suppressing hyper-links.

`cleveref` should now be compatible with the `memoir` class, as well as with the `titleref`, `nameref` and `byname` packages, and `hyperref`'s `backref` option. This support is quite new, however, so expect some niggles and please report any bugs you encounter. Other packages which alter the L^AT_EX referencing system may or may not work properly with `cleveref`. See Section 10 for additional information.

10 Known Bugs and Possible Improvements

10.1 Known Bugs, Non-Bugs, and Work-Arounds

In no particular order:

- When both the `amsmath` and `hyperref` packages are loaded at the same time, the `cleveref` cross-referencing commands do not work when used within section titles. If anyone can figure out why, let me know! As a work-around, use `\ref` within section titles when your document uses both `amsmath` and `hyperref`.
- `cleveref` will not work properly with the standard L^AT_EX `eqnarray` environment. There is no intention to fix this. The `eqnarray` environment is poorly implemented, making it difficult to get it to work properly with `cleveref`. You're better off using the `amsmath` replacements in any case, such as `gather`, `align`, `multiline` and `split`, which *do* work properly with `cleveref`. (See <http://www.tug.org/pracjourn/2006-4/madsen/>).
- `cleveref` doesn't include support for all languages yet. Please contribute translations for missing languages!¹²

¹²See Section 12.13 for information on how to contribute translations.

- `cleveref` can't cope with active characters being present in cross-reference label names. For example, if French `babel` support is loaded, the commonly used “`:`” in label names will often fail, spewing the usual random selection of mysterious `TeX` errors that accompany such deep-seated errors. The solution is to avoid using active characters in label names. (You may need to consult e.g. the `babel` documentation to discover which active characters are defined in your language.)
- `cleveref` assumes that counters are only ever reset by the standard sectioning commands (`\chapter`, `\section`, etc.). If this is not the case, the automatic compression of consecutive cross-references into a reference range may be incorrect. Making this more flexible would be a simple task, but so far there doesn't seem to be much need for it.
- `cleveref` doesn't know about the `subfloat` package, so you have to revert to using `\ref` for cross-references to sub-figures. (This should be fixed in a future version.)
- The `poorman` `sed` script loses any custom `cleveref` hyper-link formatting you might have defined, and does not reproduce the original spacing around the `\vref` command when `varioref` is used with the `legacyvarioref` option. This is not a bug; it is a side-effect of the intended purpose of the `poorman` option. The philosophy behind `poorman` is to replace `cleveref`'s enhanced cross-referencing with standard `LATEX` cross-reference commands that are guaranteed to work with any standard `LATEX` installation. Although it would be simple to fix these “bugs”, it's almost certainly impossible without using low-level `LATEX` code that is unlikely to be supported by journals, thereby defeating the whole purpose of the `poorman` option.

10.2 Possible Improvements

In no particular order:

- The `poorman` option could be enhanced to allow a choice of scripting language rather than just `sed` (e.g. `awk`, `perl`, ...?), but these are unlikely to be much better for those apt to complain about the use of `sed`. The portable option would be to output a `TeX` “script”, but this would be *much* more work¹³ than I'm prepared to invest.

11 Thanks

A number of people have helped improve `cleveref` by contributing code and translations. Thanks to Michael Ummels for contributing the `amsthm` support code, and to Stefan Pinnow, Gonzalo Medina, Massimo Redaelli, Philip Hölzenspies and

¹³`LATEX` *really* isn't suited to that kind of pattern matching task – just take a look at the code for escaping regexp special characters in this package!

Aleksander Gorohovski for contributing translations. Many people have suggested improvements or reported bugs, indeed many have put significant effort into helping investigate and fix them. So thanks (in alphabetical order) to: Aleksander Gorohovski, Anand Deopurkar, Arne Meier, Bas Ploeger, Dan Luecking, David Gleich, Denis Bitouzé, Domenic Denicola, Donald Arsenau, Hendrik Maryns, James Sharam, Jens Mueller, Joel C. Salomon, Joris Pinkse, Leo Shidai Liu, Lev Bishop, Matej Batic, Matthew Skala, Michael Barber, Michael Gorven, Michal Kaut, Olivier Roy, Paul Gomme, Ricardo de Aldama Sánchez, Stefan Pinnow, Ted Pavlic, Thomas Arildsen, and Uwe Lück for their help. (If I missed you out, please let me know!)

12 Implementation

Essentially, the core of the implementation consists of causing an extra piece of information – the label “type” – to be written to the aux file, and defining `\cref` commands which use this extra information to type-set the reference.

The least invasive implementation of this kind of thing seems to be that used by the `varioref` package. Namely, to redefine the `\refstepcounter` command so that the `\@currentlabel` macro, which usually just contains the type-set version of the counter, now contains the additional type information.

However, even less invasive than `varioref`’s implementation is to leave `\@currentlabel` alone, and define a new `\cref@currentlabel` macro to hold the extra information. (In fact, we store three extra pieces of information: the type, the counter value itself, and the value of the counter that causes the label’s counter to be reset, which we call the “prefix” from now on.) `\@currentlabel` eventually gets written to the aux file as an argument to `\newlabel` by the usual L^AT_EX label mechanisms. In order to get the information in `\cref@currentlabel` into the aux file, we also have to redefine the `\label` macro so that it writes *two* `\newlabel` lines to the aux file for *each* label: the standard one, plus an additional one which contains the extra information in `\cref@currentlabel`. The additional `\newlabel` line has the prefix `cref@` added to the label name. Thus the extra information in `\cref@currentlabel` will end up in `\r@cref@<label>` when the aux file is re-read on the next pass.

Doing things this way involves less hacking to get everything else working again, since the standard cross-reference mechanism and `\ref` command are left entirely intact. `cleveref` can then do what it likes with its own parallel set of labels, without getting in the way of other packages that play around with the cross-reference mechanism. The only downside is the additional memory resources this uses, but on modern T_EX implementations this is unlikely to be a problem.

12.1 Redefinitions of L^AT_EX kernel macros

`\refstepcounter`
`\cref@currentlabel`
`\cref@old@refstepcounter`

We store the original `\refstepcounter` in `\cref@old@refstepcounter`, then redefine `\refstepcounter` so that it first calls the old version to define the standard `\@currentlabel` macro, before defining `cleveref`’s `\cref@currentlabel`, which contains the extra information. The new `\refstepcounter` can take an optional argument, which overrides the default “type” stored in `\cref@currentlabel`, which is otherwise inferred from the counter.

```
1 \def\cref@currentlabel{}  
2 \let\cref@old@refstepcounter\refstepcounter  
3 \def\refstepcounter{  
4   \@ifnextchar[\{\refstepcounter@optarg\}{\refstepcounter@noarg}]  
5 }  
6 \def\refstepcounter@noarg#1{  
7   \cref@old@refstepcounter{#1}  
8   \cref@constructprefix{#1}{\@result}  
9   \protected@edef\cref@currentlabel{%
```

```

10      [#1] [\arabic{#1}] [\@result]%
11      \csname p@#1\endcsname\csname the#1\endcsname}%
12 \def\refstepcounter@optarg[#1]#2{%
13   \cref@old@refstepcounter{#2}%
14   \cref@constructprefix{#2}{\@result}%
15   \protected@edef\cref@currentlabel{%
16     [#1] [\arabic{#2}] [\@result]%
17     \csname p@#2\endcsname\csname the#1\endcsname}%

```

\@footnotetext Footnotes don't use the \refstepcounter mechanism, but instead set \cref@currentlabel directly in \@footnotetext or \mpfootnotetext. We modify these to make them also set \cref@currentlabel appropriately.

```

18 \let\cref@old@footnotetext\@footnotetext
19 \let\cref@old@mpfootnotetext\mpfootnotetext
20 \def\@footnotetext#1{%
21   \cref@constructprefix{footnote}{\@result}%
22   \protected@edef\cref@currentlabel{%
23     [footnote] [\arabic{footnote}] [\@result]\p@footnote\@thefnmark}%
24   \cref@old@footnotetext{#1}}
25 \def\@mpfootnotetext#1{%
26   \cref@constructprefix{mpfootnote}{\@result}%
27   \protected@edef\cref@currentlabel{%
28     [footnote] [\arabic{mpfootnote}] [\@result]\p@footnote\@thefnmark}%
29   \cref@old@mpfootnotetext{#1}}

```

\label We redefine the \label command to make it define *two* labels each time it's called: the standard one, and an additional cleveref-specific one with the prefix \cref@ added to the label name, which contains the extra information from \ref@currentlabel. We call the original \label command, stored in \cref@old@label, to write the standard label to the aux file. However, to avoid other packages messing around with the content of the parallel set of cleveref-specific labels, we write those directly to the aux file ourselves. We also allow \label to take an optional argument which overrides the default reference type in \cref@currentlabel.

The redefinition of \label has to be postponed until the beginning of the document because some other packages postpone their own \label redefinitions too, and we need to override their redefinitions.

```

30 \AtBeginDocument{%
31   \let\cref@old@label\label
32   \def\label{\@ifnextchar[\label@optarg\label@noarg}%
33   \def\label@noarg#1{%
34     \@bsphack%
35     \cref@old@label{#1}%
36     \protected@write\@auxout{}{%
37       \string\newlabel{\cref@#1}{\cref@currentlabel\thepage}}%
38     \@esphack}%
39   \def\label@optarg[#1]#2{%
40     \@bsphack%

```

```

41   \cref@old@label{#2}%
42   \protected@edef\cref@currentlabel{%
43     \expandafter\cref@override@label@type%
44     \cref@currentlabel@nil{#1}}%
45   \protected@write\@auxout{}{%
46     {\string\newlabel{\cref@#2}{\cref@currentlabel}{\thepage}}%
47   \esphack}%

```

- amsmath**
- \label** The **amsmath** package redefines the `\label` command within equation environments, so if it is loaded we have to extend the behaviour to support the optional argument. With **amsmath**, the original `\label` command is stored in `\ltx@label`, and `\label@in@display` replaces `\label` inside equations. `\label@in@display` just saves the label for later, and defining it is left until the end of the equation, when `\ltx@label` is finally called.

To allow `\label` within equations to support an optional argument, we first store the original `\label@in@display` and the new `\label` macro we defined above (since `\label` will be clobbered inside equations). Then we redefine `\label@in@display` so that it wraps all its arguments, including any optional argument, in an extra set of braces. These are stripped away again by `\ltx@label` before calling the `\label` macro we defined above (saved in `\cref@label`).

```

48  \@ifpackageloaded{amsmath}{%
49    \let\cref@label\label
50    \let\cref@old@label@in@display\label@in@display
51    \def\label@in@display{%
52      \@ifnextchar[\label@in@display@optarg\label@in@display@noarg}%
53      \def\label@in@display@noarg#1{\cref@old@label@in@display{#1}}%
54      \def\label@in@display@optarg[#1]{%
55        \cref@old@label@in@display{[#1]}%
56      \def\ltx@label#1{\cref@label#1}

```

- \measure@** The **amsmath** multi-line equation environments scan their bodies twice: once to measure, once to type-set. In the measure phase, the `\label` command is disabled by letting it to `\@gobble`. Unfortunately, this won't gobble all the arguments if an optional argument is supplied to `\label`, so we have to modify the **amsmath** measuring commands so that they let `\label` to `\@gobble@optarg` instead.

Unfortunately, **amsmath** wasn't designed with redefinitions of `\label` in mind, so there appears to be no safe way of doing this other than copying the **amsmath** definitions and making the modification directly in the macro's code. This is a recipe for future chaos if these commands are ever modified in a new version of **amsmath**, but it seems we have no choice. Luckily, **amsmath** isn't updated too often!

```

57 \def\measure@#1{%
58   \begingroup
59     \measuring@true
60     \global\eqnshift@\z@
61     \global\alignsep@\z@
62     \global\let\tag@lengths\empty
63     \global\let\field@lengths\empty

```

```

64      \savecounters@
65      \global\setbox0\vbox{%
66          \let\math@cr@@@\math@cr@@@align@measure
67          \everycr{\noalign{\global\tag@false
68              \global\let\raise@tag\empty \global\column@{z0}}}
69          \let\label@gobble@optarg% << cleveref modification
70          \global\row@{z0}
71          \tabskip{z0}
72          \halign{\span\align@preamble\crlf
73              #1%
74              \math@cr@@@
75              \global\column@{z0}
76              \add@amps\maxfields@\cr
77          }%
78      }%
79      \restorecounters@
80      \ifodd\maxfields@
81          \global\advance\maxfields@{one}
82      \fi
83      \ifnum\xatlevel@=\tw@%
84          \ifnum\maxfields@<\thr@@%
85              \let\xatlevel@{z0}
86          \fi
87      \fi
88      \setbox{z0}\vbox{%
89          \unvbox{z0} \unpenalty \global\setbox{one}\lastbox
90      }%
91      \global\totwidth@{wd}{one}
92      \if@fleqn \global\advance\totwidth@{@mathmargin} \fi
93      \global\let\maxcolumn@widths\empty
94      \begingroup
95          \let\or\relax
96          \loop
97              \global\setbox{one}\hbox{%
98                  \unhbox{one} \unskip \global\setbox\thr@@\lastbox
99              }%
100             \ifhbox\thr@@
101                 \xdef\maxcolumn@widths{ \or \the\wd\thr@@ \maxcolumn@widths}%
102             \repeat
103         \endgroup
104         \dimen@{displaywidth}
105         \advance\dimen@-\totwidth@
106         \ifcase\xatlevel@
107             \global\alignsep@{z0}
108             \let\minalignsep{z0}
109             \tempcntb{z0}
110             \if@fleqn
111                 \tempcnta{one}
112                 \global\eqnshift@{@mathmargin}
113             \else

```

```

114          \@tempcnta\tw@
115          \global\eqnshift@\dimen@
116          \global\divide\eqnshift@\@tempcnta
117      \fi
118  \or
119      \@tempcntb\maxfields@
120      \divide\@tempcntb\tw@
121      \@tempcnta\@tempcntb
122      \advance\@tempcntb\m@ne
123      \if@fleqn
124          \global\eqnshift@\mathmargin
125          \global\alignsep@\dimen@
126          \global\divide\alignsep@\@tempcnta
127      \else
128          \global\advance\@tempcnta\@ne
129          \global\eqnshift@\dimen@
130          \global\divide\eqnshift@\@tempcnta
131          \global\alignsep@\eqnshift@
132      \fi
133  \or
134      \@tempcntb\maxfields@
135      \divide\@tempcntb\tw@
136      \global\advance\@tempcntb\m@ne
137      \global\@tempcnta\@tempcntb
138      \global\eqnshift@\z@
139      \global\alignsep@\dimen@
140      \if@fleqn
141          \global\advance\alignsep@\mathmargin\relax
142      \fi
143      \global\divide\alignsep@\@tempcntb
144  \fi
145  \ifdim\alignsep@<\minalignsep\relax
146      \global\alignsep@\minalignsep\relax
147  \ifdim\eqnshift@>\z@
148      \if@fleqn\else
149          \global\eqnshift@\displaywidth
150          \global\advance\eqnshift@-\totwidth@
151          \global\advance\eqnshift@-\@tempcntb\alignsep@
152          \global\divide\eqnshift@\tw@
153      \fi
154  \fi
155  \fi
156  \ifdim\eqnshift@<\z@
157      \global\eqnshift@\z@
158  \fi
159  \calc@shift@align
160  \global>tagshift@\totwidth@
161  \global\advance>tagshift@\@tempcntb\alignsep@
162  \if@fleqn
163      \ifnum\xatlevel@=\tw@

```

```

164          \global\advance\tagshift@-\@mathmargin\relax
165      \fi
166  \else
167      \global\advance\tagshift@\eqnshift@
168  \fi
169  \iftagsleft@ \else
170      \global\advance\tagshift@-\displaywidth
171  \fi
172  \dimen@\minalignsep\relax
173  \global\advance\totwidth@\tempcntb\dimen@
174  \ifdim\totwidth@>\displaywidth
175      \global\let\displaywidth@\totwidth@
176  \else
177      \global\let\displaywidth@\displaywidth
178  \fi
179  \endgroup
180 }
181 \def\gmeasure@#1{%
182     \begingroup
183         \measuring@true
184         \totwidth@\z@
185         \global\let\tag@lengths\empty
186         \savecounters@
187         \setbox\@ne\vbox{%
188             \everycr{\noalign{\global\tag@false
189                 \global\let\raise@tag\empty \global\column@\z@}}%
190             \let\label\@gobble% << cleveref modification
191             \halign{%
192                 \setboxz@h{$\m@th\displaystyle{##}$}%
193                 \ifdim\wdz@>\totwidth@
194                     \global\totwidth@\wdz@
195                 \fi
196                 &\setboxz@h{\strut{##}}%
197                 \savetaglength@
198                 \crcr
199                 #1%
200                 \math@cr@@@
201             }%
202         }%
203         \restorecounters@
204         \if@fleqn
205             \global\advance\totwidth@\@mathmargin
206         \fi
207         \iftagsleft@
208             \ifdim\totwidth@>\displaywidth
209                 \global\let\gdisplaywidth@\totwidth@
210             \else
211                 \global\let\gdisplaywidth@\displaywidth
212             \fi
213         \fi

```



```

264          \setbox\z@\hbox{\make@display@tag}%
265          \dimen@\@mathmargin \advance\dimen@-\wd\z@
266          \ifdim\dimen@<\multlinetaggap
267              \dimen@\multlinetaggap
268          \fi
269          \box\z@\hskip\dimen@\relax
270      \fi
271      \endgroup
272      \else
273          \multline@indent
274      \fi
275      \else
276          \multline@indent
277      \fi
278  #1%
279 }

```

subequations In order for `subequations` to be sorted properly, `cleveref` needs to know that the `equation` counter is effectively reset by the `parentequation` counter within the `subequations` environment. This isn't how `amsmath` implements `subequations` (for obvious reasons!), but we harmlessly add the `equation` counter to the `parentequation` counter's reset list *within* `subequations` environments, so that `cleveref`'s sorting mechanism can figure things out. We also harmlessly make sure `parentequation` is reset by the same counter as `equation`.

```

280  \let\cref@old@subequations\subequations%
281  \let\cref@old@endsubequations\endsubequations%
282  \cref@resetby{equation}{\@result}%
283  \ifx\@result\relax\else%
284      \caddtoreset{parentequation}{\@result}%
285  \fi%
286  \renewenvironment{subequations}{%
287      \caddtoreset{equation}{parentequation}%
288      \cref@old@subequations%
289  }{%
290      \gdef\cl@parentequation{}%
291      \cref@old@endsubequations%
292      \setcounter{parentequation}{0}%
293 }

```

\make@df@tag@@ We override the internals of the `amsmath` `\tag` command to add the additional information to the label definition.

```

294  \def\make@df@tag@@#1{%
295      \gdef\df@tag{\maketag@@@{#1}%
296          \def\cref@currentlabel{[equation] [] []#1}}}
297  \def\make@df@tag@@@#1{%
298      \gdef\df@tag{\tagform@{#1}%
299          \toks@\@xp{\p@equation{#1}}%
300          \edef\cref@currentlabel{[equation] [] []\the\toks@}}}
301 }{}% end of \ifpackageloaded{amsmath}

```

```
302 }% end of AtBeginDocument
```

\appendix The \appendix command causes the top-level sectioning commands (\chapter or \section, depending on the document class) to produce appendices instead. Since we want to be able to format references to appendices separately from references to normal top-level sections, we add to the tasks that \appendix does: it redefines \refstepcounter@noarg to exceptionally override the label type for chapters or sections, as appropriate, setting it to “appendix” instead. There are two alternative definitions: one if “section” is the top-level sectioning command, and one if “chapter” fulfils that role.

```
303 \let\cref@old@appendix\appendix
304 \renewcommand\appendix{%
305   \cref@old@appendix%
306   \@ifundefined{chapter}{%
307     \gdef\refstepcounter@noarg##1{%
308       \cref@old@refstepcounter{##1}%
309       \cref@constructprefix{##1}{\@result}}%
310     \ifx\@result\empty%
311       \def\@result{2147483647}%
312     \else%
313       \edef\@result{2147483647,\@result}%
314     \fi%
```

We add a large value to the front of the counter data, to force references to anything in appendices to be sorted after everything else.

```
315   \def\@tmpa{##1}%
316   \def\@tmpb{section}%
317   \ifx\@tmpa\@tmpb%
318     \protected@edef\cref@currentlabel{%
319       [appendix] [\arabic{##1}] [\@result]%
320       \csname p@##1\endcsname\csname the##1\endcsname}%
321   \else%
322     \def\@tmpa{##1}%
323     \def\@tmpb{subsection}%
324     \ifx\@tmpa\@tmpb%
325       \protected@edef\cref@currentlabel{%
326         [subappendix] [\arabic{##1}] [\@result]%
327         \csname p@##1\endcsname\csname the##1\endcsname}%
328     \else%
329       \def\@tmpa{##1}%
330       \def\@tmpb{subsubsection}%
331       \ifx\@tmpa\@tmpb%
332         \protected@edef\cref@currentlabel{%
333           [subsubappendix] [\arabic{##1}] [\@result]%
334           \csname p@##1\endcsname\csname the##1\endcsname}%
335       \else%
336         \protected@edef\cref@currentlabel{%
337           [##1] [\arabic{##1}] [\@result]}%
```

```

338          \csname p@##1\endcsname\csname the##1\endcsname}%
339          \fi%
340          \fi%
341          \fi}%
342      }{%
343      \def\refstepcounter@noarg##1{%
344          \cref@old@refstepcounter{##1}%
345          \cref@constructprefix{##1}{\@result}%

```

Again, the large value added to the front of the counter data forces references to appendix items to be sorted last.

```

346          \ifx\@result\@empty%
347              \def\@result{2147483647}%
348          \else%
349              \edef\@result{2147483647,\@result}%
350          \fi%

```

Override the cross-reference type of sectioning commands.

```

351      \def\@tmpa{##1}%
352      \def\@tmpb{chapter}%
353      \ifx\@tmpa\@tmpb%
354          \protected@edef\cref@currentlabel{%
355              [appendix] [\arabic{##1}] [\@result]%
356              \csname p@##1\endcsname\csname the##1\endcsname}%
357      \else%
358          \def\@tmpa{##1}%
359          \def\@tmpb{section}%
360          \ifx\@tmpa\@tmpb%
361              \protected@edef\cref@currentlabel{%
362                  [subappendix] [\arabic{##1}] [\@result]%
363                  \csname p@##1\endcsname\csname the##1\endcsname}%
364          \else%
365              \def\@tmpa{##1}%
366              \def\@tmpb{subsection}%
367              \ifx\@tmpa\@tmpb%
368                  \protected@edef\cref@currentlabel{%
369                      [subsubappendix] [\arabic{##1}] [\@result]%
370                      \csname p@##1\endcsname\csname the##1\endcsname}%
371              \else%
372                  \def\@tmpa{##1}%
373                  \def\@tmpb{subsubsection}%
374                  \ifx\@tmpa\@tmpb%
375                      \protected@edef\cref@currentlabel{%
376                          [subsubsubappendix] [\arabic{##1}] [\@result]%
377                          \csname p@##1\endcsname\csname the##1\endcsname}%
378                  \else%
379                      \protected@edef\cref@currentlabel{%
380                          [##1] [\arabic{##1}] [\@result]%
381                          \csname p@##1\endcsname\csname the##1\endcsname}%
382                  \fi%
383              \fi%

```

```

384      \fi%
385      \fi}%
386  }%
387 }

```

12.2 Utility Macros

12.2.1 miscelaneous

\@gobble@optarg A basic macro that gobbles one argument plus, if present, one optional argument.

```

388 \def\@gobble@optarg{\@ifnextchar[\@@gobble@optarg\@gobble@orig}%
389 \def\@gobble@orig#1{}%
390 \def\@@gobble@optarg[#1]#2{}%

```

12.2.2 aux file information

\cref@getlabel Define some utility macros for extracting label, type, and counter information from the contents of \cref@currentlabel, as written to the aux file and stored in \r@cref@*label* when this is re-read on the next pass. Some other packages \cref@gettype \cref@getcounter \cref@getprefix commandeer the referencing system to write label information to the aux file for other purposes, and probably use \ref to recover it later. We still want them to work, so our utility macros must cope with the type information being absent. However, since we need them to be fully expandable in various places, and \@ifnextchar is definitely *not* fully expandable, we use the work-around of having the macros store their result in another macro, whose name is passed as the second argument. This other macro *will* then be fully expandable, and can be used e.g. inside an \edef or \csname... \endcsname.

```

391 \def\cref@getlabel#1#2{%
392   \expandafter\let\expandafter\@tmpa\csname r@cref@#1\endcsname%
393   \expandafter\expandafter\expandafter\def%
394     \expandafter\expandafter\expandafter\@tmpa%
395   \expandafter\expandafter\expandafter\def\%
396     \expandafter\expandafter\expandafter\@firstoftwo\@tmpa}%
397   \expandafter\@cref@getlabel\@tmpa\@nil#2}%
398 \def\@cref@getlabel{\@ifnextchar[{}%
399   \@@cref@getlabel{\@cref@getlabel[] [] []}%
400 \def\@@cref@getlabel[#1] [#2] [#3] #4\@nil#5{\def#5{#4}}%
401 \def\cref@gettype#1#2{%
402   \expandafter\let\expandafter\@tmpa\csname r@cref@#1\endcsname%
403   \expandafter\expandafter\expandafter\def%
404     \expandafter\expandafter\expandafter\@tmpa%
405   \expandafter\expandafter\expandafter\def\%
406     \expandafter\expandafter\expandafter\@firstoftwo\@tmpa}%
407   \expandafter\@cref@gettype\@tmpa\@nil#2}%
408 \def\@cref@gettype{\@ifnextchar[{}%
409   \@@cref@gettype{\@cref@gettype[] [] []}%
410 \def\@@cref@gettype[#1] [#2] [#3] #4\@nil#5{\def#5{#1}}%
411 \def\cref@getcounter#1#2{%

```

```

412  \expandafter\let\expandafter\@tmpa\csname r@cref@#1\endcsname%
413  \expandafter\expandafter\expandafter\def%
414    \expandafter\expandafter\expandafter\expandafter\@tmpa%
415    \expandafter\expandafter\expandafter\expandafter{%
416      \expandafter\@firstoftwo\@tmpa}%
417  \expandafter\@cref@getcounter\@tmpa\@nil#2}
418 \def\@cref@getcounter{\@ifnextchar[%
419   \@@cref@getcounter{\@cref@getcounter[] [] []}}
420 \def\@cref@getcounter[#1] [#2] [#3]\#4\@nil#5{\def#5[#2]}
421 \def\cref@getprefix#1#2{%
422  \expandafter\let\expandafter\@tmpa\csname r@cref@#1\endcsname%
423  \expandafter\expandafter\expandafter\def%
424    \expandafter\expandafter\expandafter\expandafter\@tmpa%
425    \expandafter\expandafter\expandafter\expandafter{%
426      \expandafter\@firstoftwo\@tmpa}%
427  \expandafter\@cref@getprefix\@tmpa\@nil#2}
428 \def\@cref@getprefix{\@ifnextchar[%
429   \@@cref@getprefix{\@cref@getprefix[] [] []}}
430 \def\@cref@getprefix[#1] [#2] [#3]\#4\@nil#5{\def#5[#3]}

```

`\cref@override@label@type` is a convenience macro for overriding the label type stored in `\cref@currentlabel`.

`\cref@override@label@type`

```
431 \def\cref@override@label@type[#1] [#2] [#3]\#4\@nil#5[#5] [#2] [#3] #4}
```

`\cref@constructprefix` The `\cref@constructprefix` macro constructs the prefix information stored in `\cref@currentlabel` (retrieved using `\cref@getprefix`). This information consists of the numerical value of each counter that's involved in resetting the label's counter, i.e. it contains the numerical values of the chapter, section, subsection... numbers that (ought to) make up the formatted label produced by `\the(counter)`. E.g. if `\theequation` produces “B.1.3”, this utility macro will return “2,1” (the “3” corresponds to the equation number itself, which is stored separately in `\cref@currentlabel`). The first argument is the counter in question; the return value is stored in the second argument, which should be a macro name.

The real work is done by the recursive `\@cref@constructprefix` macro, which works its way upwards through the counters' reset lists until it reaches a counter that isn't reset by any other.

```
432 \def\cref@constructprefix#1#2{%
433   \cref@stack@init{\@tmpstack} %
```

We fully expand the first argument (the counter name) because sometimes a counter name containing a macro gets passed to us.

```
434  \edef\@tmpa{\noexpand{\noexpand{\#1\noexpand}}}%
435  \expandafter\def\expandafter\expandafter\@tmpa\expandafter{\@tmpa{\#2}}%
436  \expandafter\@cref@constructprefix\@tmpa%
437  \cref@stack@to@list{\@tmpstack}{\@tmpa}%
438  \expandafter\def\expandafter\#2\expandafter{\@tmpa}}
```

```

439 \def\@cref@constructprefix#1#2{%
440   \cref@resetby{#1}{#2}%
441   \ifx#2\relax%
442   \else%
443     \edef\@tmpa{\the\csname c@#2\endcsname}%
444     \expandafter\cref@stack@push\expandafter{\@tmpa}{\@tmpstack}%
445     \edef\@tmpa{{#2}}%
446     \expandafter\expandafter\expandafter\cref@constructprefix%
447       \expandafter\@tmpa\expandafter{\expandafter#2\expandafter}%
448 \fi}

```

\cref@append@toks A basic utility macro for appending tokens to a token register.

```
449 \def\cref@append@toks{\#1\#2{\toks0={\#2}}%  
450   \edef\act{\noexpand#1={\the#1\the\toks0}}%  
451   \act}%
```

12.2.3 Stack data structures

`\cref@stack@init` We treat multiple references, supplied as a comma-separated list to `\cref` or `\Cref`, as a stack structure. So we define some utility macros for manipulating stacks (`\@nil` is used as an end-of-stack delimiter).

```
\cref@stack@push 452 \def\cref@stack@init#1{\def#1{\@nil}}
\cref@stack@topandbottom 453 \def\cref@stack@top#1{\expandafter\cref@stack@top#1}
\cref@stack@add 454 \def\cref@stack@pop#1{\expandafter\cref@stack@pop#1#1}
\cref@stack@to@list 455 \def\cref@stack@pop#1{\expandafter\cref@stack@pop#1#1}
456 \def\cref@stack@pop#1{\expandafter\cref@stack@pop#1#1}
457 \def\cref@stack@push#1#2{%
458   \expandafter\cref@stack@push\expandafter{\#2}{\#1}{\#2}}
459 \def\cref@stack@push#1#2#3{\def#3{\#2,\#1}}
460 \def\cref@stack@pull#1#2{\expandafter\cref@stack@pull#2{\#1}{\#2}}
461 \def\cref@stack@pull#1{\@nil#2#3{\def#3{\#1#2,\@nil}}}
462 \def\cref@stack@to@list#1#2{%
463   \cref@isstackfull{\#1}%
464   \if@cref@stackfull%
465     \expandafter\expandafter\expandafter\def%
466     \expandafter\expandafter\expandafter\expandafter{\#2}%
467     \expandafter\expandafter\expandafter\expandafter{\%}%
468     \expandafter\cref@stack@to@list#1}%
469   \else%
470     \def#2{}%
471   \fi}
472 \def\cref@stack@to@list#1,\@nil{\#1}
473 \def\cref@stack@topandbottom#1#2#3{%
474   \def#2{}%
475   \def#3{}%
476   \cref@isstackfull{\#1}%
477   \if@cref@stackfull%
478     \edef#2{\cref@stack@top{\#1}}%
479   \cref@stack@pop{\#1}%
480 }
```

```

480      \cref@isstackfull{#1}%
481      \@whilesw@if@cref@stackfull\fi{%
482          \edef#3{\cref@stack@top{#1}}%
483          \cref@stack@pop{#1}%
484          \cref@isstackfull{#1}%
485      \fi}
486 \def\cref@stack@add#1#2{%
487     \begingroup%
488         \def\@arg1{#1}%
489         \let\@tmpstack#2%
490         \newif\if@notthere%
491         \nottherettrue%
492         \cref@isstackfull{\@tmpstack}%
493         \@whilesw@if@cref@stackfull\fi{%
494             \edef\@tmpb{\cref@stack@top{\@tmpstack}}%
495             \def\@tmpa{#1}%
496             \ifx\@tmpa\@tmpb%
497                 \cref@stackfullfalse%
498                 \nottherefalse%
499             \else%
500                 \cref@stack@pop{\@tmpstack}%
501                 \cref@isstackfull{\@tmpstack}%
502             \fi}%
503     \expandafter\endgroup%
504     \if@notthere\cref@stack@push{#1}{#2}\fi}

```

\if@cref@stackempty The \cref@isstackempty and \cref@isstackfull macros test whether a stack is empty or full, respectively, and set the corresponding conditionals \cref@isstackempty and \if@cref@stackfull.

```

\cref@isstackfull 505 \newif\if@cref@stackempty
506 \newif\if@cref@stackfull
507 \def\cref@isstackempty#1{%
508     \def\@tmpa{\@nil}%
509     \ifx#1\@tmpa\@cref@stackemptytrue%
510     \else\@cref@stackemptyfalse\fi}
511 \def\cref@isstackfull#1{%
512     \def\@tmpa{\@nil}%
513     \ifx#1\@tmpa\@cref@stackfullfalse%
514     \else\@cref@stackfulltrue\fi}

```

\cref@stack@sort The \cref@stack@sort macro sorts a stack, using the comparison macro passed in the second argument, which we use later to sort lists of references. We use insertion sort despite its $O(n^2)$ scaling because it's simpler to code, and because we're very unlikely to encounter lists of more than ten or so references, so in practice a more complicated $O(n \log n)$ sorting algorithm will very likely be slower anyway in practice.

```

515 \def\cref@stack@sort#1#2{%
516     \begingroup%
517     \cref@stack@init{\@sortstack}%

```

Push first element into sorted stack.

```
518 \edef\@element{\cref@stack@top{#1}}%
519 \expandafter\cref@stack@push\expandafter{\@element}{\@sortstack}%
520 \cref@stack@pop{#1}%
```

If empty elements follow first one, need to add them after it in sorted stack.

```
521 \cref@isstackfull{#1}%
522 \if@cref@stackfull%
523   \edef\@tmpa{\cref@stack@top{#1}}%
524   \@whilesw\ifx\@tmpa\@empty\fi{%
525     \cref@stack@pull{}{\@sortstack}%
526     \cref@stack@pop{#1}%
527     \cref@isstackempty{#1}%
528     \if@cref@stackempty%
529       \let\@tmpa\relax%
530     \else%
531       \edef\@tmpa{\cref@stack@top{#1}}%
532     \fi}%
533 \fi%
```

Process elements from stack.

```
534 \cref@isstackfull{#1}%
535 \@whilesw\if@cref@stackfull\fi{%
536   \edef\@element{\cref@stack@top{#1}}%
537   \cref@stack@pop{#1}%
538 }
```

If empty elements follow current one, need to add them to sorted stack, right after element we're currently dealing with.

```
538 \def\@empties{}%
539 \cref@isstackfull{#1}%
540 \if@cref@stackfull%
541   \edef\@tmpa{\cref@stack@top{#1}}%
542   \@whilesw\ifx\@tmpa\@empty\fi{%
543     \edef\@empties{\@empties,}%
544     \cref@stack@pop{#1}%
545     \cref@isstackempty{#1}%
546     \if@cref@stackempty%
547       \let\@tmpa\relax%
548     \else%
549       \edef\@tmpa{\cref@stack@top{#1}}%
550     \fi}%
551 \fi%
```

Insert current element into sorted stack, appending any following empty elements.

```
552 \edef\@tmpa{{\expandafter\noexpand\@element}%
553   {\expandafter\noexpand\@empties}%
554   {\noexpand\@sortstack}{\noexpand#2}}%
555 \expandafter\cref@stack@insert\@tmpa%
556 \cref@isstackfull{#1}%
557 \expandafter\endgroup\expandafter%
558 \def\expandafter#1\expandafter{\@sortstack}}
```

```

\cref@stack@insert  \cref@stack@insert{#1}{#2}{#3}{#4} inserts #1 into the appropriate location
in the sorted stack #3 (appending #2 onto the end of #1 when it's inserted), using
the comparison macro #4.
559 \def\cref@stack@insert#1#2#3#4{%
560   \let\@cmp#4%
561   \@cref@stack@insert{}{#1}{#2}{#3}%
562   \cref@stack@pop{#3}%

\@cref@stack@insert  \@cref@stack@insert{#1}{#2}{#3}{#4} prepends #1 to the stack resulting from
inserting #2 (with #3 appended to it) into the sorted stack #4.
563 \def\@cref@stack@insert#1#2#3#4{%
564   \let\@iterate\relax%
565   \cref@isstackempty{#4}%
566   \if@cref@stackempty%
567     \cref@stack@push{#1, #2#3}{#4}%
568   \else%
569     \edef\@tmpa{\cref@stack@top{#4}}%
570     \expandafter\@cmp\expandafter{\@tmpa}{#2}{\@result}%
571     \ifnum\@result=2\relax%
572       \cref@stack@push{#1, #2#3}{#4}%
573     \else%
574       \cref@stack@pop{#4}%
575       \edef\@tmpa{\noexpand#1,\@tmpa{\noexpand#2}}%
576       {\noexpand#3}{\noexpand#4}}%
577     \expandafter\def\expandafter\@iterate\expandafter{%
578       {\expandafter\@cref@stack@insert\@tmpa}%
579     \fi%
580   \fi%
581 \@iterate}

```

12.2.4 Sorting and comparison of counters

\cref@countercmp The \cref@countercmp macro compares two sets of counter data, as returned by \cref@getcounter, and \chardef's its third argument to 0 if they're equal, 1 if the first comes earlier than the second, or 2 if the first comes later than the second. This is used later for sorting references.

```

582 \def\cref@counter@first#1#2@nil{#1}
583 \def\cref@counter@rest#1#2@nil{#2}
584 \def\cref@countercmp#1#2#3{%
585   \begingroup%
586   \def\@tmpa{#1}%

```

In order to ensure empty references end up in the right place when sorting lists of multiple references, we make the comparison macro sorts them before a non-empty reference.

```

587   \ifx\@tmpa\@empty%
588     \def\@result{1}%
589   \else%
590     \def\@tmpa{#2}%

```

```

591      \ifx\@tmpa\@empty%
592          \def\@result{2}%
593      \else%

```

Conversely, undefined references come after everything else.

```

594      \expandafter\ifx\csname r@cref@#1\endcsname\relax%
595          \def\@result{2}%
596      \else%
597          \expandafter\ifx\csname r@cref@#2\endcsname\relax%
598              \def\@result{1}%
599          \else%

```

The real work of comparing two references is done by `\@ceref@countercmp`.

```

600          \ceref@getcounter{#1}{\@counter{a}}%
601          \ceref@getprefix{#1}{\@prefix{a}}%
602          \ceref@getcounter{#2}{\@counter{b}}%
603          \ceref@getprefix{#2}{\@prefix{b}}%
604          \ceref@stack@init{\@countstack{a}}%
605          \expandafter\ceref@stack@push\expandafter%
606              {\@counter{a}}{\@countstack{a}}%
607          \ifx\@prefix{a}\@empty%
608          \else%
609              \expandafter\ceref@stack@push\expandafter%
610                  {\@prefix{a}}{\@countstack{a}}%
611          \fi%
612          \ceref@stack@init{\@countstack{b}}%
613          \expandafter\ceref@stack@push\expandafter%
614              {\@counter{b}}{\@countstack{b}}%
615          \ifx\@prefix{b}\@empty%
616          \else%
617              \expandafter\ceref@stack@push\expandafter%
618                  {\@prefix{b}}{\@countstack{b}}%
619          \fi%
620          \@ceref@countercmp%
621          \fi%
622          \fi%
623          \fi%
624      \fi%
625      \expandafter\endgroup\expandafter%
626      \chardef\expandafter\#3\expandafter=\@result\relax}

```

`\ceref@countercmp` The `\@ceref@countercmp` macro recursively compares counter components until it runs out of components for one of the references, or finds an two corresponding components that are unequal.

```

627 \def\@ceref@countercmp{%
628     \let\@iterate\relax%
629     \ceref@isstackempty{\@countstack{a}}%
630     \if@ceref@stackempty%
631         \ceref@isstackempty{\@countstack{b}}%
632         \if@ceref@stackempty%

```

```

633     \def\@result{0}%
634   \else%
635     \def\@result{1}%
636   \fi%
637 \else%
638   \cref@isstackempty{\@countstackb}%
639   \if@cref@stackempty%
640     \def\@result{2}%
641   \else%
642     \edef\@tmpa{\cref@stack@top{\@countstacka}}%
643     \cref@stack@pop{\@countstacka}%
644     \edef\@tmpb{\cref@stack@top{\@countstackb}}%
645     \cref@stack@pop{\@countstackb}%
646     \ifnum\@tmpa<\@tmpb\relax%
647       \def\@result{1}%
648     \else%
649       \ifnum\@tmpa>\@tmpb\relax%
650         \def\@result{2}%
651       \else%
652         \def\@iterate{\cref@countercmp}%
653       \fi%
654     \fi%
655   \fi%
656 \fi%
657 \iterate}

```

\if@cref@inresetlist We need to be able to determine which counter is used to reset a given counter.
 \cref@isinresetlist Usually, resets are done by sectioning counters, and we assume that to be the
 \cref@resetby case here. \cref@isinresetlist searches through one counter's reset list, stored
 in \cl@⟨counter⟩, to determine whether another counter appears there, and sets
 the new conditional appropriately. \cref@reset@by searches through all the sec-
 tioning counters' reset lists, from lowest-level (subsubsection) to highest (part),
 checking whether the given counter is in the list, and returns the first sectioning
 counter in whose list it appears. (The value is returned by defining its second
 argument, which should be a macro name.)

```

658 \newif\if@cref@inresetlist
659 \def\cref@isinresetlist#1#2{%
660   \begingroup%
661   \def\@counter{#1}%

```

We locally redefine \@elt, which appears at the head of the expansion of
 \cl@⟨counter⟩, so that entries in the reset list end up separated by commas, thus
 can be treated as a stack.

```

662   \def\@elt##1{##1,}%
663   \expandafter\ifx\csname cl@#2\endcsname\relax%
664     \def\cref@resetstack{\@nil}%
665   \else%
666     \edef\cref@resetstack{\csname cl@#2\endcsname\noexpand\@nil}%
667   \fi%

```

```

668     \let\@nextcounter\relax%
669     \cref@isstackfull{\cref@resetstack}%
670     @whilesw@if@cref@stackfull\fi{%
671         \edef\@nextcounter{\cref@stack@top{\cref@resetstack}}%
672         \ifx\@nextcounter\@counter%
673             \cref@stackfullfalse%
674         \else%
675             \let\@nextcounter\relax%
676             \cref@stack@pop{\cref@resetstack}%
677             \cref@isstackfull{\cref@resetstack}%
678         \fi}%
679     \ifx\@nextcounter\relax%
680         \def\@next{\@cref@inresetlistfalse}%
681     \else%
682         \def\@next{\@cref@inresetlisttrue}%
683     \fi%
684     \expandafter%
685     \endgroup%
686     \@next}

```

FIXME: We could easily remove the hard-coded search order in `\cref@resetby` and, say, replace it with a customisable list of counters to search in order. But, so far, I've yet to encounter a need for anything other than the hard-coded default.

```

687 \def\cref@resetby#1#2{%
688     \let#2\relax%

```

If counter in question is `subfigure` or `subtable`, check if it's reset by `figure` or `table`, respectively.

```

689     \def\@tmpa{#1}%
690     \def\@tmpb{subfigure}%
691     \ifx\@tmpa\@tmpb%
692         \cref@isinresetlist{#1}{figure}%
693         \if@cref@inresetlist%
694             \def#2{figure}%
695         \fi%
696     \fi%
697     \def\@tmpa{#1}%
698     \def\@tmpb{subtable}%
699     \ifx\@tmpa\@tmpb%
700         \cref@isinresetlist{#1}{table}%
701         \if@cref@inresetlist%
702             \def#2{table}%
703         \fi%
704     \fi%

```

If counter in question is `equation`, and the counter `parentequation` is defined, check if it's reset by that. The `parentequation` counter is used by `amsmath`'s `subequations` environment. Although `amsmath` doesn't implement `subequations` using counter reset lists, `cleveref`'s `amsmath` support (above) tweaks the reset lists inside `subequations` environments to hook into this mechanism. We should really only check this when `amsmath` is loaded, but checking it anyway might catch other

packages that independently implement amsmath's `subequations` environment (are there any?).

```

705  \@ifundefined{cl@parentequation}{}{%
706    \def\@tmpa{\#1}%
707    \def\@tmpb{equation}%
708    \ifx\@tmpa\@tmpb%
709      \cref@isinresetlist{\#1}{parentequation}%
710      \if@cref@inresetlist%
711        \expandafter\ifnum\c@parentequation=0\else%
712          \def#2{parentequation}%
713        \fi%
714      \fi%
715    \fi}%

```

If counter in question is `enum<x>`, check if it's reset by a higher-level `enum<x>`.

```

716  \def\@tmpa{\#1}%
717  \def\@tmpb{enumii}%
718  \ifx\@tmpa\@tmpb%
719    \def#2{enum}%
720  \fi%
721  \def\@tmpb{enumiii}%
722  \ifx\@tmpa\@tmpb%
723    \def#2{enum}%
724  \fi%
725  \def\@tmpb{enumiv}%
726  \ifx\@tmpa\@tmpb%
727    \def#2{enum}%
728  \fi%
729  \def\@tmpb{enumv}%
730  \ifx\@tmpa\@tmpb%
731    \def#2{enum}%
732  \fi%
733  \def\@tmpb{enum}%
734  \ifx#2\@tmpb%
735    \cref@isinresetlist{\#1}{enumiv}%
736    \if@cref@inresetlist%
737      \def#2{enumiv}%
738    \else%
739      \cref@isinresetlist{\#1}{enumiii}%
740      \if@cref@inresetlist%
741        \def#2{enumiii}%
742      \else%
743        \cref@isinresetlist{\#1}{enumii}%
744        \if@cref@inresetlist%
745          \def#2{enumii}%
746        \else%
747          \cref@isinresetlist{\#1}{enumi}%
748          \if@cref@inresetlist%
749            \def#2{enumi}%
750          \else%

```

```

751           \cref@isinresetlist{#1}{part}%
752           \if@cref@inresetlist%
753               \def#2{part}%
754           \else%
755               \let#2\relax%
756           \fi%
757       \fi%
758   \fi%
759 \fi%
760 \fi%
761 \fi%

```

If we haven't found anything so far, check if it's reset by a sectioning command.

```

762 \ifx#2\relax%
763   \cref@isinresetlist{#1}{table}%
764   \if@cref@inresetlist%
765       \def#2{table}%
766   \else%
767       \cref@isinresetlist{#1}{subsubsection}%
768       \if@cref@inresetlist%
769           \def#2{subsubsection}%
770       \else%
771           \cref@isinresetlist{#1}{subsection}%
772           \if@cref@inresetlist%
773               \def#2{subsection}%
774           \else%
775               \cref@isinresetlist{#1}{section}%
776               \if@cref@inresetlist%
777                   \def#2{section}%
778               \else%
779                   \cref@isinresetlist{#1}{chapter}%
780                   \if@cref@inresetlist%
781                       \def#2{chapter}%
782                   \else%
783                       \cref@isinresetlist{#1}{part}%
784                       \if@cref@inresetlist%
785                           \def#2{part}%
786                       \else%
787                           \let#2\relax%
788                       \fi%
789                   \fi%
790               \fi%
791           \fi%
792       \fi%
793   \fi%
794 \fi}

```

- | | |
|--------------------------------------|---|
| <code>\if@cref@refconsecutive</code> | Define a new conditional to test whether two references are consecutive (needed |
| <code>\cref@isrefconsecutive</code> | when type-setting reference ranges). This uses the counter and prefix (i.e. formatted version of the counter that resets the label's counter) information provided by |

`\r@cref@⟨label⟩` (via the aux file) to check if the prefixes are identical (i.e. the references come from the same chapter, section or whatever), and that the label counters differ by 0 or 1.

```

795 \newif\if@cref@refconsecutive%
796 \def\cref@isrefconsecutive#1#2{%
797   \begingroup%
798   \countdef\refa@counter=0%
799   \countdef\refb@counter=1%
800   \cref@getcounter{#1}{\@result}%
801   \refa@counter=\@result%
802   \cref@getcounter{#2}{\@result}%
803   \refb@counter=\@result%
804   \cref@getprefix{#1}{\refa@prefix}%
805   \cref@getprefix{#2}{\refb@prefix}%
806   \def\@after{\@cref@refconsecutivefalse}%
807   \ifx\refa@prefix\refb@prefix%
808     \ifnum\refa@counter=\refb@counter\relax%
809       \def\@after{\@cref@refconsecutivetrue}%
810     \else%
811       \advance\refa@counter 1\relax%
812       \ifnum\refa@counter=\refb@counter\relax%
813         \def\@after{\@cref@refconsecutivetrue}%
814       \fi%
815     \fi%
816   \fi%
817   \expandafter\endgroup\@after}

```

12.2.5 Reference stack processing

`\cref@processgroup` `\cref@processgroup` processes the first group of references from the stack passed in argument #1, by moving references to the stack passed in argument #2 until it encounters a reference that has a different type to those that came before. Note that empty references are treated as having the same type as the preceding one.

```

818 \def\cref@processgroup#1#2{%
819   \edef\@nextref{\cref@stack@top{#1}}%
820   \expandafter\ifx\csname r@cref@\@nextref\endcsname\relax%
821   \def\@grouptype{\@undefined}%
822   \def\@groupformat{\@undefined}%
823   \else%
824   \expandafter\cref@gettype\expandafter{\@nextref}{\@grouptype}%
825   \expandafter\expandafter\expandafter\def%
826   \expandafter\expandafter\expandafter\@groupformat%
827   \expandafter\expandafter\expandafter\expandafter\%%
828   \csname r@cref@\@grouptype @format\endcsname%
829   {\@dummya}{\@dummyb}{\@dummyc}}%
830   \fi%
831   \let\@nexttype\@grouptype%
832   \let\@nextformat\@groupformat%
833 %

```

```

834  \@whilesw\ifx\@nextformat\@groupformat\fi{%
835    \expandafter\cref@stack@pull\expandafter{\@nextref}{#2}%
836    \cref@stack@pop{#1}%
837    \cref@isstackempty{#1}%
838    \if@cref@stackempty%
839      \let\@nexttype\relax%
840      \let\@nextformat\relax%
841    \else%
842      \edef\@nextref{\cref@stack@top{#1}}%
843      \ifx\@nextref\@empty%
844        \let\@nexttype\@grouptype%
845        \let\@nextformat\@groupformat%
846      \else%
847        \expandafter\ifx\csname r@cref@\@nextref\endcsname\relax%
848          \def\@nexttype{\@undefined}%
849          \def\@nextformat{\@undefined}%
850        \else%
851          \expandafter\cref@gettype\expandafter%
852            {\@nextref}{\@nexttype}%
853          \def\@tmpa{\@undefined}%
854          \ifx\@nexttype\@tmpa%
855            \def\@nextformat{\@undefined}%
856          \else%
857            \expandafter\expandafter\expandafter\def%
858              \expandafter\expandafter\expandafter\@nextformat%
859              \expandafter\expandafter\expandafter{%
860                \csname cref@\@nexttype @format\endcsname%
861                {\@dummya}{\@dummyb}{\@dummyc}}%
862            \fi%
863            \fi%
864            \fi%
865          \fi}%
866 }

```

\cref@processgroupall \cref@processgroupall processes the first group of references from the stack passed in argument #1, by moving all references with the same type as the first one into the stack passed in argument #2.

```

867 \def\cref@processgroupall#1#2{%
868   \cref@stack@init{\@tmpstack}%
869   \edef\@nextref{\cref@stack@top{#1}}%
870   \expandafter\ifx\csname r@cref@\@nextref\endcsname\relax%
871     \def\@grouptype{\@undefined}%
872     \def\@groupformat{\@undefined}%
873   \else%
874     \expandafter\cref@gettype\expandafter{\@nextref}{\@grouptype}%
875     \expandafter\expandafter\expandafter\def%
876       \expandafter\expandafter\expandafter\@groupformat%
877       \expandafter\expandafter\expandafter{%
878         \csname cref@\@grouptype @format\endcsname%
879         {\@dummya}{\@dummyb}{\@dummyc}}%

```

```

880   \fi%
881   \let\@lasttype\@groupype%
882   \let\@lastformat\@groupformat%
883   \cref@isstackfull{#1}%
884 %
885   \@whilesw\if@cref@stackfull\fi{%
886     \edef\@nextref{\cref@stack@top{#1}}%
887     \ifx\@nextref\empty%
888       \ifx\@lastformat\@groupformat%
889         \let\@nexttype\@groupype%
890         \let\@nextformat\@groupformat%
891       \else%
892         \let\@nexttype\relax%
893         \let\@nextformat\relax%
894       \fi%
895     \else%
896       \expandafter\ifx\csname r@cref@\@nextref\endcsname\relax%
897         \def\@nexttype{\@undefined}%
898         \def\@nextformat{\@undefined}%
899       \else%
900         \expandafter\cref@gettype\expandafter%
901           {\@nextref}{\@nexttype}%
902         \def\@tmpa{\@undefined}%
903         \ifx\@nexttype\@tmpa%
904           \def\@nextformat{\@undefined}%
905         \else%
906           \expandafter\expandafter\expandafter\def%
907             \expandafter\expandafter\expandafter\@nextformat%
908             \expandafter\expandafter\expandafter\{%
909               \csname cref@\@nexttype @format\endcsname%
910               {\@dummya}{\@dummyb}{\@dummyc}}%
911             \fi%
912           \fi%
913         \fi%
914 %
915     \ifx\@nextformat\@groupformat%
916       \expandafter\cref@stack@pull\expandafter{\@nextref}{#2}%
917     \else%
918       \expandafter\cref@stack@pull\expandafter{\@nextref}{\@tmpstack}%
919     \fi%
920     \cref@stack@pop{#1}%
921     \let\@lasttype\@nexttype%
922     \let\@lastformat\@nextformat%
923     \cref@isstackfull{#1}%
924     \let#1\@tmpstack}

```

\cref@processconsecutive \cref@processconsecutive processes the first sequence of consecutive references from the stack passed in #1, sets the macro passed as #2 to the first reference in the sequence, sets #3 to the last reference, and sets the counter passed in #4 to

the number of consecutive references in the sequence.

```
925 \def\cref@processconsecutive#1#2#3#4{%
926   #4=0%
927   \edef\@nextref{\cref@stack@top{#1}}%
928   \cref@stack@pop{#1}%
```

If stack only contains one reference, set appropriate return values.

```
929   \cref@isstackempty{#1}%
930   \if@cref@stackempty%
931     \edef#2{\@nextref}%
932     \let#3\relax%
933     #4=1\relax%
```

If stack contains multiple references, find end of consecutive references.

```
934   \else%
935     \edef#2{\@nextref}%
936     \let#3\relax%
937     \edef\@nextref{\cref@stack@top{#1}}%
938     #4=1\relax%
939     \expandafter\ifx\csname r@cref@#2\endcsname\relax%
940       \cref@refconsecutivefalse%
941     \else%
```

If next reference in substack is empty, it indicates that no further compression should take place. Having served its purpose, the empty reference and any consecutive empty references are removed from the stack.

```
942     \ifx\@nextref\empty%
943       \cref@refconsecutivefalse%
944       \whilesw\ifx\@nextref\empty\fi{%
945         \cref@stack@pop{#1}%
946         \cref@isstackempty{#1}%
947         \if@cref@stackempty%
948           \let\@nextref\relax%
949         \else%
950           \edef\@nextref{\cref@stack@top{#1}}%
951         \fi%}
```

Otherwise, test whether next reference is consecutive or not.

```
952   \else%
953     \expandafter\ifx\csname r@cref@\@nextref\endcsname\relax%
954       \cref@refconsecutivefalse%
955     \else%
956       \edef\tmpa{{#2}{\@nextref}}%
957       \expandafter\cref@isrefconsecutive\tmpa%
958     \fi%
959   \fi%
960 \fi%
```

Remove references from the stack until we find end of consecutive sequence.

```
961   \whilesw\if@cref@refconsecutive\fi{%
962     \advance#4 1%
```

```

963      \let#3\@nextref%
964      \cref@stack@pop{#1}%
965      \cref@isstackempty{#1}%
966      \if@cref@stackempty%
967          \cref@refconsecutivefalse%
968      \else%
969          \edef\@nextref{\cref@stack@top{#1}}%

```

If next reference is empty, remove any consecutive empty references and we're done.

```

970      \ifx\@nextref\@empty%
971          \cref@refconsecutivefalse%
972          \@whilsw\ifx\@nextref\@empty\fi{%
973              \cref@stack@pop{#1}%
974              \cref@isstackempty{#1}%
975              \if@cref@stackempty%
976                  \let\@nextref\relax%
977              \else%
978                  \edef\@nextref{\cref@stack@top{#1}}%
979              \fi}%

```

Otherwise, test whether next reference is consecutive or not.

```

980      \else%
981          \expandafter\ifx\csname r@cref@\@nextref\endcsname\relax%
982              \cref@refconsecutivefalse%
983          \else%
984              \edef\@tmpa{{#3}{\@nextref}}%
985              \expandafter\cref@isrefconsecutive\@tmpa%
986          \fi%
987      \fi%
988  \fi}%
989 \fi}

```

12.3 Cross-Referencing Commands

\cref Define the main referencing command `\cref` and the start-of-sentence variant `\Cref`, along with the reference range commands `\crefrange` and `\Crefrange`.

\crefrange 990 `\DeclareRobustCommand{\cref}[1]{\@cref{cref}{#1}}`

\Crefrange 991 `\DeclareRobustCommand{\Cref}[1]{\@cref{Cref}{#1}}`

992 `\DeclareRobustCommand{\crefrange}[2]{\@setcrefrange{#1}{#2}{cref}{}}`

993 `\DeclareRobustCommand{\Crefrange}[2]{\@setcrefrange{#1}{#2}{Cref}{}}`

\if@crefstarred The `\if@crefstarred` flag is set within starred variants of `cleveref` commands. Starred variants are only defined if either the `hyperref` or `variorref` package is loaded, so we only define it in those cases.¹⁴

994 `\@ifpackageloaded{hyperref}{\newif\if@crefstarred}{}`

995 `\@ifpackageloaded{variorref}{\newif\if@crefstarred}{}`

¹⁴In fact, the flag isn't needed when only `variorref` is loaded and the `legacyvariorref` is set, *unless* the `poorman` option is also set. However, avoiding the redundant `\if` in these cases doesn't seem worth the significantly more complicated code that would be required.

\@cref To save duplicating code, the referencing macros pass an argument determining the variant to an auxilliary macro \@cref, which does the real work. The \@cref macro is the behemoth at the heart of all the clever referencing features. It deals with grouping references by type, type-setting the conjunctions between groups, choosing the right formatting macro to use for each reference, and compressing consecutive references into ranges.

```
996 \def\@cref#1#2{%
997   \leavevmode%
998   \begingroup%
```

Initialise some things, and put all the references into a stack called \@refstack. Note that we fully expand the second argument, in case it contains commands that expand to label names rather than label names per se.

```
999  \countdef\count@consecutive=0%
1000 \countdef\count@group=1%
1001 \count@group=1%
1002 \def\cref@variant{\#1}%
1003 \newif\if@secondref%
1004 \cref@stack@init{\@refstack}%
1005 \edef\@tmpa{\#2}%
1006 \expandafter\cref@stack@push\expandafter{\@tmpa}{\@refstack}%
1007 \cref@isstackfull{\@refstack}%
```

Loop until the reference stack is empty.

```
1008 \@whilew\if@cref@stackfull\fi{%
```

Move next group of references with same type into \@refsubstack.

```
1009  \cref@stack@init{\@refsubstack}%
1010  \if@cref@sort%
1011    \cref@processgroupall{\@refstack}{\@refsubstack}%
1012    \cref@stack@sort{\@refsubstack}{\cref@countercmp}%
1013  \else%
1014    \cref@processgroup{\@refstack}{\@refsubstack}%
1015  \fi%
```

Type-set appropriate conjunction between groups of reference types.

```
1016  \ifnum\count@group=1\relax%
1017    \advance\count@group 1%
1018  \else%
1019    \cref@isstackfull{\@refstack}%
1020    \if@cref@stackfull%
1021      \@setcref@middlegroupconjunction%
1022    \else%
1023      \ifnum\count@group=2\relax%
1024        \@setcref@pairgroupconjunction%
1025      \else%
1026        \@setcref@lastgroupconjunction%
1027      \fi%
1028    \fi%
1029  \advance\count@group 1%
```

```

1030      \def\cref@variant{\cref}%
1031      \fi%

```

Process first group of consecutive references.

```

1032      \if@cref@compress%
1033          \cref@processconsecutive%
1034          {\@refsubstack}{\beginref}{\endref}{\count@consecutive}%
1035      \else%
1036          \edef\beginref{\cref@stack@top{\@refsubstack}}%
1037          \cref@stack@pop{\@refsubstack}%

```

Empty references serve no purpose when we're not compressing consecutive references, so we simply remove them.

```

1038      \@whilsw\ifx\beginref\empty\fi{%
1039          \cref@stack@pop{\@refsubstack}%
1040          \cref@isstackempty{\@refsubstack}%
1041          \if@cref@stackempty%
1042              \let\beginref\relax%
1043          \else%
1044              \edef\beginref{\cref@stack@top{\@refsubstack}}%
1045          \fi}%
1046          \let\endref\relax%
1047          \count@consecutive=1\relax%
1048      \fi%

```

If there were no consecutive references, type-set the first reference;

```

1049      \ifnum\count@consecutive=1\relax%
1050          \cref@isstackfull{\@refsubstack}%
1051          \if@cref@stackfull%
1052              \expandafter\@setcref%
1053              \expandafter{\beginref}{\cref@variant}{@first}%
1054          \else%
1055              \expandafter\@setcref%
1056              \expandafter{\beginref}{\cref@variant}{%}
1057          \fi%

```

if there were only two consecutive references, type-set the first one and return the second to the substack (we add an empty reference after it just to make sure there's no further compression);

```

1058      \else%
1059          \ifnum\count@consecutive=2\relax%
1060              \expandafter\@setcref%
1061              \expandafter{\beginref}{\cref@variant}{@first}%
1062              \expandafter\cref@stack@push\expandafter%
1063              {\endref,}{\@refsubstack}%

```

otherwise, type-set a reference range.

```

1064      \else%
1065          \edef\tmpa{\beginref}{\endref}%
1066          \if@cref@stackempty%
1067              \expandafter\@setcrefrange\tmpa{\cref@variant}{%}

```

```

1068      \else%
1069          \expandafter\@setcrefrange\@tmpa{\cref@variant}{@first}%
1070          \fi%
1071          \fi%
1072      \fi%

```

Process further groups of consecutive references, until substack is empty.

```

1073      \if@secondreftrue%
1074          \cref@isstackfull{\@refsubstack}%
1075          \@whilesw\if@cref@stackfull\fi{%
1076              \if@cref@compress%
1077                  \cref@processconsecutive%
1078                  {\@refsubstack}{\@beginref}{\@endref}{\count@consecutive}%
1079          \else%
1080              \edef\@beginref{\cref@stack@top{\@refsubstack}}%
1081              \cref@stack@pop{\@refsubstack}%

```

Empty references serve no purpose when we're not compressing consecutive references, so we simply remove them.

```

1082      \@whilesw\ifx\@beginref\@empty\fi{%
1083          \cref@stack@pop{\@refsubstack}%
1084          \cref@isstackempty{\@refsubstack}%
1085          \if@cref@stackempty%
1086              \let\@beginref\relax%
1087          \else%
1088              \edef\@beginref{\cref@stack@top{\@refsubstack}}%
1089          \fi}%
1090          \let\@endref\relax%
1091          \count@consecutive=1\relax%
1092      \fi%

```

If the substack is now empty, we will need to type-set an “end” reference, otherwise we will need to type-set a “middle” reference.

```

1093      \cref@isstackempty{\@refsubstack}%
1094      \if@cref@stackempty%
1095          \if@secondref%
1096              \def\@pos{@second}%
1097          \else%
1098              \def\@pos{@last}%
1099          \fi%
1100      \else%
1101          \def\@pos{@middle}%
1102      \fi%

```

If there were no consecutive references, just type-set the next reference;

```

1103      \ifnum\count@consecutive=1\relax%
1104          \edef\@tmpa{{\@beginref}{\cref}{\@pos}}%
1105          \expandafter\@setcref\@tmpa%
1106      \else%

```

if there were only two consecutive references, type-set the first one, and return the second one to the substack,

```

1107      \ifnum\count@consecutive=2\relax%
1108          \expandafter\@setcref\expandafter%
1109              {\@beginref}{\cref}{\middle}%
1110          \expandafter\cref@stack@push\expandafter%
1111              {\@endref}{\@refsubstack}%
1112      \else%
1113          \edef\@tmpa{{\@beginref}{\@endref}{\cref}{\@pos}}%
1114          \expandafter\@setcrefrange\@tmpa%
1115      \fi%
1116      \fi%
1117      \@secondreffalse%
1118      \cref@isstackfull{\@refsubstack}%
1119  }% end loop over reference substack
1120  \cref@isstackfull{\@refstack}%
1121 }% end loop over main reference stack
1122 \endgroup

```

\@setcref The internal `\@setcref` macro deals with actually type-setting the reference, by calling the appropriate type-dependent formatting macro defined by `\crefformat` etc.

```

1123 \def\@setcref#1#2#3{%
1124     \expandafter\ifx\csname r@\cref@#1\endcsname\relax%
1125         \protect\G@refundefinedtrue%
1126         \nfss@text{\reset@font\bfseries ??}%
1127         \@latex@warning{Reference '#1' on page \thepage \space undefined}%
1128     \else%
1129         \cref@gettype{#1}{\@temptype}% puts label type in \@temptype
1130         \cref@getlabel{#1}{\@templabel}% puts label in \@templabel
1131         \expandafter\ifx\csname #2@\@temptype\endcsname\relax%
1132             \protect\G@refundefinedtrue%
1133             \nfss@text{\reset@font\bfseries ??}\@templabel%
1134             \@latex@warning{\string\cref \space reference format for label
1135                 type '\@temptype' undefined}%
1136     \else%
1137         \expandafter\@setcref\expandafter%
1138             {\csname #2@\@temptype\endcsname}{#1}%
1139     \fi%
1140 \fi}

```

\@setcref We separate out the very final type-setting step into a separate macro, in order to make it easier to redefine things later to make them work with the `hyperref` package.

```
1141 \def\@setcref#1#2{\cref@getlabel{#2}{\@templabel}#1{\@templabel}{}{}}
```

\@setcrefrange The internal `\@setcrefrange` macro deals with type-setting reference ranges, just as `\@setcref` does for normal references. The actual type-setting is no more complicated in the range case; it's the error checking that makes the code so much

longer. We now have to check whether *two* references are undefined, whether *two* reference formats are undefined, whether the reference types are consistent, and also combinations of these various errors.

```

1142 \def\@setcrefrange#1#2#3#4{%
1143   \begingroup%
    Check if both references are defined.

1144   \expandafter\ifx\csname r@cref@#1\endcsname\relax%
1145     \protect\G@refundefinedtrue%
1146     \G@latex@warning{Reference '#1' on page \thepage \space%
1147       undefined}%
1148     \expandafter\ifx\csname r@cref@#2\endcsname\relax%
1149       \nfss@text{\reset@font\bfseries ??}--%
1150       \nfss@text{\reset@font\bfseries ??}%
1151     \G@latex@warning{Reference '#2' on page \thepage \space%
1152       undefined}%
1153   \else%
1154     \cref@getlabel{#2}{\@labelb}%
1155     \nfss@text{\reset@font\bfseries ??}--\@labelb%
1156   \fi%
1157 \else%
1158   \expandafter\ifx\csname r@cref@#2\endcsname\relax%
1159     \protect\G@refundefinedtrue%
1160     \cref@getlabel{#1}{\@labela}%
1161     \G@labela--\nfss@text{\reset@font\bfseries ??}%
1162     \G@latex@warning{Reference '#2' on page \thepage %
1163       \space undefined}%

```

If both references are defined, check that the reference format is defined.

```

1164   \else%
1165     \cref@gettype{#1}{\@typea}%
1166     \cref@gettype{#2}{\@typeb}%
1167     \cref@getlabel{#1}{\@labela}%
1168     \cref@getlabel{#2}{\@labelb}%
1169     \edef\@format{\expandafter\noexpand%
1170       \csname #3range@\@typea\@format\#4\endcsname}%
1171     \edef\@formatb{\expandafter\noexpand%
1172       \csname #3range@\@typeb\@format\#4\endcsname}%
1173     \expandafter\ifx\@format\relax%
1174       \protect\G@refundefinedtrue%
1175       \nfss@text{\reset@font\bfseries ??}^{\@labela--\@labelb}%
1176       \G@latex@warning{#3\space reference range format for label
1177         type '\@typea' undefined}%
1178     \else%

```

If reference types are identical, type-set reference range, otherwise display warning.
 (Note: there's no need to check if reference format for second type is defined, since if it isn't it will be caught here as a non-identical type.)

```

1179     \ifx\@format\@formatb%
1180       \expandafter\@setcrefrange\expandafter{\@format}{#1}{#2}%

```

```

1181      \else%
1182          \protect\G@refundefinedtrue%
1183          \nfss@text{\reset@font\bfseries ??}~\@labela--\@labelb%
1184          \@latex@warning{Types inconsistent in reference range for
1185              references '#1' and '#2' on page \thepage}%
1186      \fi%
1187      \fi%
1188      \fi%
1189      \fi%
1190  \endgroup}

```

\@@setcrefrange We again separate out the very final type-setting step into a separate macro, in order to make it easier to redefine things later to make them work with the `hyperref` package.

```

1191 \def\@@setcrefrange#1#2#3{%
1192   \cref@getlabel{#2}{\@labela}%
1193   \cref@getlabel{#3}{\@labelb}%
1194   #1{\@labela}{\@labelb}{}{}{}{}}

```

The type-setting of conjunctions is also separated out into separate macros, for the same reason.

```

1195 \def\@setcref@pairgroupconjunction{\crefpairgroupconjunction}
1196 \def\@setcref@middlegroupconjunction{\crefmiddlegroupconjunction}
1197 \def\@setcref@lastgroupconjunction{\creflastgroupconjunction}

```

\namecref Finally, we define `\namecref`, `\nameCref`, `\namecrefs` and `\nameCrefs` commands that return just the type-set name of a reference, without the reference `\namecref` label, which is occasionally useful. They retrieves the reference name from the `\nameCrefs` corresponding `\crefname` or `\Crefname` definition, if these exist.

```

1198 \DeclareRobustCommand{\namecref}[1]{%
1199   \expandafter\ifx\csname r@cref@\#1\endcsname\relax%
1200     \protect\G@refundefinedtrue%
1201     \nfss@text{\reset@font\bfseries ??}%
1202     \@latex@warning{Reference '#1' on page \thepage \space undefined}%
1203   \else%
1204     \cref@gettype{#1}{\@tmpa}%
1205     \@ifundefined{cref@\@tmpa \name}{}{%
1206       \protect\G@refundefinedtrue`‘%
1207       \nfss@text{\reset@font\bfseries ??}%
1208       \@latex@warning{Reference name for label type ‘\@tmpa’ undefined}%
1209     }{\csname cref@\@tmpa \name\endcsname}%
1210   \fi}
1211 \DeclareRobustCommand{\nameCref}[1]{%
1212   \expandafter\ifx\csname r@cref@\#1\endcsname\relax%
1213     \protect\G@refundefinedtrue%
1214     \nfss@text{\reset@font\bfseries ??}%
1215     \@latex@warning{Reference '#1' on page \thepage \space undefined}%
1216   \else%
1217     \cref@gettype{#1}{\@tmpa}%

```

```

1218     \@ifundefined{Cref@\@tmpa @name}{%
1219         \protect\G@refundefinedtrue%
1220         \nfss@text{\reset@font\bfseries ??}%
1221         \@latex@warning{Reference name for label type '\@tmpa' undefined}%
1222     }{\csname Cref@\@tmpa @name\endcsname}%
1223     \fi}
1224 \DeclareRobustCommand{\namecrefs}[1]{%
1225     \expandafter\ifx\csname r@cref@#1\endcsname\relax%
1226         \protect\G@refundefinedtrue%
1227         \nfss@text{\reset@font\bfseries ??}%
1228         \@latex@warning{Reference '#1' on page \thepage \space undefined}%
1229     \else%
1230         \cref@gettype{#1}{\@tmpa}%
1231         \@ifundefined{\cref@\@tmpa @name@plural}{%
1232             \protect\G@refundefinedtrue%
1233             \nfss@text{\reset@font\bfseries ??}%
1234             \@latex@warning{Reference name for label type '\@tmpa' undefined}%
1235         }{\csname cref@\@tmpa @name@plural\endcsname}%
1236     \fi}
1237 \DeclareRobustCommand{\nameCrefs}[1]{%
1238     \expandafter\ifx\csname r@cref@#1\endcsname\relax%
1239         \protect\G@refundefinedtrue%
1240         \nfss@text{\reset@font\bfseries ??}%
1241         \@latex@warning{Reference '#1' on page \thepage \space undefined}%
1242     \else%
1243         \cref@gettype{#1}{\@tmpa}%
1244         \@ifundefined{Cref@\@tmpa @name@plural}{%
1245             \protect\G@refundefinedtrue%
1246             \nfss@text{\reset@font\bfseries ??}%
1247             \@latex@warning{Reference name for label type '\@tmpa' undefined}%
1248         }{\csname Cref@\@tmpa @name@plural\endcsname}%
1249     \fi}

```

12.4 Reference Format Customisation Commands

12.4.1 Format Component Commands

`\cref@label@types` The reference formats are usually constructed out of components defined by the user-level `\crefname`, `\Crefname`, `\creflabel` and `\crefrangelabel` commands. `\cref@label@types` keeps track of label types for which components have been defined, and therefore need constructing at `\begindocument` (see below).

FIXME: we don't check if the label type is already in the list, so some formats may needlessly be redefined identically, multiple times.

```
1250 \cref@stack@init{\cref@label@types}
```

`\crefdefaultlabelformat` The component customisation commands simply use the supplied arguments to define appropriately named macros containing the formatting components. If the corresponding `\Crefname` or `\crefname` variant is not already defined, `\crefname`
`\creflabelformat`
`\crefrangelabelformat`

and `\Crefname` define it to be a version with the first letter capitalised or lower-cased, respectively.

```

1251 \newcommand{\crefdefaultlabelformat}[1]{%
1252   \def\cref@default@label##1##2##3{##1}%
1253 \newcommand{\crefname}[3]{%
1254   \@cerefname{cref}{##1}{##2}{##3}{}}%
1255 \newcommand{\Crefname}[3]{%
1256   \@cerefname{Cref}{##1}{##2}{##3}{}}%
1257 \newcommand{\creflabelformat}[2]{%
1258   \expandafter\def\csname cref@##1@label\endcsname##1##2##3{##2}%
1259   \cref@stack@add{##1}{\cref@label@types}%
1260 \newcommand{\crefrangelabelformat}[2]{%
1261   \expandafter\def\csname cref@##1@rangelabel\endcsname{%
1262     ##1##2##3##4##5##6{##2}}%
1263   \cref@stack@add{##1}{\cref@label@types}}%

```

`\crefname@preamble` The `\crefname@preamble` and `\Crefname@preamble` commands are very like the `\Crefname@preamble` `\crefname` and `\Crefname` commands, but they tag “`@preamble`” onto the end of the generated macro names. They are used when defining the default formats for different languages (see Section 12.13).

```

1264 \newcommand{\crefname@preamble}[3]{%
1265   \@cerefname{cref}{##1}{##2}{##3}{@preamble}%
1266 \newcommand{\Crefname@preamble}[3]{%
1267   \@cerefname{Cref}{##1}{##2}{##3}{@preamble}}%

```

`\@cerefname` The `\@cerefname` utility macro does the real work of defining format names, by defining an appropriately named command to contain the format component, and using the additional first argument (“`cref`” or “`Cref`”) to determine how to define the corresponding command with the other capitalisation. The extra fifth argument gets tagged onto the end of the generated macro names.

```

1268 \def\@cerefname#1#2#3#4#5{%
1269   \begingroup%
1270   \expandafter\gdef\csname #1##2##3##4##5\endcsname{##3}%
1271   \expandafter\gdef\csname #1##2##3##4##5\endcsname{##4}}%

```

The following `\@tmpa` macro makes use of the fact that the first character of `#1` is “`c`” for lower-case and “`C`” for upper-case, in order to wrap the capitalisation-dependent parts in macros so that the rest of the code can be capitalisation-agnostic.

```

1272 \def\@tmpa##1##2\@nil{%
1273   \if##1c%
1274     \def\@other{C##2}%
1275     \def\@change-case{\expandafter\MakeUppercase}%
1276   \else%
1277     \def\@other{c##2}%
1278     \if@cref@capitalise%
1279       \def\@change-case{}%
1280     \else%
1281       \def\@change-case{\MakeLowercase}%

```

```

1282      \fi%
1283      \fi}%
1284      \atmpa#1\@nil%

```

If the other capitalisation variant is not already defined...

```

1285      \@ifundefined{\@other @#2@name#5}{%

```

Define \atmpa and \tmpb to be partial expansions (expanded just once) of the macros for the capitalisation variant we've just defined above.

```

1286      \expandafter\expandafter\expandafter\def%
1287      \expandafter\expandafter\expandafter\atmpa\%
1288      \expandafter\expandafter\expandafter\expandafter{%
1289          \csname#1@#2@name\endcsname}%
1290      \expandafter\expandafter\expandafter\expandafter\def%
1291      \expandafter\expandafter\expandafter\expandafter\atmpb\%
1292      \expandafter\expandafter\expandafter\expandafter{%
1293          \csname#1@#2@name@plural\endcsname}%

```

Add the \changecase command to the front of the definitions of \atmpa and \tmpb.

```

1294      \expandafter\expandafter\expandafter\def%
1295      \expandafter\expandafter\expandafter\atmpa\%
1296      \expandafter\expandafter\expandafter\expandafter{%
1297          \expandafter\changecase\atmpa}%
1298      \expandafter\expandafter\expandafter\expandafter\def%
1299      \expandafter\expandafter\expandafter\expandafter\atmpb\%
1300      \expandafter\expandafter\expandafter\expandafter{%
1301          \expandafter\changecase\atmpb}%

```

Define the other capitalisation variants to be the partial expansions (expanded just once) of \atmpa and \tmpb. The \toksa token register just makes the code less verbose.

```

1302      \toksdef\@toksa=0%
1303      \@toksa={%
1304          \expandafter\gdef\csname\@other @#2@name#5\endcsname}%
1305          \expandafter\the\expandafter\@toksa\expandafter{\atmpa}%
1306          \@toksa={%
1307              \expandafter\gdef\csname\@other @#2@name@plural#5\endcsname}%
1308              \expandafter\the\expandafter\@toksa\expandafter{\atmpb}%
1309          }{}%
1310      \endgroup%

```

Add label type to list of types that need defining from components.

```

1311      \cref@stack@add{#2}\cref@label@types}%

```

\crefconstructcomponents The \crefconstructcomponents utility macro puts the reference format components for the specified reference type into temporary macros, for use by later macros. The ridiculous number of “#” characters ensure that the correct number remain when they come to be used later (recall that pairs “##” are collapsed to a single “#” each time the code is expanded).

```

1312 \def\crefconstructcomponents#1{%

```

Single cross-reference label format.

```
1313  \cifundefined{cref@#1@label}{%
1314    \let\@tmplabel\cref@default@label%
1315  }{%
1316    \expandafter\let\expandafter\@tmplabel%
1317    \csname cref@#1@label\endcsname%
1318 }
```

Reference range label format.

```
1319  \cifundefined{cref@#1@rangelabel}{%
1320    \expandafter\def\expandafter\@tmpa\expandafter{%
1321      \@tmplabel{####1}{####3}{####4}}%
1322    \expandafter\def\expandafter\@tmpb\expandafter{%
1323      \@tmplabel{####2}{####5}{####6}}%
1324    \toksdef\@toksa=0%
1325    \@toksa={\def\@tmprangelabel##1##2##3##4##5##6}%
1326    \expandafter\expandafter\expandafter\the%
1327    \expandafter\expandafter\expandafter\@toksa%
1328    \expandafter\expandafter\expandafter{%
1329      \expandafter\expandafter\expandafter\crefrangepreconjunction%
1330      \expandafter\@tmpa\expandafter\crefrangeconjunction\@tmpb%
1331      \crefrangepostconjunction}%
1332  }{%
1333    \expandafter\let\expandafter\@tmprangelabel%
1334    \csname cref@#1@rangelabel\endcsname%
1335 }
```

Get the correct number of “#”’s into the label format definitions.

```
1336  \expandafter\def\expandafter\@tmplabel\expandafter{%
1337    \@tmplabel{#####1}{#####2}{#####3}}%
1338  \expandafter\def\expandafter\@tmprangelabel\expandafter{%
1339    \@tmprangelabel{#####1}{#####2}{#####3}}%
1340    #####4}{#####5}{#####6}}%
```

Lower-case singular cross-reference name.

```
1341  % \expandafter\expandafter\expandafter\def%
1342  % \expandafter\expandafter\expandafter\@tmpname%
1343  % \expandafter\expandafter\expandafter{%
1344  %   \csname cref@#1@name\endcsname}%
1345  \expandafter\def\expandafter\@tmpname\expandafter{%
1346    \csname cref@#1@name\endcsname}%
```

Upper-case singular cross-reference name.

```
1347  % \expandafter\expandafter\expandafter\def%
1348  % \expandafter\expandafter\expandafter\@tmpName%
1349  % \expandafter\expandafter\expandafter{%
1350  %   \csname Cref@#1@name\endcsname}%
1351  \expandafter\def\expandafter\@tmpName\expandafter{%
1352    \csname Cref@#1@name\endcsname}%
```

Lower-case plural cross-reference name.

```

1353   \expandafter\def\expandafter@\tmpnameplural\expandafter{%
1354     \csname cref@#1@name@plural\endcsname}%
    Upper-case plural cross-reference name.
1355   \expandafter\def\expandafter@\tmpNameplural\expandafter{%
1356     \csname Cref@#1@name@plural\endcsname}%
1357 }

\@crefdefineformat The \@crefdefineformat et al. macros construct calls to \crefformat et al. for the supplied reference type that define the corresponding formats in terms of the format components. This is mostly just an arduous exercise in controlling macro expansion order.
1358 \def\@crefdefineformat#1{%
1359   \begingroup%
    Put format components into tmp macros.
1360   \@crefconstructcomponents{#1}%
    Assemble the arguments for \crefformat and \Crefformat from the components.
1361   \expandafter\expandafter\expandafter\def%
1362   \expandafter\expandafter\expandafter@\tmpfirst%
1363   \expandafter\expandafter\expandafter{%
1364     \expandafter\@tmpname\expandafter~\@tmplabel}%
1365   \expandafter\expandafter\expandafter\def%
1366   \expandafter\expandafter\expandafter@\tmpFirst%
1367   \expandafter\expandafter\expandafter{%
1368     \expandafter\@tmpName\expandafter~\@tmplabel}%

    Define \crefformat and \Crefformat.
1369   \toksdef\@toksa=0%
1370   \@toksa=\{\crefformat{#1}\}%
1371   \expandafter\the\expandafter\@toksa\expandafter{\@tmpfirst}%
1372   \@toksa=\{\Crefformat{#1}\}%
1373   \expandafter\the\expandafter\@toksa\expandafter{\@tmpFirst}%
1374   \endgroup}

\@crefrangedefineformat Construct call to \crefrangeformat.
1375 \def\@crefrangedefineformat#1{%
1376   \begingroup%
    Put format components into tmp macros.
1377   \@crefconstructcomponents{#1}%
    Assemble the arguments for \crefrangeformat and \Crefrangeformat from the components.
1378   \expandafter\expandafter\expandafter\def%
1379   \expandafter\expandafter\expandafter@\tmpfirst%
1380   \expandafter\expandafter\expandafter{%
1381     \expandafter\@tmpnameplural\expandafter~\@tmprangelabel}%
1382   \expandafter\expandafter\expandafter\def%
1383   \expandafter\expandafter\expandafter@\tmpFirst%
1384   \expandafter\expandafter\expandafter{%
1385     \expandafter\@tmpNameplural\expandafter~\@tmprangelabel}%

```

```

Define \crefrangeformat and \Crefrangeformat.

1386   \toksdef{\toksa=0%
1387   \toksa={\crefrangeformat{#1}}%
1388   \expandafter\the\expandafter{\toksa\expandafter{\tmpfirst}}%
1389   \toksa={\Crefrangeformat{#1}}%
1390   \expandafter\the\expandafter{\toksa\expandafter{\tmpFirst}}%
1391   \endgroup}

\@crefdefinemultiformat Construct call to \crefmultiformat.

1392 \def{\@crefdefinemultiformat#1{%
1393   \begingroup%
Put format components into tmp macros.

1394   \@crefconstructcomponents{#1}%

Assemble the arguments for \crefmultiformat and \Crefmultiformat from the
components.

1395   \expandafter\expandafter\expandafter\def%
1396   \expandafter\expandafter\expandafter{\tmpfirst}%
1397   \expandafter\expandafter\expandafter{%
1398     \expandafter{\tmpnameplural}\expandafter{\tmplabel}}%
1399   \expandafter\expandafter\expandafter\def%
1400   \expandafter\expandafter\expandafter{\tmpFirst}%
1401   \expandafter\expandafter\expandafter{%
1402     \expandafter{\tmpNameplural}\expandafter{\tmplabel}}%
1403   % \expandafter\expandafter\expandafter\def%
1404   % \expandafter\expandafter\expandafter{\tmpsecond}%
1405   % \expandafter\expandafter\expandafter{%
1406   %   \expandafter{\crefpairconjunction}\tmplabel}%
1407   \expandafter\def\expandafter{\tmpsecond}\expandafter{%
1408     \expandafter{\crefpairconjunction}\tmplabel}%
1409   % \expandafter\expandafter\expandafter\def%
1410   % \expandafter\expandafter\expandafter{\tmpmiddle}%
1411   % \expandafter\expandafter\expandafter{%
1412   %   \expandafter{\crefmiddleconjunction}\tmplabel}%
1413   \expandafter\def\expandafter{\tmpmiddle}\expandafter{%
1414     \expandafter{\crefmiddleconjunction}\tmplabel}%
1415   % \expandafter\expandafter\expandafter\def%
1416   % \expandafter\expandafter\expandafter{\tmplast}%
1417   % \expandafter\expandafter\expandafter{%
1418   %   \expandafter{\creflastconjunction}\tmplabel}%
1419   \expandafter\def\expandafter{\tmplast}\expandafter{%
1420     \expandafter{\creflastconjunction}\tmplabel}%

Bundle all four arguments for \crefmultiformat in token register \toksb, then
call it.

1421   \toksdef{\toksa=0%
1422   \toksdef{\toksb=1%
1423   \toksb={}%
1424   \expandafter{\cref@append{\toks}\expandafter{\toksb}\expandafter{}}
```

```

1425      \expandafter{\@tmpfirst}%
1426      \expandafter\cref@append@toks\expandafter\@toksb\expandafter{%
1427          \expandafter{\@tmpsecond}%
1428      \expandafter\cref@append@toks\expandafter\@toksb\expandafter{%
1429          \expandafter{\@tmpmiddle}%
1430      \expandafter\cref@append@toks\expandafter\@toksb\expandafter{%
1431          \expandafter{\@tmplast}%
1432      \@toksa=\{\crefmultiformat{#1}\}%
1433      \expandafter\the\expandafter\@toksa\the\@toksb%

```

Bundle all four arguments for \Crefmultiformat in token register \@toksb, then call it.

```

1434      \@toksb={}%
1435      \expandafter\cref@append@toks\expandafter\@toksb\expandafter{%
1436          \expandafter{\@tmpFirst}%
1437      \expandafter\cref@append@toks\expandafter\@toksb\expandafter{%
1438          \expandafter{\@tmpsecond}%
1439      \expandafter\cref@append@toks\expandafter\@toksb\expandafter{%
1440          \expandafter{\@tmpmiddle}%
1441      \expandafter\cref@append@toks\expandafter\@toksb\expandafter{%
1442          \expandafter{\@tmplast}%
1443      \@toksa=\{\crefmultiformat{#1}\}%
1444      \expandafter\the\expandafter\@toksa\the\@toksb%
1445      \endgroup}

```

\@crefrangedefinemultiformat Construct call to \crefrangemultiformat.

```

1446 \def\@crefrangedefinemultiformat#1{%
1447   \begingroup%

```

Put format components into tmp macros.

```
1448   \crefconstructcomponents{#1}%

```

Assemble the arguments that need to be passed to \crefrangemultiformat and \Crefrangemultiformat from the reference components.

```

1449   \expandafter\expandafter\expandafter\def%
1450   \expandafter\expandafter\expandafter{@tmpfirst}%
1451   \expandafter\expandafter\expandafter{%
1452       \expandafter\@tmpnameplural\expandafter~\@tmprangelabel}%
1453   \expandafter\expandafter\expandafter\def%
1454   \expandafter\expandafter\expandafter{@tmpFirst}%
1455   \expandafter\expandafter\expandafter{%
1456       \expandafter\@tmpNameplural\expandafter~\@tmprangelabel}%
1457   \% \expandafter\expandafter\expandafter\def%
1458   \% \expandafter\expandafter\expandafter{@tmpsecond}%
1459   \% \expandafter\expandafter\expandafter{%
1460   \% \expandafter\crefpairconjunction\@tmprangelabel}%
1461   \expandafter\def\expandafter\expandafter{@tmpsecond}\expandafter{%
1462       \expandafter\crefpairconjunction\@tmprangelabel}%
1463   \% \expandafter\expandafter\expandafter\def%
1464   \% \expandafter\expandafter\expandafter{@tmpmiddle}%
1465   \% \expandafter\expandafter\expandafter{%

```

```

1466     % \expandafter\crefmiddleconjunction{@tmpranglelabel}%
1467     \expandafter\def\expandafter{@tmpmiddle\expandafter{%
1468         \expandafter\crefmiddleconjunction{@tmpranglelabel}%
1469     % \expandafter\expandafter\expandafter\def%
1470     % \expandafter\expandafter\expandafter@tmplast%
1471     % \expandafter\expandafter\expandafter{%
1472     % \expandafter\creflastconjunction{@tmpranglelabel}%
1473     \expandafter\def\expandafter{@tmplast\expandafter{%
1474         \expandafter\creflastconjunction{@tmpranglelabel}%

```

Bundle all four arguments for `\crefrangemultiformat` in token register `\@toksb`, then call it.

```

1475     \@toksdef{@toksa=0%
1476     \@toksdef{@toksb=1%
1477     \@toksb={}%
1478     \expandafter\cref@append@toks\expandafter{@toksb\expandafter{%
1479         \expandafter{@tmpfirst}}%
1480     \expandafter\cref@append@toks\expandafter{@toksb\expandafter{%
1481         \expandafter{@tmpsecond}}%
1482     \expandafter\cref@append@toks\expandafter{@toksb\expandafter{%
1483         \expandafter{@tmpmiddle}}%
1484     \expandafter\cref@append@toks\expandafter{@toksb\expandafter{%
1485         \expandafter{@tmplast}}%
1486     \@toksa=\{\crefrangemultiformat{#1}\}%
1487     \expandafter\the\expandafter{@toksa\the\@toksb}%

```

Bundle all four arguments for `\Crefrangemultiformat` in token register `\@toksb`, then call it.

```

1488     \@toksb={}%
1489     \expandafter\cref@append@toks\expandafter{@toksb\expandafter{%
1490         \expandafter{@tmpFirst}}%
1491     \expandafter\cref@append@toks\expandafter{@toksb\expandafter{%
1492         \expandafter{@tmpsecond}}%
1493     \expandafter\cref@append@toks\expandafter{@toksb\expandafter{%
1494         \expandafter{@tmpmiddle}}%
1495     \expandafter\cref@append@toks\expandafter{@toksb\expandafter{%
1496         \expandafter{@tmplast}}%
1497     \@toksa=\{\Crefrangemultiformat{#1}\}%
1498     \expandafter\the\expandafter{@toksa\the\@toksb}%
1499     \endgroup}

```

`\@crefdefineallformats` `\@crefdefineallformats` calls each of the above, to define all formats for the given type from the corresponding components.

```

1500 \def\@crefdefineallformats#1{%
1501     \@crefdefineformat{#1}%
1502     \@crefrangedefineformat{#1}%
1503     \@crefdefinemultiformat{#1}%
1504     \@crefrangedefinemultiformat{#1}%

```

12.4.2 Cross-Reference Format Definition Commands

\crefformat \crefformat et al. are lower-level commands that give complete control over the format of different reference types. They override the component-based formats, simply using the supplied arguments to define appropriately named formatting macros, which are called by \Qsetcref. If the corresponding \Crefformat or \crefmultiformat variant is not already defined, they define it to be a version with the first letter capitalised or lower-cased.

```

\crefrangemultiformat 1505 \newcommand{\crefformat}[2]{\@crefformat{cref}{#1}{#2}}
\Crefrangemultiformat 1506 \newcommand{\Crefformat}[2]{\@crefformat{Cref}{#1}{#2}}
          1507 \newcommand{\crefrangeformat}[2]{\@crefrangeformat{crefrange}{#1}{#2}}
          1508 \newcommand{\Crefrangeformat}[2]{\@crefrangeformat{Crefrange}{#1}{#2}}
          1509 \newcommand{\crefmultiformat}[5]{%
            1510   \@crefmultiformat{cref}{#1}{#2}{#3}{#4}{#5}%
            1511 \newcommand{\Crefmultiformat}[5]{%
              1512   \@crefmultiformat{Cref}{#1}{#2}{#3}{#4}{#5}%
            1513 \newcommand{\crefrangemultiformat}[5]{%
              1514   \@crefrangemultiformat{crefrange}{#1}{#2}{#3}{#4}{#5}%
            1515 \newcommand{\Crefrangemultiformat}[5]{%
              1516   \@crefrangemultiformat{Crefrange}{#1}{#2}{#3}{#4}{#5}}}
```

The utility macros do the real work, by using the first argument (“cref” or “Cref”, and “crefrange” or “Crefrange”) to determine how to define the corresponding command with the other capitalisation.

\@crefformat \@crefformat defines the macros for single references.

```

1517 \def\@crefformat#1#2#3{%
1518   \begingroup%
1519     \expandafter\gdef\csname #1@#2@format\endcsname##1##2##3{#3}%
}
```

The following \tmpa macro makes use of the fact that the first character of #1 is “c” for lower-case and “C” for upper-case, in order to wrap the capitalisation-dependent parts in macros so that the rest of the code can be capitalisation-variant agnostic.

```

1520   \def\@tmpa##1##2\@nil{%
1521     \if##1c%
1522       \def\@other{C##2}%
1523       \def\@change-case{\expandafter\MakeUppercase}%
1524     \else%
1525       \def\@other{c##2}%
1526       \if@cref@capitalise%
1527         \def\@change-case{}%
1528       \else%
1529         \def\@change-case{\MakeLowercase}%
1530       \fi%
1531     \fi%
1532   \@tmpa#1\@nil%
```

If the other capitalisation variant is not already defined...

```
1533   \Qifundefined{\@other @#2@format}{%
```

Define `\@tmpa` to be a partial expansion (expanded just once) of the capitalisation variant we've just defined above. The `\@toska` token register just makes the code less verbose.

```
1534     \toksdef\@toska=0%
1535     \@toska={\def\@tmpa##1##2##3}{%
1536     \expandafter\expandafter\expandafter\the%
1537     \expandafter\expandafter\expandafter\expandafter\@toska%
1538     \expandafter\expandafter\expandafter\expandafter{%
1539         \csname#1\@#2@format\endcsname{##1}{##2}{##3}}}
```

Add the `\@changecase` command to the front of the definition of `\@tmpa`.

```
1540     \expandafter\expandafter\expandafter\expandafter\the%
1541     \expandafter\expandafter\expandafter\expandafter\@toska%
1542     \expandafter\expandafter\expandafter\expandafter{%
1543         \expandafter\@changecase\@tmpa{##1}{##2}{##3}}}
```

Define the other capitalisation variant to be the partial expansion (expanded just once) of `\@tmpa`.

```
1544     \@toska={%
1545     \expandafter\gdef\csname\@other \#2@format\endcsname##1##2##3}{%
1546     \expandafter\the\expandafter\@toska\expandafter{%
1547         \@tmpa{##1}{##2}{##3}}%
1548     }{%
1549     \endgroup}
```

`\@crefrangeformat` `\@crefrangeformat` defines the macros for single reference ranges.

```
1550 \def\@crefrangeformat#1#2#3{%
1551   \begingroup%
1552   \expandafter\gdef\csname #1\#2@format\endcsname{%
1553     ##1##2##3##4##5##6{##3}}}
```

The following `\@tmpa` macro makes use of the fact that the first character of `#1` is “c” for lower-case and “C” for upper-case, in order to wrap the capitalisation-dependent parts in macros so that the rest of the code can be capitalisation-variant agnostic.

```
1554   \def\@tmpa##1##2\@nil{%
1555     \if##1c%
1556       \def\@other{C##2}%
1557       \def\@changecase{\expandafter\MakeUppercase}%
1558     \else%
1559       \def\@other{c##2}%
1560       \if@cref@capitalise%
1561         \def\@changecase{}%
1562       \else%
1563         \def\@changecase{\MakeLowercase}%
1564       \fi%
1565     \fi%
1566   \@tmpa#1\@nil%
```

If the other capitalisation variant is not already defined...

```
1567   \@ifundefined{\@other \#2@format}{%
```

Define `\@tmpa` to be a partial expansion (expanded just once) of the capitalisation variant we've just defined above. The `\@toksa` token register just makes the code less verbose.

```
1568     \toksdef\@toksa=0%
1569     \@toksa={\def\@tmpa##1##2##3##4##5##6}%
1570     \expandafter\expandafter\expandafter\the%
1571     \expandafter\expandafter\expandafter\expandafter\@toksa%
1572     \expandafter\expandafter\expandafter\expandafter{%
1573         \csname##1\@##2@format\endcsname##1##2##3##4##5##6}%

```

Add the `\@changecase` command to the front of the definition of `\@tmpa`.

```
1574     \expandafter\expandafter\expandafter\expandafter\the%
1575     \expandafter\expandafter\expandafter\expandafter\@toksa%
1576     \expandafter\expandafter\expandafter\expandafter{%
1577         \expandafter\@changecase\@tmpa##1##2##3##4##5##6}%

```

Define the other capitalisation variant to be the partial expansion (expanded just once) of `\@tmpa`.

```
1578     \@toksa={\expandafter\gdef%
1579         \csname\@other\@##2@format\endcsname##1##2##3##4##5##6}%
1580     \expandafter\the\expandafter\@toksa\expandafter{%
1581         \@tmpa##1##2##3##4##5##6}%
1582     }{}%
1583 \endgroup
```

`\@crefmultiformat` `\@crefmultiformat` defines the macros for multiple references.

```
1584 \def\@crefmultiformat#1#2#3#4#5#6{%
1585   \begingroup%
1586   \expandafter\gdef\csname #1\@##2@format@first\endcsname##1##2##3{#3}%
1587   \expandafter\gdef\csname #1\@##2@format@second\endcsname##1##2##3{#4}%
1588   \expandafter\gdef\csname #1\@##2@format@middle\endcsname##1##2##3{#5}%
1589   \expandafter\gdef\csname #1\@##2@format@last\endcsname##1##2##3{#6}%

```

The following `\@tmpa` macro makes use of the fact that the first character of `#1` is “c” for lower-case and “C” for upper-case, in order to wrap the capitalisation-dependent parts in macros so that the rest of the code can be capitalisation-agnostic.

```
1590   \def\@tmpa##1##2\@nil{%
1591     \if##1c%
1592       \def\@other{C##2}%
1593       \def\@changecase{\expandafter\MakeUppercase}%
1594     \else%
1595       \def\@other{c##2}%
1596       \if@cref@capitalise%
1597         \def\@changecase{}%
1598       \else%
1599         \def\@changecase{\MakeLowercase}%
1600       \fi%
1601     \fi}%
1602   \@tmpa#1\@nil%
```

If the other capitalisation variant of the first part of the multi-format definition is not already defined...

```
1603      \c@ifundefined{\@other @#2@format@first}{%
```

Define \@tmpa to be a partial expansion (expanded just once) of the capitalisation variant we've just defined above. The \@toksa token register just makes the code less verbose.

```
1604      \toksdef{\@toksa=0%
1605      \@toksa={\def{\@tmpa##1##2##3}%
1606      \expandafter\expandafter\expandafter\the%
1607      \expandafter\expandafter\expandafter\expandafter{\@toksa}%
1608      \expandafter\expandafter\expandafter\expandafter{%
1609      \csname{\@2@format@first}\endcsname{##1}{##2}{##3}}%
```

Add the \change case command to the front of the definition of \@tmpa.

```
1610      \expandafter\expandafter\expandafter\the%
1611      \expandafter\expandafter\expandafter{\@toksa}%
1612      \expandafter\expandafter\expandafter{%
1613      \expandafter\@change case{\@tmpa{##1}{##2}{##3}}%
```

Define the other capitalisation variant to be the partial expansion (expanded just once) of \@tmpa.

```
1614      \toksa={%
1615      \expandafter\gdef\csname{\@other @#2@format@first}\endcsname{%
1616      ##1##2##3}%
1617      \expandafter\the\expandafter{\@toksa}\expandafter{%
1618      \@tmpa{##1}{##2}{##3}}%
1619      }{}}
```

The other parts of the multi-format definition are defined to be identical for both capitalisation variants.

```
1620      \c@ifundefined{\@other @#2@format@second}{%
1621      \@toksa={%
1622      \expandafter\global\expandafter\let%
1623      \csname{\@other @#2@format@second}\endcsname{%
1624      \expandafter\the\expandafter{\@toksa}%
1625      \csname{\#1@#2@format@second}\endcsname{%
1626      }{}}%
1627      \c@ifundefined{\@other @#2@format@middle}{%
1628      \@toksa={%
1629      \expandafter\global\expandafter\let%
1630      \csname{\@other @#2@format@middle}\endcsname{%
1631      \expandafter\the\expandafter{\@toksa}%
1632      \csname{\#1@#2@format@middle}\endcsname{%
1633      }{}}%
1634      \c@ifundefined{\@other @#2@format@last}{%
1635      \@toksa={%
1636      \expandafter\global\expandafter\let%
1637      \csname{\@other @#2@format@last}\endcsname{%
1638      \expandafter\the\expandafter{\@toksa}%
1639      \csname{\#1@#2@format@last}\endcsname{%
```

```

1640      }{}}%
1641  \endgroup}

```

\@crefrangemultiformat \@crefmultiformat defines the macros for reference ranges within multiple references.

```

1642 \def\@crefrangemultiformat#1#2#3#4#5#6{%
1643   \begingroup%
1644     \expandafter\gdef\csname #1@#2@format@first\endcsname{%
1645       ##1##2##3##4##5##6{#3}%
1646     \expandafter\gdef\csname #1@#2@format@second\endcsname{%
1647       ##1##2##3##4##5##6{#4}%
1648     \expandafter\gdef\csname #1@#2@format@middle\endcsname{%
1649       ##1##2##3##4##5##6{#5}%
1650     \expandafter\gdef\csname #1@#2@format@last\endcsname{%
1651       ##1##2##3##4##5##6{#6}%

```

The following \@tmpa macro makes use of the fact that the first character of #1 is “c” for lower-case and “C” for upper-case, in order to wrap the capitalisation-dependent parts in macros so that the rest of the code can be capitalisation-variant agnostic.

```

1652 \def\@tmpa##1##2\@nil{%
1653   \if##1%
1654     \def\@other{C##2}%
1655     \def\@change-case{\expandafter\MakeUppercase}%
1656   \else%
1657     \def\@other{c##2}%
1658     \if@cref@capitalise%
1659       \def\@change-case{}%
1660     \else%
1661       \def\@change-case{\MakeLowercase}%
1662     \fi%
1663   \fi}%
1664 \@tmpa#1\@nil%

```

If the other capitalisation variant of the first part of the multi-format definition is not already defined...

```

1665 \@ifundefined{\@other @#2@format@first}{%

```

Define \@tmpa to be a partial expansion (expanded just once) of the capitalisation variant we’ve just defined above. The \@toska token register just makes the code less verbose.

```

1666 \toksdef\@toska=0%
1667 \@toska={\def\@tmpa##1##2##3##4##5##6}{%
1668   \expandafter\expandafter\expandafter\the%
1669   \expandafter\expandafter\expandafter\expandafter\@toska%
1670   \expandafter\expandafter\expandafter\expandafter{%
1671     \csname#1@#2@format@first\endcsname{%
1672       {##1}{##2}{##3}{##4}{##5}{##6}}%

```

Add the \@change-case command to the front of the definition of \@tmpa.

```

1673     \expandafter\expandafter\expandafter\the%
1674     \expandafter\expandafter\expandafter\@toksa%
1675     \expandafter\expandafter\expandafter{%
1676         \expandafter\@changecase\@tmpa{##1}{##2}{##3}{##4}{##5}{##6}}%

```

Define the other capitalisation variant to be the partial expansion (expanded just once) of `\@tmpa`.

```

1677     \@toksa={%
1678         \expandafter\gdef\csname@other @#2@format@first\endcsname{%
1679             ##1##2##3##4##5##6}%
1680         \expandafter\the\expandafter\@toksa\expandafter{%
1681             \@tmpa{##1}{##2}{##3}{##4}{##5}{##6}}%
1682     }{}%

```

The other parts of the multi-format definition are defined to be identical for both capitalisation variants.

```

1683     \@ifundefined{\@other @#2@format@second}{%
1684         \@toksa={%
1685             \expandafter\global\expandafter\let%
1686             \csname@other @#2@format@second\endcsname}%
1687             \expandafter\the\expandafter\@toksa%
1688             \csname #1@#2@format@second\endcsname%
1689     }{}%
1690     \@ifundefined{\@other @#2@format@middle}{%
1691         \@toksa={%
1692             \expandafter\global\expandafter\let%
1693             \csname@other @#2@format@middle\endcsname}%
1694             \expandafter\the\expandafter\@toksa%
1695             \csname #1@#2@format@middle\endcsname%
1696     }{}%
1697     \@ifundefined{\@other @#2@format@last}{%
1698         \@toksa={%
1699             \expandafter\global\expandafter\let%
1700             \csname@other @#2@format@last\endcsname}%
1701             \expandafter\the\expandafter\@toksa%
1702             \csname #1@#2@format@last\endcsname%
1703     }{}%
1704     \endgroup}

```

12.5 hyperref Support

hyperref If the `hyperref` package is loaded, we add hyper-link support to `cleveref`. Since `hyperref` messes around with some of the same L^AT_EX internals as we do, we also have to override some of its redefinitions so that they work with `cleveref`.

```

1705 \@ifpackageloaded{hyperref}{%
1706   \PackageInfo{cleveref}{`hyperref' support loaded}}

```

\cref@hyperref We define a utility macro to extract the hyper-link supplied by `hyperref` (via the aux file). Note that `hyperref` adds the hyper-link information to the stan-

dard `\newlabel` line in the aux file, so we have to retrieve it from the standard `\@⟨label⟩`, *not* the one prefixed with `\cref@` that we've created ourselves.

```
1707 \def\cref@hyperref#1{\expandafter\expandafter\expandafter%
1708     \fourthoffive\csname r@#1\endcsname}
```

`\H@refstepcounter` The `hyperref` package stores the original `\refstepcounter` definition as `\H@refstepcounter`. Unfortunately, it plasters `\refstepcounter` all over the place, sometimes bypassing `\refstepcounter` entirely. So we're forced to modify `\H@refstepcounter` itself, in order to ensure that the extra information we need is stored in `\cref@currentlabel`.

```
1709 \let\cref@old@H@refstepcounter\H@refstepcounter
1710 \def\H@refstepcounter#1{%
1711     \cref@old@H@refstepcounter{#1}%
1712     \cref@constructprefix{#1}{\@result}%
1713     \protected@edef\cref@currentlabel{%
1714         [#1] [\arabic{#1}] [\@result]%
1715         \csname p@#1\endcsname\csname the#1\endcsname}}
```

`\refstepcounter@noarg` `\refstepcounter`'s `\refstepcounter`, which ends up stored in our `\refstepcounter@optarg` `\refstepcounter`, already calls `\H@refstepcounter`, and we just redefined the latter to store the extra information. So we only need to change `\cref@currentlabel` in *our* `\refstepcounter` if an optional argument was supplied. (Note that, in this case, the mechanism for setting `\cref@currentlabel` is slightly different than it is without `hyperref`: `\cref@currentlabel` first gets set by our modified `\H@refstepcounter`, which gets called via `\cref@old@refstepcounter`. `\cref@refstepcounter@optarg` then overrides the label type.)

```
1716 \def\refstepcounter@noarg#1{\cref@old@refstepcounter{#1}}
1717 \def\refstepcounter@optarg[#1]#2{%
1718     \cref@old@refstepcounter{#2}%
1719     \protected@edef\cref@currentlabel{%
1720         \expandafter\cref@Override@label@type%
1721         \cref@currentlabel\@nil{#1}}}
```

`\appendix` We again make `\appendix` redefine things so that the label type for chapters or sections is exceptionally overridden and set to “appendix” instead. But this time, it is `\H@refstepcounter` that needs to be redefined.

```
1722 \renewcommand\appendix{%
1723     \cref@old@appendix%
1724     \@ifundefined{chapter}{%
1725         \def\H@refstepcounter##1{%
1726             \cref@old@H@refstepcounter{##1}%
1727             \cref@constructprefix{##1}{\@result}}%
```

We add a large value to the front of the counter data, to force references to anything in appendices to be sorted after everything else.

```
1728     \ifx\@result\empty%
1729         \def\@result{2147483647}%
1730     \else%
```

```

1731           \edef\@result{2147483647,\@result}%
1732       \fi%
Override the cross-reference type of sectioning commands.
1733           \def\@tmpa{##1}%
1734           \def\@tmpb{section}%
1735           \ifx\@tmpa\@tmpb%
1736               \protected@edef\cref@currentlabel{%
1737                   [appendix] [\arabic{##1}] [\@result]%
1738                   \csname p@##1\endcsname\csname the##1\endcsname}%
1739           \else%
1740               \def\@tmpa{##1}%
1741               \def\@tmpb{subsection}%
1742               \ifx\@tmpa\@tmpb%
1743                   \protected@edef\cref@currentlabel{%
1744                       [subappendix] [\arabic{##1}] [\@result]%
1745                       \csname p@##1\endcsname\csname the##1\endcsname}%
1746           \else%
1747               \def\@tmpa{##1}%
1748               \def\@tmpb{subsubsection}%
1749               \ifx\@tmpa\@tmpb%
1750                   \protected@edef\cref@currentlabel{%
1751                       [subsubappendix] [\arabic{##1}] [\@result]%
1752                       \csname p@##1\endcsname\csname the##1\endcsname}%
1753           \else%
1754               \protected@edef\cref@currentlabel{%
1755                   [##1] [\arabic{##1}] [\@result]%
1756                   \csname p@##1\endcsname\csname the##1\endcsname}%
1757           \fi%
1758           \fi%
1759       \fi}%
1760   }{%
1761       \def\H@refstepcounter##1{%
1762           \cref@old@H@refstepcounter{##1}%
1763           \cref@constructprefix{##1}{\@result}%

```

Again, the large value added to the front of the counter data forces references to appendix items to be sorted last.

```

1764           \ifx\@result\empty%
1765               \def\@result{2147483647}%
1766           \else%
1767               \edef\@result{2147483647,\@result}%
1768           \fi%

```

Override the cross-reference type of sectioning commands.

```

1769           \def\@tmpa{##1}%
1770           \def\@tmpb{chapter}%
1771           \ifx\@tmpa\@tmpb%
1772               \protected@edef\cref@currentlabel{%
1773                   [appendix] [\arabic{##1}] [\@result]%
1774                   \csname p@##1\endcsname\csname the##1\endcsname}%

```

```

1775     \else%
1776         \def\@tmpa{\#1}%
1777         \def\@tmpb{section}%
1778         \ifx\@tmpa\@tmpb%
1779             \protected@edef\cref@currentlabel{%
1780                 [subappendix] [\arabic{##1}] [\@result]%
1781                 \csname p@##1\endcsname\csname the##1\endcsname}%
1782         \else%
1783             \def\@tmpa{\#1}%
1784             \def\@tmpb{subsection}%
1785             \ifx\@tmpa\@tmpb%
1786                 \protected@edef\cref@currentlabel{%
1787                     [subsubappendix] [\arabic{##1}] [\@result]%
1788                     \csname p@##1\endcsname\csname the##1\endcsname}%
1789             \else%
1790                 \def\@tmpa{\#1}%
1791                 \def\@tmpb{subsubsection}%
1792                 \ifx\@tmpa\@tmpb%
1793                     \protected@edef\cref@currentlabel{%
1794                         [subsubsubappendix] [\arabic{##1}] [\@result]%
1795                         \csname p@##1\endcsname\csname the##1\endcsname}%
1796                 \else%
1797                     \protected@edef\cref@currentlabel{%
1798                         [\##1] [\arabic{##1}] [\@result]%
1799                         \csname p@##1\endcsname\csname the##1\endcsname}%
1800                 \fi%
1801             \fi%
1802         \fi%
1803     \fi}%
1804 }
1805 }

```

\cref* Redefine \cref and all the others to allow starred variants, which don't create hyper-links. The starred variants simply set a flag, which is tested in \@@setceref \crefrange* and \@@setrangeref (below).

```

\crefrange* 1806 \DeclareRobustCommand{\cref}{%
\@crefstar 1807   \@ifstar{\@crefstar{cref}}{\@crefnostar{cref}}}
\@crefrangestar 1808 \DeclareRobustCommand{\Cref}{%
\@crefrangenostar 1809   \@ifstar{\@crefstar{Cref}}{\@crefnostar{Cref}}}
1810   \def\@crefnostar#1#2{\@cref{#1}{#2}}
1811   \def\@crefstar#1#2{%
1812     \ifstarredtrue\@cref{#1}{#2}\ifstarredfalse\relax\fi}
1813   \DeclareRobustCommand{\crefrange}{%
1814     \ifstar{\@crefrangestar{cref}}{\@crefrangenostar{cref}}}
1815   \DeclareRobustCommand{\Crefrange}{%
1816     \ifstar{\@crefrangestar{Cref}}{\@crefrangenostar{Cref}}}
1817   \def\@crefrangenostar#1#2#3{\@setcrefrange{#2}{#3}{#1}{\relax}}
1818   \def\@crefrangestar#1#2#3{%
1819     \ifstarredtrue\@setcrefrange{#2}{#3}{#1}{\relax}\ifstarredfalse\relax\fi}

```

\@setceref Redefine \@setceref and \@setrangeref to create hyper-links (unless the \@setcrefrange starred flag is set), using the extra arguments supplied in \r@cref@(*label*) (via the aux file) by hyperref.

```

1820  \def\@setceref#1#2{%
1821    \cref@getlabel{#2}{\@tmplabel}%
1822    \if@crefstarred%
1823      #1{\@tmplabel}{\{}{\}%
1824    \else%
1825      \edef\@tmplink{\cref@hyperref{#2}}%
1826      #1{\@tmplabel}{\hyper@linkstart{link}{\@tmplink}{\hyper@linkend}}%
1827    \fi%
1828  \def\@setcrefrange#1#2#3{%
1829    \cref@getlabel{#2}{\@labela}%
1830    \cref@getlabel{#3}{\@labelb}%
1831    \if@crefstarred%
1832      #1{\@labela}{\@labelb}{\{}{\}{}{}}%
1833    \else%
1834      \edef\@linka{\cref@hyperref{#2}}%
1835      \edef\@linkb{\cref@hyperref{#3}}%
1836      #1{\@labela}{\@labelb}%
1837      {\hyper@linkstart{link}{\@linka}{\hyper@linkend}}%
1838      {\hyper@linkstart{link}{\@linkb}{\hyper@linkend}}%
1839    \fi}%
1840 }{}% end of \@ifpackageloaded{hyperref}

```

12.6 ntheorem Support

ntheorem If ntheorem is loaded, we need to modify its theorem referencing features so that thref they work with cleverref.

```

1841  \@ifpackageloaded{ntheorem}{%
1842    \PackageInfo{cleverref}{`ntheorem' support loaded}%
1843    \@ifpackagewith{ntheorem}{thref}{%
1844      \PackageWarning{cleverref}{`cleverref' supersedes `ntheorem's `thref'%
1845      option}%
1846      \renewcommand{\thref}{\cref}}%

```

\theorem@prework Newer versions of ntheorem require a call to \theorem@prework when type-setting theorems. If an older version of ntheorem is being used, we just \let it to \relax to make sure it's defined.

```
1847  \@ifundefined{theorem@prework}{\let\theorem@prework\relax}{}%
```

\@thm We modify ntheorem's version of the \@thm macro very slightly, to have it call \refstepcounter with an optional argument containing the theorem type.

```

1848  \gdef\@thm#1#2#3{%
1849    \if@thmmarks%
1850      \stepcounter{end\InTheoType ctr}%
1851    \fi%
1852    \renewcommand{\InTheoType}{#1}%

```

```

1853     \if@thmmarks%
1854         \stepcounter{curr#1ctr}%
1855         \setcounter{end#1ctr}{0}%
1856     \fi%
1857     \refstepcounter[#1]{#2}\% <<< cleveref modification
1858     \theorem@prework%
1859     \thm@topsepadd \theorempostskipamount%
1860     \ifvmode \advance\thm@topsepadd\partopsep\fi%
1861     \trivlist%
1862     \c@topsep \theorempreskipamount%
1863     \c@topsepadd \thm@topsepadd%
1864     \advance\linewidth -\theorem@indent%
1865     \advance\c@totalleftmargin \theorem@indent%
1866     \parshape \c@ne \c@totalleftmargin \linewidth%
1867     \c@ifnextchar[\{\c@ythm{#1}{#2}{#3}\}\{\c@xthm{#1}{#2}{#3}\}]%
1868 }
1869 \}{}% end of \c@ifpackageloaded{ntheorem}

```

12.7 `\newtheorem` Support

`\newtheorem` A `\newtheorem` command provides sufficient information to automatically define a reasonable cross-reference name for theorem-like environments (`ntheorem`'s `thmref` does essentially this). So we modify `\newtheorem` (actually, the lower-level `\c@othm`, `\c@xnthm` and `\c@ynthm` macros) so that it does so. We do this in such a way that default definitions or explicit `\crefname` definitions for theorem-like environments override those produced automatically by our modified `\newtheorem`.

The catch is that, although the `\newtheorem` command provides the singular form, there's no way of reliably deducing the plural form from this. Rather than implement some half-baked attempt at this which will be wrong more often than it's right (especially in languages other than English) and generally cause more trouble than it's worth, we simply define the singular form but leave the plural form undefined. If the latter is ever needed, it will produce a "undefined cross-reference type" warning, prompting the author to provide an appropriate `\crefname` definition themselves.

`\c@othm` After sorting out its arguments, `\newtheorem` calls one of `\c@othm`, `\c@xthm` or `\c@ythm`. We add automatic definitions of `\cref@<type>\name` and `\Cref@<type>\name` to all three of these, and add the theorem-like environment to the list of cross-reference types that need to be defined from components at `\begin{document}`. Since we want explicit `\crefname`'s to override these automatic definitions, we store the definitions in `\cref@<type>\name@preamble`, which are processed at `\begin{document}`) if they haven't been overridden. The default definitions also get stored in `\cref@<type>\name@preamble` later on, so they too will override these automatic definitions, which is what we want.

All this means that these automatic `\newtheorem` definitions will only work when `\newtheorem` is used in the preamble. However, this is also true of (new) cross-reference types defined using `\crefname`, so it doesn't seem worth the sig-

nificant effort of getting the automatic definitions to work within the document body.

```

1870 \let\cref@old@othm\@othm
1871 \def\@othm#1[#2]{%
1872   \edef\@tmpa{\expandafter\noexpand%
1873     \csname cref@\#1@name@preamble\endcsname}%
1874   \expandafter\expandafter\expandafter\gdef\expandafter\%
1875   \expandafter{\MakeLowercase {#3}}%
1876   \edef\@tmpa{\expandafter\noexpand%
1877     \csname Cref@\#1@name@preamble\endcsname}%
1878   \expandafter\expandafter\expandafter\gdef\expandafter\%
1879   \expandafter{\MakeUppercase {#3}}%
1880   \cref@stack@add{#1}{\cref@label@types}%
1881   \cref@old@othm{#1}{#2}{#3}}
1882 \let\cref@old@xnthm\@xnthm
1883 \def\@xnthm#1#2[#3]{%
1884   \edef\@tmpa{\expandafter\noexpand%
1885     \csname cref@\#1@name@preamble\endcsname}%
1886   \expandafter\expandafter\expandafter\gdef\expandafter\%
1887   \expandafter{\MakeLowercase {#2}}%
1888   \edef\@tmpa{\expandafter\noexpand%
1889     \csname Cref@\#1@name@preamble\endcsname}%
1890   \expandafter\expandafter\expandafter\gdef\expandafter\%
1891   \expandafter{\MakeUppercase {#2}}%
1892   \cref@stack@add{#1}{\cref@label@types}%
1893   \cref@old@xnthm{#1}{#2}{#3}}
1894 \let\cref@old@ynthm\@ynthm
1895 \def\@ynthm#1#2{%
1896   \edef\@tmpa{\expandafter\noexpand%
1897     \csname cref@\#1@name@preamble\endcsname}%
1898   \expandafter\expandafter\expandafter\gdef\expandafter\%
1899   \expandafter{\MakeLowercase {#2}}%
1900   \edef\@tmpa{\expandafter\noexpand%
1901     \csname Cref@\#1@name@preamble\endcsname}%
1902   \expandafter\expandafter\expandafter\gdef\expandafter\%
1903   \expandafter{\MakeUppercase {#2}}%
1904   \cref@stack@add{#1}{\cref@label@types}%
1905   \cref@old@ynthm{#1}{#2}}

```

12.8 amsthm Support

amsthm If **amsthm** is loaded, we need to modify its theorem referencing features so that they work with **cleveref**.

```

1906  \@ifpackageloaded{amsthm}{%
1907    \PackageInfo{cleveref}{`amsthm' support loaded}}

```

\@thm We modify **amsthm**'s version of the **\@thm** macro, to have it call **\refstepcounter** with an optional argument containing the theorem type.

```

1908 \let\cref@thmnoarg\@thm

```

```

1909 \def\@thm{\@ifnextchar[{\cref@thmoptarg}{\cref@thmnoarg}}%]
1910 \def\cref@thmoptarg[#1]#2#3#4{%
1911   \ifhmode\unskip\unskip\par\fi%
1912   \normalfont%
1913   \trivlist%
1914   \let\thmheadnl\relax%
1915   \let\thm@swap\@gobble%
1916   \thm@notefont{\fontseries\mddefault\upshape}%
1917   \thm@headpunct{.}% add period after heading
1918   \thm@headsep 5\p0 plus\p0 minus\p0\relax%
1919   \thm@space@setup%
1920   #2% style overrides
1921   \atopsep \thm@preskip           % used by thm head
1922   \atopsepadd \thm@postskip      % used by \endparenv
1923   \def\@tempa{#3}\ifx\empty\@tempa%
1924     \def\@tempa{\@oparg{\begintheorem{#4}{}}[]}%
1925   \else%
1926     \refstepcounter[#1]{#3}% << cleveref modification
1927     \def\@tempa{\@oparg{\begintheorem{#4}{\csname the#3\endcsname}}[]}%
1928   \fi%
1929 \@tempa}

```

`\@ynthm` We also have to modify `amsthm`'s `\@ynthm` command so that it passes the optional argument to `\@thm`. Since `amsmath`'s `\@ynthm` takes a different parameter list to the standard L^AT_EX `\@ynthm` macro, we deliberately override our previous redefinition, and add the code for the automatic `\crefname` definitions directly to this version.

```
1930 \def\@ynthm#1[#2]#3{%
```

Here's the automatic `\crefname` definition.

```

1931 \edef\@tempa{\expandafter\noexpand%
1932   \csname cref@\#1@name@preamble\endcsname}%
1933 \expandafter\expandafter\expandafter\gdef\expandafter%
1934 \@tempa\expandafter{\MakeLowercase #3}%
1935 \edef\@tempa{\expandafter\noexpand%
1936   \csname Cref@\#1@name@preamble\endcsname}%
1937 \expandafter\expandafter\expandafter\gdef\expandafter%
1938 \@tempa\expandafter{\MakeUppercase #3}%
1939 \cref@stack@add{\cref@label@types}%

```

Here's the original `amsthm` `\@ynthm` definition, with the `cleveref` modification.

```

1940 \ifx\relax#2\relax%
1941   \def\@tempa{\@oparg{\@xthm{#1}{#3}}[]}%
1942 \else%
1943   \c@ifundefined{c@#2}{%
1944     \def\@tempa{\@nocounterr{#2}}%
1945   }{%
1946     \c@xp\xdef\csname the#1\endcsname{\c@xp\c@nx\csname the#2\endcsname}%
1947     \toks@{#3}%
1948     \c@xp\xdef\csname#1\endcsname{%
1949       \c@nx\c@thm[#1]{% << new optional argument for theorem name

```

```

1950      \let\@nx\thm@swap%
1951          \if S\thm@swap\@nx\@firstoftwo\else\@nx\@gobble\fi%
1952          \xp\@nx\csname th@\the\thm@style\endcsname}%
1953          {#2}{\the\toks@}}}%
1954      \let\@tempa\relax%
1955  }%
1956 \fi%
1957 \@tempa}

```

\@xnthm Finally, we have to restore the `amsthm` version of `\@xnthm`, which we stored earlier in `\cref@old@xnthm` and redefined. With `amsthm`, `\@xnthm` calls `\@ynthm`, so the automatic `\crefname` definition is already taken care of.

```

1958 \let\@xnthm\cref@old@xnthm
1959 }{}% end of \ifpackageloaded{amsthm}

```

12.9 varioref Support

`varioref` If `varioref` is loaded, we redefine its commands to use `\cref` instead of `\ref` to produce the reference. Since `\cref` can cope with multiple references, We extend the page referencing magic of `\vref` et al. so that they check whether they need to use `\vpagerefrange` instead of `\vpageref`.

```

1960 \@ifpackageloaded{varioref}%
1961     \PackageInfo{cleveref}{`varioref' support loaded}
1962     \PackageInfo{cleveref}{`cleveref' supersedes `varioref's %
1963         \$\backslash\$labelformat command, which will not work}
1964 \AtBeginDocument{%
1965     \def\cref{\vref#1#2}%

```

Since we're modifying the `varioref` commands anyway, we also (by default) take this opportunity to get rid of the irritating spacing issues of `\vref` et al. However, this breaks strict compatibility with the original `varioref` spacing behaviour, so we also provide a `legacyvarioref` option to restore the spacing behaviour, in case full compatibility is required.

```

1966     \if@cref@legacyvarioref%
1967         \leavevmode\unskip\vref@space%
1968     \fi%
1969     \cref{#1}{#2} % space here is deliberate
1970     \begingroup%
1971         \def\@tmpstack{#2,\@nil}%
1972         \cref@stack@topandbottom{\@tmpstack}{\@firstref}{\@lastref}%
1973         \ifx\@lastref\@empty%
1974             \vpageref[\unskip]{#2}%
1975         \else%
1976             \edef\@tmpa{{\@firstref}{\@lastref}}%
1977             \expandafter\def\expandafter\@tmpa\expandafter{%
1978                 \expandafter[\expandafter\unskip\expandafter]%
1979                 \@tmpa}%
1980             \expandafter\vpagerefrange\@tmpa%

```

```

1981      \fi%
1982      \endgroup}
1983 \def\cref@vrefrange#1#2#3{%
1984     \setcrefrange{#2}{#3}{#1}{} \vpagerefrange[\unskip]{#2}{#3}}
1985 \def\cref@fullref#1#2{%
1986     \cref[#1]{#2} % space here is deliberate
1987     \begingroup%
1988     \def\@tmpstack{#2,\@nil}%
1989     \cref@stack@topandbottom{\@tmpstack}{\@firstref}{\@lastref}%
1990     \ifx\@lastref\@empty%
1991         \reftextfaraway{#2}%
1992     \else%
1993         \expandafter\vrefpagenum\expandafter%
1994             \tmpa\expandafter{\@firstref}%
1995         \expandafter\vrefpagenum\expandafter%
1996             \tmpb\expandafter{\@lastref}%
1997         \ifx\@tmpa\@tmpb%
1998             \expandafter\reftextfaraway\expandafter{\@firstref}%
1999         \else%
2000             \edef\@tmpa{\{\@firstref\}\{\@lastref\}}%
2001             \expandafter\reftextpagerange\@tmpa%
2002         \fi%
2003     \fi%
2004 } \endgroup}

```

\vref If `legacyvarior` is set, we only modify the original `varior` commands, and
 \vref* don't define any new ones.

```

\vrefrange
\fullref 2005   \if@cref@legacyvarior%
\vr@f 2006     \def\vr@f#1{\cref@vref{cref}{#1}}
\VR@f 2007     \def\VR@f#1{\cref@vref{Cref}{#1}}
\Vr@f 2008     \renewcommand\vrefrange[3]{\reftextcurrent}{%
2009       \crefrange{#2}{#3} \vpagerefrange[\unskip]{#2}{#3}}
2010     \def\fullref#1{\cref@fullref{cref}{#1}}

```

\vref If we're not providing legacy compatibility with `varior`, we define \vref et al.
 \vref* to be consistent with the other `cleverref` referencing commands. This frees up
 \Vref the starred variants to be used to suppress hyperlinks when `hyperref` is loaded,
 \Vref* as usual.

```

\vrefrange
\vrefrange* 2011  \else%
\VRfrange 2012    \@ifpackageloaded{hyperref}{%
\VRfrange* 2013    \DeclareRobustCommand{\vref}{%
\fullref 2014      \@ifstar{\cref@vrefstar{cref}}{\cref@vref{cref}}}
\fullref* 2015    \DeclareRobustCommand{\Vref}{%
\fullref 2016      \@ifstar{\cref@vrefstar{Cref}}{\cref@vref{Cref}}}
\Fullref 2017    \DeclareRobustCommand{\vrefrange}{%
\Fullref* 2018      \@ifstar{\cref@vrefrangestar{cref}}{\cref@vrefrange{cref}}}
2019      \DeclareRobustCommand{\Vrefrange}{%
2020        \@ifstar{\cref@vrefrangestar{Cref}}{\cref@vrefrange{Cref}}}

```

```

2021     \DeclareRobustCommand{\fullref}{%
2022         \@ifstar{\cref@fullrefstar{cref}}{\cref@fullref{cref}}}
2023     \DeclareRobustCommand{\Fullref}{%
2024         \@ifstar{\cref@fullrefstar{Cref}}{\cref@fullref{Cref}}}
2025     \def\cref@vrefstar#1#2{%
2026         \@crefstarredtrue%
2027         \cref@vref{#1}{#2}%
2028         \@crefstarredfalse}
2029     \def\cref@vrefrangestar#1#2#3{%
2030         \@crefstarredtrue%
2031         \cref@vrefrange{#1}{#2}{#3}%
2032         \@crefstarredfalse}
2033     \def\cref@fullrefstar#1#2{%
2034         \@crefstarredtrue%
2035         \cref@fullref{#1}{#2}%
2036         \@crefstarredfalse}
2037     }{%
2038         \DeclareRobustCommand{\vref}{\cref@vref{cref}}
2039         \DeclareRobustCommand{\Vref}{\cref@vref{Cref}}
2040         \DeclareRobustCommand{\vrefrange}{\cref@vrefrange{cref}}
2041         \DeclareRobustCommand{\Vrefrange}{\cref@vrefrange{Cref}}
2042         \DeclareRobustCommand{\fullref}{\cref@fullref{cref}}
2043         \DeclareRobustCommand{\Fullref}{\cref@fullref{Cref}}
2044     }
2045     \fi%
2046   }% end of \AtBeginDocument
2047 }{}% end of \@ifpackageloaded{varioref}
2048 % \end{macrocode}
2049 %
2050 % \begin{macro}{legacyvarioref}
2051 %   The \option{legacyvarioref} option just sets a flag, checked in the
2052 %   redefinitions set up at the beginning of the document, above.
2053 % \end{macro}
2054 % \begin{macrocode}
2055 \let\if@cref@legacyvarioref\iffalse
2056 \DeclareOption{legacyvarioref}{%
2057   \PackageInfo{cleveref}{legacy ‘varioref’ compatibility enabled}
2058   \let\if@cref@legacyvarioref\iftrue}

```

12.10 Poor Man’s cleveref

poorman The `poorman` option causes a `sed` script to automatically be written. When the original L^AT_EX source file is processed through this script, it strips out all the `cleveref` commands, type-setting all the reference formatting explicitly, and using the standard `\ref` command to produce the references themselves.

```

2059 \DeclareOption{poorman}{%
2060   \PackageInfo{cleveref}{option ‘poorman’ loaded}}

```

`\cref@poorman@text` Define global macro `\cref@poorman@text` to store the text produced by the `\cref`

commands, and open an output stream for writing the script before starting to process the document body.

```
2061 \gdef\cref@poorman@text{%
2062   \AtBeginDocument{%
2063     \newwrite\@crefscript%
2064     \immediate\openout\@crefscript=\jobname.sed}
```

`select@language` If `babel` is loaded, we add to the `\select@language` and `\forreign@language` commands to make them write substitution rules to the script that replace the cross-reference name and conjunction component macros with the appropriate language-dependent names. We use `sed` line-number addresses in the rules to ensure they are only applied to the regions in which that particular language was in use.

Note that we write substitution rules for the *previous* language block when the language is changed, because we need the rules to appear in the script *after* all the cross-reference substitution rules for that language block. `\ref@inputlineno` stores the input-file line-number of the start of the previous language block.

We postpone the redefinitions until the beginning of the document not only to ensure that they don't get clobbered by other package's redefinitions, but also because we don't want the redefinitions to take effect until after `babel` has called `\selectlanguage` for the main language (remember, the substitution rules for this first language block will get written at the next language change).

Note that, since we're writing to the script file within `\AtBeginDocument` and `\AtEndDocument`, this code has to come *after* the above `\AtBeginDocument` code which opens the script file for writing, and *before* the later `\AtEndDocument` code (below) which closes it.

The `\if@cref@switched@language` flag is set when a `babel` language switching command is called. It is checked by `\cref@writelanguagerules` when writing substitution rules.

```
2065 \newif\if@cref@switched@language
2066 \c@ifpackageloaded{babel}{%
2067   \AtBeginDocument{%
2068     \let\cref@old@select@language\select@language
2069     \def\select@language{%
2070       \c@ref@switched@languagetrue%
2071       \c@ref@writelanguagerules%
2072       \c@ref@old@select@language}
2073     \let\cref@old@forreign@language\forreign@language
2074     \def\forreign@language{%
2075       \c@ref@switched@languagetrue%
2076       \c@ref@writelanguagerules%
2077       \c@ref@old@forreign@language}
2078     \edef\c@ref@inputlineno{\the\inputlineno}%
2079   }{}}
```

The final set of substitution rules gets written at the end of the document. This is the only set of rules that gets written if `babel` is not loaded.

```

2080   \AtEndDocument{%
2081     \let\select@language\cref@old@select@language%
2082     \let\forreign@language\cref@old@forreign@language%
2083     \cref@writelanguagerules}

```

\cref@writelanguagerules \cref@writelanguagerules does the grunt work of writing out the necessary substitution rules.

```

2084   \def\cref@writelanguagerules{%
2085     \begingroup%

```

If \if@cref@switched@language hasn't been set, then we must be writing the final set of substitution rules at the end of a document, in which no language switching command was ever used. In which case, the substitution rules don't specify a line-number address.

```

2086     \if@cref@switched@language%
2087       \edef\@address{\cref@inputlineno,\the\inputlineno}%
2088     \else%
2089       \def\@address{}%
2090     \fi%
2091     \expandafter\def\expandafter\cref@poorman@text\expandafter{%
2092       \crefrangeconjunction}%
2093     \expandafter\def\expandafter\@tmpa\expandafter{%
2094       \expandafter{\@address}{\string\crefrangeconjunction}}%
2095     \expandafter\cref@writescript@\@tmpa%
2096     \expandafter\def\expandafter\cref@poorman@text\expandafter{%
2097       \crefrangepreconjunction}%
2098     \expandafter\def\expandafter\@tmpa\expandafter{%
2099       \expandafter{\@address}{\string\crefrangepreconjunction}}%
2100     \expandafter\cref@writescript@\@tmpa%
2101     \expandafter\def\expandafter\cref@poorman@text\expandafter{%
2102       \crefrangepostconjunction}%
2103     \expandafter\def\expandafter\@tmpa\expandafter{%
2104       \expandafter{\@address}{\string\crefrangepostconjunction}}%
2105     \expandafter\cref@writescript@\@tmpa%
2106     \expandafter\def\expandafter\cref@poorman@text\expandafter{%
2107       \crefpairconjunction}%
2108     \expandafter\def\expandafter\@tmpa\expandafter{%
2109       \expandafter{\@address}{\string\crefpairconjunction}}%
2110     \expandafter\cref@writescript@\@tmpa%
2111     \expandafter\def\expandafter\cref@poorman@text\expandafter{%
2112       \crefmiddleconjunction}%
2113     \expandafter\def\expandafter\@tmpa\expandafter{%
2114       \expandafter{\@address}{\string\crefmiddleconjunction}}%
2115     \expandafter\cref@writescript@\@tmpa%
2116     \expandafter\def\expandafter\cref@poorman@text\expandafter{%
2117       \creflastconjunction}%
2118     \expandafter\def\expandafter\@tmpa\expandafter{%
2119       \expandafter{\@address}{\string\creflastconjunction}}%
2120     \expandafter\cref@writescript@\@tmpa%
2121     \expandafter\def\expandafter\cref@poorman@text\expandafter{%

```

```
1222 \crefpairgroupconjunction}%
1223 \expandafter\def\expandafter\@tmpa\expandafter{%
1224   \expandafter{\@address}{\string\crefpairgroupconjunction}}%
1225 \expandafter\cref@writescrpt\@tmpa%
1226 \expandafter\def\expandafter\cref@poorman@text\expandafter{%
1227   \crefmiddlegroupconjunction}%
1228 \expandafter\def\expandafter\@tmpa\expandafter{%
1229   \expandafter{\@address}{\string\crefmiddlegroupconjunction}}%
1230 \expandafter\cref@writescrpt\@tmpa%
1231 \expandafter\def\expandafter\cref@poorman@text\expandafter{%
1232   \creflastgroupconjunction}%
1233 \expandafter\def\expandafter\@tmpa\expandafter{%
1234   \expandafter{\@address}{\string\creflastgroupconjunction}}%
1235 \expandafter\cref@writescrpt\@tmpa%
```

We write substitution rules for all component-derived cross-reference formats, as listed in `\cref@label@types`.

```
2136 \let@\tmpstack\cref@label@types%
2137 \cref@isstackfull{\@tmpstack}%
2138 \@whilesw@if@\cref@stackfull\fif%
```

\cref@*type*@name substitution rules.

```
2139 \edef@\tmpa{\cref@stack@top{\@tmpstack}}%
2140 \expandafter\expandafter\expandafter\def%
2141 \expandafter\expandafter\expandafter\cref@poorman@text%
2142 \expandafter\expandafter\expandafter{%
2143     \csname cref@\@tmpa \name\endcsname}%
2144 \edef@\tmpa{%
2145     \string\cref@\expandafter\noexpand\@tmpa \name\space}%
2146 \expandafter\expandafter\expandafter\def%
2147 \expandafter\expandafter\expandafter\@tmpa%
2148 \expandafter\expandafter\expandafter{%
2149     \expandafter\expandafter\expandafter{%
2150         \expandafter\@address\expandafter}%
2151     \expandafter{\@tmpa}}%
2152 \expandafter\cref@writescript\@tmpa%
```

\cref@*type*@name@plural substitution rules.

```
2153 \edef\@tmpa{\cref@stack@top{\@tmpstack}}%
2154 \expandafter\expandafter\expandafter\def%
2155 \expandafter\expandafter\expandafter\cref@poorman@text%
2156 \expandafter\expandafter\expandafter{%
2157     \csname cref@\@tmpa \cname@plural\endcsname}%
2158 \edef\@tmpa{%
2159     \string\cref@\expandafter\noexpand\@tmpa%
2160     \cname@plural\space}%
2161 \expandafter\expandafter\expandafter\def%
2162 \expandafter\expandafter\expandafter\@tmpa%
2163 \expandafter\expandafter\expandafter{%
2164     \expandafter\expandafter\expandafter{%
2165         \expandafter\expandafter\expandafter\expandafter{%
```

```

2166      \expandafter{\@tmpa}%
2167      \expandafter\cref@writescrpt\@tmpa%
\cref@<type>@name substitution rules.
2168      \edef\@tmpa{\cref@stack@top{\@tmpstack}}%
2169      \expandafter\expandafter\expandafter\def%
2170      \expandafter\expandafter\expandafter\cref@poorman@text%
2171      \expandafter\expandafter\expandafter{%
2172      \csname Cref@\@tmpa @name\endcsname}%
2173      \edef\@tmpa{%
2174      \string\cref@\expandafter\noexpand\@tmpa @name\space}%
2175      \expandafter\expandafter\expandafter\def%
2176      \expandafter\expandafter\expandafter\@tmpa%
2177      \expandafter\expandafter\expandafter{%
2178      \expandafter\expandafter\expandafter%
2179      {\expandafter\@address\expandafter}%
2180      \expandafter{\@tmpa}%
2181      \expandafter\cref@writescrpt\@tmpa%
\cref@<type>@name@plural substitution rules.
2182      \edef\@tmpa{\cref@stack@top{\@tmpstack}}%
2183      \expandafter\expandafter\expandafter\def%
2184      \expandafter\expandafter\expandafter\cref@poorman@text%
2185      \expandafter\expandafter\expandafter{%
2186      \csname Cref@\@tmpa @name@plural\endcsname}%
2187      \edef\@tmpa{%
2188      \string\cref@\expandafter\noexpand\@tmpa%
2189      @name@plural\space}%
2190      \expandafter\expandafter\expandafter\def%
2191      \expandafter\expandafter\expandafter\@tmpa%
2192      \expandafter\expandafter\expandafter{%
2193      \expandafter\expandafter\expandafter%
2194      {\expandafter\@address\expandafter}%
2195      \expandafter{\@tmpa}%
2196      \expandafter\cref@writescrpt\@tmpa%

```

After the loop over cross-reference types, we set `\cref@inputlineno` to the current input-file line, in preparation for the next language block.

```

2197      \cref@stack@pop{\@tmpstack}%
2198      \cref@isstackfull{\@tmpstack}%
2199      \endgroup%
2200      \edef\cref@inputlineno{\the\inputlineno}%

```

After processing the document body, we re-read in the temporary script file, and write it out again to the final `sed` script file, escaping regexp special characters in the process. The escaping is carried out by turning the regexp special characters into active characters, and defining them to expand to their escaped form. This involves a lot of juggling of catcodes and lccodes!

Both `\DeclareOption` and `\AtEndDocument` store their arguments in token lists, so all the following TeXcode is already tokenised long before it is expanded

and evaluated. Thus there is no (easy) way to change the catcodes of the characters appearing here before they are tokenised. In one way this is convenient: the catcode changes we make don't "take" until evaluated, so we can continue to use the standard TeX characters (\, {, } etc.) even after the lines containing the catcode commands. But in another, more significant, way, it is very inconvenient: it makes it difficult to define the regexp special characters as active characters, since it's impossible to directly create tokens with the correct char- and catcodes.

We get around this by creating the unusual charcode/catcode combinations using the \lowercase trick (\lowercase changes the charcodes of all characters in its argument to their lccodes, but *leaves their catcodes alone*). That way, the argument of \AtEndDocument is tokenised correctly, and when it comes to be expanded and evaluated, the \lowercase commands create tokens with the correct char- and catcodes.

```

2201  \AtEndDocument{%
2202    \immediate\closeout\@crefscript%
2203    \newread\@crefscript%
2204    \immediate\openin\@crefscript=\jobname.sed%
2205    \begingroup%
2206      \newif\if@not@eof%
2207      \def\@eof{\par }%

```

Change catcodes of regexp special characters to make them active characters and define them to expand to their escaped forms. Change those of TeXspecial characters to make them normal letters.

```

2208    \catcode`.=13 \catcode`*=13
2209    \catcode`[=13 \catcode`]=13
2210    \catcode`^=13 \catcode`$=13 %$
2211    \catcode`\=0 \catcode`<=1 \catcode`>=2
2212    \catcode`\|=13 \catcode`\{=12 \catcode`\}=12 \catcode`_=12
2213    \lccode`=/92
2214    \lccode`~=92\lowercase{\def~{\string/\string/}}%
2215    \lccode`~=42\lowercase{\def~{\string/\string*}}%
2216    \lccode`~=46\lowercase{\def~{\string/\string.}}%
2217    \lccode`~=91\lowercase{\def~{\string/\string[}}%
2218    \lccode`~=93\lowercase{\def~{\string/\string]}}%
2219    \lccode`~=94\lowercase{\def~{\string/\string^}}%
2220    \lccode`~=36\lowercase{\def~{\string/\string$}}% $
2221    \lccode`~=0 \lccode`/=0 \catcode`'=12

```

Read lines from the temporary script file, expand them to escape regexp special characters, and store them in \cref@poorman@text.

```

2222  \def\cref@poorman@text{}%
2223  \immediate\read\@crefscript to \tmpa%
2224  \ifx\@tmpa\@eof%
2225    \@not@eoffalse%
2226  \else%
2227    \@not@eoftrue%
2228    \edef\@tmpa{\@tmpa}%
2229  \fi%

```

```

2230     \@whilesw\if@not@eof\fi{%
2231         \expandafter\g@addto@macro\expandafter%
2232             \cref@poorman@text\expandafter{\@tmpa^~J}%
2233             \immediate\read\@crefscript to \@tmpa%
2234             \ifx\@tmpa\@eof%
2235                 \@not@eoffalse%
2236             \else%
2237                 \@not@eoftrue%
2238                 \edef\@tmpaf{\@tmpa}%
2239             \fi}%
2240     \endgroup%
2241     \immediate\closein\@crefscript%

```

Add some rules to remove other `\cleveref` commands. We use the `\lowercase` trick again for writing the \, { and } characters. (This could be done in other ways, but since we're in `\lowercase` mood, why not stick with it.)

```

2242     \begingroup%
2243         \lccode`|=92 \lccode`<=123 \lccode`C=67
2244         \lowercase{\def\@tmpaf{[%
2245             s/||label|[[^]]*|]/||label/g}}
2246         \expandafter\g@addto@macro\expandafter%
2247             \cref@poorman@text\expandafter{\@tmpa^~J}%
2248             \lowercase{\edef\@tmpa{s/||usepackage|([.*])|<0,1|><\cleveref>/g}}%
2249             \expandafter\g@addto@macro\expandafter%
2250                 \cref@poorman@text\expandafter{\@tmpa^~J}%
2251             \lowercase{\edef\@tmpa{s/||[cC]reformat<.*><.*>/g}}%
2252             \expandafter\g@addto@macro\expandafter%
2253                 \cref@poorman@text\expandafter{\@tmpa^~J}%
2254             \lowercase{\edef\@tmpa{s/||[cC]refrangingformat<.*><.*>/g}}%
2255             \expandafter\g@addto@macro\expandafter%
2256                 \cref@poorman@text\expandafter{\@tmpa^~J}%
2257             \lowercase{\edef\@tmpa{s/||[cC]refmultiformat<.*><.*><.*>/g}}%
2258             \expandafter\g@addto@macro\expandafter%
2259                 \cref@poorman@text\expandafter{\@tmpa^~J}%
2260             \lowercase{\edef\@tmpaf{%
2261                 s/|[cC]refrangemultiformat<.*><.*><.*>/g}}%
2262             \expandafter\g@addto@macro\expandafter%
2263                 \cref@poorman@text\expandafter{\@tmpa^~J}%
2264             \lowercase{\edef\@tmpa{s/|[cC]refname<.*><.*>/g}}%
2265             \expandafter\g@addto@macro\expandafter%
2266                 \cref@poorman@text\expandafter{\@tmpa^~J}%
2267             \lowercase{\edef\@tmpa{s/|[cC]reflabelformat<.*><.*>/g}}%
2268             \expandafter\g@addto@macro\expandafter%
2269                 \cref@poorman@text\expandafter{\@tmpa^~J}%
2270             \lowercase{\edef\@tmpa{s/|[cC]refrangelabelformat<.*><.*>/g}}%
2271             \expandafter\g@addto@macro\expandafter%
2272                 \cref@poorman@text\expandafter{\@tmpa^~J}%
2273             \lowercase{\edef\@tmpa{s/|[cC]refdefaultlabelformat<.*>/g}}%
2274             \expandafter\g@addto@macro\expandafter%
2275                 \cref@poorman@text\expandafter{\@tmpa^~J}%

```

```

2276      \lowercase{\edef\@tmpa{%
2277          s/||renewcommand<||crefpairconjunction><.*>//g}%%
2278          \expandafter\g@addto@macro\expandafter%
2279              \cref@poorman@text\expandafter{\@tmpa^^J}%
2280      \lowercase{\edef\@tmpa{%
2281          s/||renewcommand<||crefpairgroupconjunction><.*>//g}%%
2282          \expandafter\g@addto@macro\expandafter%
2283              \cref@poorman@text\expandafter{\@tmpa^^J}%
2284      \lowercase{\edef\@tmpa{%
2285          s/||renewcommand<||crefmiddleconjunction><.*>//g}%%
2286          \expandafter\g@addto@macro\expandafter%
2287              \cref@poorman@text\expandafter{\@tmpa^^J}%
2288      \lowercase{\edef\@tmpa{%
2289          s/||renewcommand<||crefmiddlegroupconjunction><.*>//g}%%
2290          \expandafter\g@addto@macro\expandafter%
2291              \cref@poorman@text\expandafter{\@tmpa^^J}%
2292      \lowercase{\edef\@tmpa{%
2293          s/||renewcommand<||creflastconjunction><.*>//g}%%
2294          \expandafter\g@addto@macro\expandafter%
2295              \cref@poorman@text\expandafter{\@tmpa^^J}%
2296      \lowercase{\edef\@tmpa{%
2297          s/||renewcommand<||creflastgroupconjunction><.*>//g}%%
2298          \expandafter\g@addto@macro\expandafter%
2299              \cref@poorman@text\expandafter{\@tmpa^^J}%
2300      \lowercase{\edef\@tmpa{s/||renewcommand<|[cC]ref><.*>//g}%%
2301          \expandafter\g@addto@macro\expandafter%
2302              \cref@poorman@text\expandafter{\@tmpa^^J}%
2303      \lowercase{\edef\@tmpa{s/||renewcommand<|[cC]refrange><.*>//g}%%
2304          \expandafter\g@addto@macro\expandafter%
2305              \cref@poorman@text\expandafter{\@tmpa^^J}%
2306      \endgroup%

```

Overwrite the script file with the new, escaped regexp rules.

```

2307      \newwrite\@crefscript%
2308      \immediate\openout\@crefscript=\jobname.sed%
2309      \immediate\write\@crefscript{\cref@poorman@text}%
2310      \immediate\closeout\@crefscript%
2311 }% end of \AtEndDocument

```

\cref@writescript The **\cref@writescript** utility macro does the actual writing of the substitution rule to the script. The first argument is the “address”, the second argument is the regexp pattern to match, whilst the substitution must be stored in **\cref@poorman@text**.

```

2312      \def\cref@getmeaning#1{\expandafter\cref@getmeaning\meaning#1\@nil}
2313      \def\cref@getmeaning#1->#2\@nil{#2}
2314      \def\cref@writescript#1#2{%
2315          \edef\@tmpa{\cref@getmeaning{\cref@poorman@text}}%
2316          \immediate\write\@crefscript{\#1 s/#2/\@tmpa/g}

```

\cref Redefine the user-level referencing commands so that they write a substitution
\Cref
\crefrange
\Crefrange
\crefstar
\Crefstar
\crefnostar
\Crefnostar
\crefrangestar
\Crefrangestar
\crefrangenostar
\Crefrangenostar

rule for the reference to the script, as well as type-setting the reference itself.

We use a temporary `\@tmpa` macro that makes use of the fact that the first character of #1 is “c” for lower-case and “C” for upper-case in these commands, in order to write out the correct capitalisation in the substitution.

FIXME: We only resort to this because `\string#1` doesn’t work. But there *must* be a better way to get a backslash character into the token stream, obviating the need for the ugly `\@tmpa` macro.

```

2317  \@ifpackageloaded{hyperref}{%
2318    \def\@crefnostar#1#2{%
2319      \gdef\cref@poorman@text{}%
2320      \cref{#1}{#2}%
2321      \def\@tmpa##1##2\@nil{%
2322        \if##1c%
2323          \cref@writescr{}{\string\cref\string{#2\string}}%
2324        \else%
2325          \cref@writescr{}{\string\cref\string{#2\string}}%
2326        \fi}%
2327      \@tmpa#1\@nil}
2328    \def\@crefstar#1#2{%
2329      \gdef\cref@poorman@text{}%
2330      \crefstarredtrue\cref{#1}{#2}\crefstarredfalse%
2331      \def\@tmpa##1##2\@nil{%
2332        \if##1c%
2333          \cref@writescr{}{\string\cref*\string{#2\string}}%
2334        \else%
2335          \cref@writescr{}{\string\cref*\string{#2\string}}%
2336        \fi}%
2337      \@tmpa#1\@nil}
2338    \def\@crefrangenostar#1#2#3{%
2339      \gdef\cref@poorman@text{}%
2340      \setcrefrange{#2}{#3}{#1}{}%
2341      \def\@tmpa##1##2\@nil{%
2342        \if##1c%
2343          \cref@writescr{}{%
2344            \string\crefrange\string{#2\string}\string{#3\string}}%
2345        \else%
2346          \cref@writescr{}{%
2347            \string\Crefrange\string{#2\string}\string{#3\string}}%
2348        \fi}%
2349      \@tmpa#1\@nil}
2350    \def\@crefrangestar#1#2#3{%
2351      \gdef\cref@poorman@text{}%
2352      \crefstarredtrue\setcrefrange{#2}{#3}{#1}{}\crefstarredfalse%
2353      \def\@tmpa##1##2\@nil{%
2354        \if##1c%
2355          \cref@writescr{}{%
2356            \string\crefrange*\string{#2\string}\string{#3\string}}%
2357        \else%
2358          \cref@writescr{}{%

```

```

2359         \string\Crefrange*\string{\#2\string}\string{\#3\string}}}%
2360         \fi}%
2361         \atmpa#1\@nil}
2362 %
2363 }{%
2364     \DeclareRobustCommand{\cref}[1]{%
2365         \edef\cref@poorman@text{}%
2366         \cref{cref}{#1}%
2367         \cref@writescr{}{\string\cref\string{\#1\string}}}
2368     \DeclareRobustCommand{\Cref}[1]{%
2369         \edef\cref@poorman@text{}%
2370         \cref{Cref}{#1}%
2371         \cref@writescr{}{\string\cref\string{\#1\string}}}
2372     \DeclareRobustCommand{\crefrange}[2]{%
2373         \edef\cref@poorman@text{}%
2374         \setcrefrange{#1}{#2}{\cref}{}%
2375         \cref@writescr{}{%
2376             \string\crefrange\string{\#1\string}\string{\#2\string}}}
2377     \DeclareRobustCommand{\Crefrange}[2]{%
2378         \edef\cref@poorman@text{}%
2379         \setcrefrange{#1}{#2}{\Cref}{}%
2380         \cref@writescr{}{%
2381             \string\Crefrange\string{\#1\string}\string{\#2\string}}}
2382 }

```

\vref If varioref is loaded, do the same for the \vref et al. commands. Note that we \vref* now need to set the \if@crefstarred flag for the starred variant \vref* even if \Vref legacyvarioef is set and it changes the spacing rather than suppressing hyper-\Vref* links, so that we can write the correct substitution rule.

```

\vrefrange 2383  \@ifpackageloaded{varioref}{%
\vrefrange* 2384  \AtBeginDocument{%
\Vrefrange 2385  \if@cref@legacyvarioef%
\Vrefrange* 2386  \DeclareRobustCommand{\vref}{%
\fullref 2387  \ifstar{\cref@vrefstar{cref}}{\cref@vref{cref}}}
\fullref* 2388  \def\cref@vrefstar#1#2{%
\Fullref 2389  \crefstarredtrue\cref@vref{#1}{#2}\@crefstarredfalse}
\Fullref* 2390  \fi%
2391  \def\cref@vref#1#2{%
2392  \gdef\cref@poorman@text{}%
2393  \if@cref@legacyvarioef%
2394  \leavevmode\unskip\vref@space%
2395  \fi%
2396  \begingroup%

```

If legacyvarioef is set, \vref* shouldn't suppress hyper-links, so temporarily disable then restore the flag whilst type-setting the cross-reference.

```

2397  \let\if@tmp\if@crefstarred%
2398  \if@cref@legacyvarioef\@crefstarredfalse\fi%
2399  \cref{#1}{#2} % space here is deliberate
2400  \let\if@crefstarred\if@tmp%

```

```

2401 \def\@tmpstack{\#2,\@nil}%
2402 \cref@stack@topandbottom{\@tmpstack}{\@firstref}{\@lastref}%
2403 \ifx\@lastref\@empty%
2404   \vpageref[\unskip]{#2}%
2405   \g@addto@macro\cref@poorman@text{ \vpageref[\unskip]{#2}}%
2406 \else%
2407   \g@addto@macro\cref@poorman@text{ }%
2408   \edef\@tmpa{\@firstref\@lastref}%
2409   \expandafter\def\expandafter\@tmpa\expandafter{%
2410     \expandafter[\expandafter\unskip\expandafter]%
2411     \@tmpa}%
2412   \expandafter\expandafter\expandafter\@tmpa%
2413   \expandafter\g@addto@macro\expandafter\cref@poorman@text{%
2414     \expandafter{\expandafter\expandafter\expandafter\expandafter\expandafter\@tmpa}}%
2415 \fi%
2416 \def\@tmpa##1##2\@nil{%
2417   \if##1c%
2418     \if@crefstarred%
2419       \cref@writescript{}{\string\vref*\string{#2\string}}%
2420     \else%
2421       \cref@writescript{}{\string\vref\string{#2\string}}%
2422     \fi%
2423   \else%
2424     \if@crefstarred%
2425       \cref@writescript{}{\string\Vref*\string{#2\string}}%
2426     \else%
2427       \cref@writescript{}{\string\Vref\string{#2\string}}%
2428     \fi%
2429   \fi}%
2430   \@tmpa#1\@nil%
2431 \endgroup}
2432 %
2433 \def\cref@vrefrange#1#2#3{%
2434   \gdef\cref@poorman@text{}%
2435   \setcrefrange{#2}{#3}{#1}{ } \vpagerefrange[\unskip]{#2}{#3}%
2436   \g@addto@macro\cref@poorman@text{ \vpagerefrange[\unskip]{#2}{#3}}%■
2437 \def\@tmpa##1##2\@nil{%
2438   \if##1c%
2439     \if@crefstarred%
2440       \cref@writescript{}{%
2441         \string\vrefrange*\string{#2\string}\string{#3\string}}%
2442     \else%
2443       \cref@writescript{}{%
2444         \string\vrefrange\string{#2\string}\string{#3\string}}%
2445     \fi%
2446   \else%
2447     \if@crefstarred%
2448       \cref@writescript{}{%
2449         \string\Vrefrange*\string{#2\string}\string{#3\string}}%
2450   \else%

```

```

2451           \cref@writescript{}{%
2452             \string\Vrefrange\string{\#2\string}\string{\#3\string}}{%
2453               \fi%
2454             \fi}%
2455           \tmpa#1\@nil}
2456 %
2457 \def\cref@fullref#1#2{%
2458   \gdef\cref@poorman@text{}%
2459   \begingroup%
2460     \cref{\#1}{\#2} % space here is deliberate
2461     \def\@tmpstack{\#2,\@nil}%
2462     \cref@stack@topandbottom{\@tmpstack}{\@firstref}{\@lastref}%
2463     \ifx\@lastref\@empty%
2464       \reftextfaraway{\#2}%
2465       \def\@pageref{\reftextfaraway{\#1}}%
2466     \else%
2467       \expandafter\vrefpagenum\expandafter%
2468         \tmpa\expandafter{\@firstref}%
2469       \expandafter\vrefpagenum\expandafter%
2470         \tmpb\expandafter{\@lastref}%
2471       \ifx\@tmpa\@tmpb%
2472         \expandafter\reftextfaraway\expandafter{\@firstref}%
2473         \expandafter\def\expandafter\@pageref\expandafter{%
2474           \expandafter\reftextfaraway\expandafter{\@firstref}}%
2475     \else%
2476       \edef\@tmpa{\{\@firstref\{\@lastref\}}%
2477       \expandafter\reftextpagerange\@tmpa%
2478       \expandafter\def\expandafter\@pageref\expandafter{%
2479         \expandafter\reftextpagerange\@tmpa}%
2480     \fi%
2481   \fi%
2482   \g@addto@macro\cref@poorman@text{ }%
2483   \expandafter\g@addto@macro\expandafter\cref@poorman@text{%
2484     \expandafter{\@pageref}}%
2485   \def\@tmpa##1##2\@nil{%
2486     \if##1c%
2487       \if@crefstarred%
2488         \cref@writescript{}{\string\fullref*\string{\#2\string}}{%
2489           \else%
2490             \cref@writescript{}{\string\fullref\string{\#2\string}}{%
2491               \fi}%
2492             \else%
2493               \if@crefstarred%
2494                 \cref@writescript{}{\string\Fullref*\string{\#2\string}}{%
2495                   \else%
2496                     \cref@writescript{}{\string\Fullref\string{\#2\string}}{%
2497                       \fi}%
2498                     \fi}%
2499           \tmpa#1\@nil%
2500         \endgroup}

```

```

2501      }% end of \AtBeginDocument
2502  }{}}% end of \@ifpackageloaded{varioref}

\@setceref Redefine \@setceref and \@setrangeref, as well as the conjunction macros
\@setcerefrange \@setceref@middlegroupconjunction, \@setceref@lastgroupconjunction and
\@setceref@pairgroupconjunction, to append text they type-set to
the \cref@poorman@text macro, as well as actually doing the type-setting.
2503  \def\@setceref@pairgroupconjunction{%
2504    \crefpairgroupconjunction%
2505    \expandafter\g@addto@macro\expandafter\cref@poorman@text%
2506    \expandafter{\crefpairgroupconjunction}%
2507  \def\@setceref@middlegroupconjunction{%
2508    \crefmiddlegroupconjunction%
2509    \expandafter\g@addto@macro\expandafter\cref@poorman@text%
2510    \expandafter{\crefmiddlegroupconjunction}%
2511  \def\@setceref@lastgroupconjunction{%
2512    \creflastgroupconjunction%
2513    \expandafter\g@addto@macro\expandafter\cref@poorman@text%
2514    \expandafter{\creflastgroupconjunction}%
2515  \@ifpackageloaded{hyperref}{%
2516    \def\@setceref#1#2{%
2517      \cref@getlabel{#2}{\@tmplabel}%
2518      \if@crefstarred%
2519        #1{\@tmplabel}{}{%
2520        \expandafter\g@addto@macro\expandafter\cref@poorman@text%
2521        \expandafter{\#1{\ref*{#2}}{}{}}%
2522      \else%
2523        \edef\@tmplink{\cref@hyperref{#2}}%
2524        #1{\@tmplabel}{\hyper@linkstart{link}{\@tmplink}}%
2525        {\hyper@linkend}%
2526        \expandafter\g@addto@macro\expandafter\cref@poorman@text%
2527        \expandafter{\#1{\ref{#2}}{}{}}%
2528      \fi}
2529    \def\@setcerefrange#1#2#3{%
2530      \cref@getlabel{#2}{\@labela}%
2531      \cref@getlabel{#3}{\@labelb}%
2532      \if@crefstarred%
2533        #1{\@labela}{\@labelb}{}{}{}{%
2534        \expandafter\g@addto@macro\expandafter\cref@poorman@text%
2535        \expandafter{\#1{\ref*{#2}}{\ref*{#3}}{}{}{}{}}%
2536      \else%
2537        \edef\@linka{\cref@hyperref{#2}}%
2538        \edef\@linkb{\cref@hyperref{#3}}%
2539        #1{\@labela}{\@labelb}{%
2540          {\hyper@linkstart{link}{\@linka}}{\hyper@linkend}%
2541          {\hyper@linkstart{link}{\@linkb}}{\hyper@linkend}%
2542          \expandafter\g@addto@macro\expandafter\cref@poorman@text%
2543          \expandafter{\#1{\ref{#2}}{\ref{#3}}{}{}{}{}}%
2544        \fi}
2545    }{%

```

```

2546   \let\old@@setceref\@@setceref%
2547   \let\old@@setcrefrange\@@setcrefrange%
2548   \def\@@setceref#1#2{%
2549     \old@@setceref{\#1}{\#2}%
2550     \expandafter\g@addto@macro\expandafter{%
2551       \expandafter\cref@poorman@text\expandafter}\expandafter{%
2552       #1{\ref{\#2}}{}{}}
2553   \def\@@setcrefrange#1#2#3{%
2554     \old@@setcrefrange{\#1}{\#2}{\#3}%
2555     \expandafter\g@addto@macro%
2556       \expandafter{\expandafter\cref@poorman@text\expandafter}%
2557       \expandafter{\#1{\ref{\#2}}{\ref{\#3}}{}{}{}}
2558   }
2559 }% end of poorman option

```

12.11 Sort and Compress options

`sort` The `sort`, `compress` or `nosort` options determine whether to sort and/or compress lists of multiple references (default is to do both). They work simply by setting `nosort` the `\if@cref@sort` and `\if@cref@compress` flags appropriately.

```

\if@cref@sort 2560 \newif\if@cref@sort
\if@cref@compress 2561 \newif\if@cref@compress
    Default is to both sort and compress references.
2562 \cref@sorttrue
2563 \cref@compresstrue
    Options override default.
2564 \DeclareOption{sort}{%
2565   \PackageInfo{cleveref}{sorting but not compressing references}%
2566   \cref@sorttrue
2567   \cref@compressfalse}
2568 \DeclareOption{compress}{%
2569   \PackageInfo{cleveref}{compressing but not sorting references}%
2570   \cref@sortfalse
2571   \cref@compresstrue}
2572 \DeclareOption{sort&compress}{%
2573   \PackageInfo{cleveref}{sorting and compressing references}%
2574   \cref@sorttrue
2575   \cref@compresstrue}
2576 \DeclareOption{nosort}{%
2577   \PackageInfo{cleveref}{neither sorting nor compressing references}%
2578   \cref@sortfalse
2579   \cref@compressfalse}

```

12.12 Capitalise option

`capitalise` The `capitalise` option causes `cleveref` to always use the `\Cref*` variants for `\if@cref@capitalise` type-setting cross-references, so that cross-reference names are always capitalised.

```
2580 \newif\if@cref@capitalise
```

Disabled by default.

```
2581 \cref@capitalisefalse
      Option overrides default.
2582 \DeclareOption{capitalise}{%
2583   \PackageInfo{cleveref}{always capitalise cross-reference names}
2584   \cref@capitalisetrue}
2585 \DeclareOption{capitalize}{%
2586   \PackageInfo{cleveref}{always capitalise cross-reference names}
2587   \cref@capitalisetrue}
```

12.13 Language and babel Support

Default reference formats for different languages are supported via package options, in the usual way.

Any contributions of translations for missing languages are most welcome! If you can contribute definitions for a missing language, ideally you should add them below the existing ones (using those as a model), generate a patch against the original `cleveref.dtx` file, and send the patch by email to the package author. However, if you don't know how to produce a patch, you can instead just send the translations as a plain text file.

`\crefdefaultlabelformat` We first define the default label formats, which don't depend on language. We
`\creflabelformat` override the default format for equations, to follow the near universal convention of enclosing equation labels in brackets.

```
2588 \crefdefaultlabelformat{\textup{(#2#1#3)}}
2589 \creflabelformat{equation}{\textup{(#2#1#3)}}
```

`\cref@addto` Utility macro to use instead of `babel`'s flawed `\addto` (copied and modified from `variorom`).

```
2590 \def\cref@addto#1#2{%
2591   \temptokena{#2}%
2592   \ifx#1\undefined%
2593     \edef#1{\the\temptokena}%
2594   \else%
2595     \toks@\expandafter{#1}%
2596     \edef#1{\the\toks@\the\temptokena}%
2597   \fi%
2598   \temptokena{}\toks@\temptokena%
2599 }
2600 \onlypreamble\cref@addto
```

Passing a language option to `cleveref` defines the cross-reference names and conjunctions as appropriate for that language. We can't make the definitions straight away, since they would prevent the automatic definition of the other capitalisation variant from working if the user chooses to change a default definition in the preamble, so we postpone them until the beginning of the document. However, if each language option were to simply to define any formats that aren't already

defined by the end of the preamble, the *first* language option would override all the others. Unfortunately, the convention in L^AT_EX and `babel` is for the *last* language option to take precedence. So we instead used the `\crefname@preamble` command to save the definitions in `\cref@\meta{type}@name@preamble` etc., and after all the language options have been processed, use the contents of these to set the default definitions for any undefined formats.

For `babel` support, we add the appropriate redefinitions to the `\extras<language>` macro, which is called by `babel`'s `\selectlanguage` at al. commands. The main language (the last one listed in the options) is set up by an automatic call to `\selectlanguage` at the beginning of the document, which would clobber any redefinitions made by the user in the preamble. To avoid this, we postpone adding the redefinitions to `\extras<language>` until the beginning of the document. Since `cleveref` must always be loaded *after* `babel`, the redefinitions won't be added to `\extras<language>` until *after* `babel` has already called `\selectlanguage` for the main language. Thus the redefinitions will only be in effect when `\selectlanguage` is called explicitly within the document. (The definitions for the main language are taken care of by the language options passed to `cleveref`, independently of `babel`.)

Note that we define both capitalisation variants explicitly throughout, rather than relying on the automatic definition of the other variant, in order to make the code produced by the poor man's `sed` script slightly cleaner.

`english` English definitions (these are used by default).

```
2601 \DeclareOption{english}{%
2602   \PackageInfo{cleveref}{loaded 'english' language definitions}}
```

First, we set up the definitions used at the beginning of the document to define the formats created by the document preamble.

```
2603 \AtBeginDocument{%
2604   \def\crefrangeconjunction@preamble{ to~}%
2605   \def\crefrangepreconjunction@preamble{}%
2606   \def\crefrangepostconjunction@preamble{}%
2607   \def\crefpairconjunction@preamble{ and~}%
2608   \def\crefmiddleconjunction@preamble{, }%
2609   \def\creflastconjunction@preamble{ and~}%
```

We have to define the group conjunctions explicitly here, rather than relying on fall-back definitions in terms of the above conjunctions (see Section 12.13.1), in case any other language option defines them explicitly and we need to override those.

```
2610   \def\crefpairgroupconjunction@preamble{ and~}%
2611   \def\crefmiddlegroupconjunction@preamble{, }%
2612   \def\creflastgroupconjunction@preamble{, and~}%
2613   \Crefname@preamble{equation}{Equation}{Equations}%
2614   \Crefname@preamble{chapter}{Chapter}{Chapters}%
2615   \Crefname@preamble{section}{Section}{Sections}%
2616   \Crefname@preamble{appendix}{Appendix}{Appendices}%
2617   \Crefname@preamble{enumi}{Item}{Items}%
```

```

2618 \Crefname@preamble{footnote}{Footnote}{Footnotes}%
2619 \Crefname@preamble{figure}{Figure}{Figures}%
2620 \Crefname@preamble{table}{Table}{Tables}%
2621 \Crefname@preamble{theorem}{Theorem}{Theorems}%
2622 \Crefname@preamble{lemma}{Lemma}{Lemmas}%
2623 \Crefname@preamble{corollary}{Corollary}{Corollaries}%
2624 \Crefname@preamble{proposition}{Proposition}{Propositions}%
2625 \Crefname@preamble{definition}{Definition}{Definitions}%
2626 \Crefname@preamble{result}{Result}{Results}%
2627 \Crefname@preamble{example}{Example}{Examples}%
2628 \Crefname@preamble{remark}{Remark}{Remarks}%
2629 \Crefname@preamble{note}{Note}{Notes}%
2630 \if@cref@capitalise%
2631     \crefname@preamble{equation}{Eq.}{Eqs.}%
2632     \crefname@preamble{chapter}{Chapter}{Chapters}%
2633     \crefname@preamble{section}{Section}{Sections}%
2634     \crefname@preamble{appendix}{Appendix}{Appendices}%
2635     \crefname@preamble{enumi}{Item}{Items}%
2636     \crefname@preamble{footnote}{Footnote}{Footnotes}%
2637     \crefname@preamble{figure}{Fig.}{Figs.}%
2638     \crefname@preamble{table}{Table}{Tables}%
2639     \crefname@preamble{theorem}{Theorem}{Theorems}%
2640     \crefname@preamble{lemma}{Lemma}{Lemmas}%
2641     \crefname@preamble{corollary}{Corollary}{Corollaries}%
2642     \crefname@preamble{proposition}{Proposition}{Propositions}%
2643     \crefname@preamble{definition}{Definition}{Definitions}%
2644     \crefname@preamble{result}{Result}{Results}%
2645     \crefname@preamble{example}{Example}{Examples}%
2646     \crefname@preamble{remark}{Remark}{Remarks}%
2647     \crefname@preamble{note}{Note}{Notes}%
2648 \else%
2649     \crefname@preamble{equation}{eq.}{eqs.}%
2650     \crefname@preamble{chapter}{chapter}{chapters}%
2651     \crefname@preamble{section}{section}{sections}%
2652     \crefname@preamble{appendix}{appendix}{appendices}%
2653     \crefname@preamble{enumi}{item}{items}%
2654     \crefname@preamble{footnote}{footnote}{footnotes}%
2655     \crefname@preamble{figure}{fig.}{figs.}%
2656     \crefname@preamble{table}{table}{tables}%
2657     \crefname@preamble{theorem}{theorem}{theorems}%
2658     \crefname@preamble{lemma}{lemma}{lemmas}%
2659     \crefname@preamble{corollary}{corollary}{corollaries}%
2660     \crefname@preamble{proposition}{proposition}{propositions}%
2661     \crefname@preamble{definition}{definition}{definitions}%
2662     \crefname@preamble{result}{result}{results}%
2663     \crefname@preamble{example}{example}{examples}%
2664     \crefname@preamble{remark}{remark}{remarks}%
2665     \crefname@preamble{note}{note}{notes}%
2666 \fi%
2667 \def\cref@language{english}%

```

Next, we add the definitions to `\extras...` so that babel's `\selectlanguage` command will change the format appropriately.

```

2668     \cref@addto\extrasenglish{%
2669         \renewcommand{\crefrangeconjunction}{ to~}%
2670         \renewcommand{\crefrangepreconjunction}{ }%
2671         \renewcommand{\crefrangepostconjunction}{ }%
2672         \renewcommand{\crefpairconjunction}{ and~}%
2673         \renewcommand{\crefmiddleconjunction}{, }%
2674         \renewcommand{\creflastconjunction}{ and~}%
2675         \renewcommand{\crefpairgroupconjunction}{ and~}%
2676         \renewcommand{\crefmiddlegroupconjunction}{, }%
2677         \renewcommand{\creflastgroupconjunction}{, and~}%
2678         \Crefname{equation}{Equation}{Equations}%
2679         \Crefname{chapter}{Chapter}{Chapters}%
2680         \Crefname{section}{Section}{Sections}%
2681         \Crefname{subsection}{Section}{Sections}%
2682         \Crefname{subsubsection}{Section}{Sections}%
2683         \Crefname{appendix}{Appendix}{Appendices}%
2684         \Crefname{subappendix}{Appendix}{Appendices}%
2685         \Crefname{subsubappendix}{Appendix}{Appendices}%
2686         \Crefname{subsubsubappendix}{Appendix}{Appendices}%
2687         \Crefname{enumi}{Item}{Items}%
2688         \Crefname{enumii}{Item}{Items}%
2689         \Crefname{enumiii}{Item}{Items}%
2690         \Crefname{enumiv}{Item}{Items}%
2691         \Crefname{enumv}{Item}{Items}%
2692         \Crefname{footnote}{Footnote}{Footnotes}%
2693         \Crefname{figure}{Figure}{Figures}%
2694         \Crefname{subfigure}{Figure}{Figures}%
2695         \Crefname{table}{Table}{Tables}%
2696         \Crefname{subtable}{Table}{Tables}%
2697         \Crefname{theorem}{Theorem}{Theorems}%
2698         \Crefname{lemma}{Lemma}{Lemmas}%
2699         \Crefname{corollary}{Corollary}{Corollaries}%
2700         \Crefname{proposition}{Proposition}{Propositions}%
2701         \Crefname{definition}{Definition}{Definitions}%
2702         \Crefname{result}{Result}{Results}%
2703         \Crefname{example}{Example}{Examples}%
2704         \Crefname{remark}{Remark}{Remarks}%
2705         \Crefname{note}{Note}{Notes}%
2706         \if@cref@capitalise%
2707             \crefname{equation}{Eq.}{Eqs.}%
2708             \crefname{chapter}{Chapter}{Chapters}%
2709             \crefname{section}{Section}{Sections}%
2710             \crefname{subsection}{Section}{Sections}%
2711             \crefname{subsubsection}{Section}{Sections}%
2712             \crefname{appendix}{Appendix}{Appendices}%
2713             \crefname{subappendix}{Appendix}{Appendices}%
2714             \crefname{subsubappendix}{Appendix}{Appendices}%

```

```

2715   \crefname{subsubsubappendix}{Appendix}{Appendices}%
2716   \crefname{enumi}{Item}{Items}%
2717   \crefname{enumii}{Item}{Items}%
2718   \crefname{enumiii}{Item}{Items}%
2719   \crefname{enumiv}{Item}{Items}%
2720   \crefname{enumv}{Item}{Items}%
2721   \crefname{footnote}{Footnote}{Footnotes}%
2722   \crefname{figure}{Fig.}{Figs.}%
2723   \crefname{subfigure}{Fig.}{Figs.}%
2724   \crefname{table}{Table}{Tables}%
2725   \crefname{subtable}{Table}{Tables}%
2726   \crefname{theorem}{Theorem}{Theorems}%
2727   \crefname{lemma}{Lemma}{Lemmas}%
2728   \crefname{corollary}{Corollary}{Corollaries}%
2729   \crefname{proposition}{Proposition}{Propositions}%
2730   \crefname{definition}{Definition}{Definitions}%
2731   \crefname{result}{Result}{Results}%
2732   \crefname{example}{Example}{Examples}%
2733   \crefname{remark}{Remark}{Remarks}%
2734   \crefname{note}{Note}{Notes}%
2735 \else%
2736   \crefname{equation}{eq.}{eqs.}%
2737   \crefname{chapter}{chapter}{chapters}%
2738   \crefname{section}{section}{sections}%
2739   \crefname{subsection}{section}{sections}%
2740   \crefname{subsubsection}{section}{sections}%
2741   \crefname{appendix}{appendix}{appendices}%
2742   \crefname{subappendix}{appendix}{appendices}%
2743   \crefname{subsubappendix}{appendix}{appendices}%
2744   \crefname{subsubsubappendix}{appendix}{appendices}%
2745   \crefname{enumi}{item}{items}%
2746   \crefname{enumii}{item}{items}%
2747   \crefname{enumiii}{item}{items}%
2748   \crefname{enumiv}{item}{items}%
2749   \crefname{enumv}{item}{items}%
2750   \crefname{footnote}{footnote}{footnotes}%
2751   \crefname{figure}{fig.}{figs.}%
2752   \crefname{subfigure}{fig.}{figs.}%
2753   \crefname{table}{table}{tables}%
2754   \crefname{subtable}{table}{tables}%
2755   \crefname{theorem}{theorem}{theorems}%
2756   \crefname{lemma}{lemma}{lemmas}%
2757   \crefname{corollary}{corollary}{corollaries}%
2758   \crefname{proposition}{proposition}{propositions}%
2759   \crefname{definition}{definition}{definitions}%
2760   \crefname{result}{result}{results}%
2761   \crefname{example}{example}{examples}%
2762   \crefname{remark}{remark}{remarks}%
2763   \crefname{note}{note}{notes}%
2764 \fi%

```

```
2765     }}}
```

german German translations kindly provided by Stefan Pinnow, with a few additions by the package author (so you know to blame the latter for any errors!).

```
2766 \DeclareOption{german}{%
2767   \PackageInfo{cleveref}{loaded 'german' language definitions}}
```

First, we set up the definitions used at the beginning of the document to define the formats created by the document preamble.

```
2768 \AtBeginDocument{%
2769   \def\crefrangeconjunction@preamble{ bis~}%
2770   \def\crefrangepreconjunction@preamble{}%
2771   \def\crefrangepostconjunction@preamble{}%
2772   \def\crefpairconjunction@preamble{ und~}%
2773   \def\crefmiddleconjunction@preamble{, }%
2774   \def\creflastconjunction@preamble{ und~}%
```

We don't want the extra comma before "und" that would be added by the default fall-back definitions in terms of the above conjunctions, so we define `\crefpairgroupconjunction` explicitly. In fact, we have to define the other group conjunctions explicitly too here, in case any other language option defines them explicitly and we need to override them.

```
2775   \def\crefpairgroupconjunction@preamble{ und~}%
2776   \def\crefmiddlegroupconjunction@preamble{, }%
2777   \def\creflastgroupconjunction@preamble{ und~}%
2778   \Crefname@preamble{equation}{Gleichung}{Gleichungen}%
2779   \Crefname@preamble{chapter}{Kapitel}{Kapitel}%
2780   \Crefname@preamble{section}{Abschnitt}{Abschnitte}%
2781   \Crefname@preamble{appendix}{Anhang}{Anh\"ange}%
2782   \Crefname@preamble{enumi}{Punkt}{Punkte}%
2783   \Crefname@preamble{footnote}{Fu\ss note}{Fu\ss noten}%
2784   \Crefname@preamble{figure}{Abbildung}{Abbildungen}%
2785   \Crefname@preamble{table}{Tabelle}{Tabellen}%
2786   \Crefname@preamble{theorem}{Theorem}{Theoremen}%
2787   \Crefname@preamble{lemma}{Lemma}{Lemmata}%
2788   \Crefname@preamble{corollary}{Korollar}{Korollaren}%
2789   \Crefname@preamble{proposition}{Satz}{S\"atze}%
2790   \Crefname@preamble{definition}{Definition}{Definitionen}%
2791   \Crefname@preamble{result}{Ergebnis}{Ergebnisse}%
2792   \Crefname@preamble{example}{Beispiel}{Beispiele}%
2793   \Crefname@preamble{remark}{Bemerkung}{Bemerkungen}%
2794   \Crefname@preamble{note}{Anmerkung}{Anmerkungen}%
2795   \if@cref@capitalise{%
2796     \crefname@preamble{equation}{Gleichung}{Gleichungen}%
2797     \crefname@preamble{chapter}{Kapitel}{Kapitel}%
2798     \crefname@preamble{section}{Abschnitt}{Abschnitte}%
2799     \crefname@preamble{appendix}{Anhang}{Anh\"ange}%
2800     \crefname@preamble{enumi}{Punkt}{Punkte}%
2801     \crefname@preamble{footnote}{Fu\ss note}{Fu\ss noten}%
}
```

```

2802 \crefname@preamble{figure}{Abbildung}{Abbildungen}%
2803 \crefname@preamble{table}{Tabelle}{Tabellen}%
2804 \crefname@preamble{theorem}{Theorem}{Theoremen}%
2805 \crefname@preamble{lemma}{Lemma}{Lemmata}%
2806 \crefname@preamble{corollary}{Korollar}{Korollaren}%
2807 \crefname@preamble{proposition}{Satz}{S\"atze}%
2808 \crefname@preamble{definition}{Definition}{Definitionen}%
2809 \crefname@preamble{result}{Ergebnis}{Ergebnisse}%
2810 \crefname@preamble{example}{Beispiel}{Beispiele}%
2811 \crefname@preamble{remark}{Bemerkung}{Bemerkungen}%
2812 \crefname@preamble{note}{Anmerkung}{Anmerkungen}%
2813 \else%
2814   \crefname@preamble{equation}{Gleichung}{Gleichungen}%
2815   \crefname@preamble{chapter}{Kapitel}{Kapitel}%
2816   \crefname@preamble{section}{Abschnitt}{Abschnitte}%
2817   \crefname@preamble{appendix}{Anhang}{Anh\"ange}%
2818   \crefname@preamble{enumi}{Punkt}{Punkte}%
2819   \crefname@preamble{footnote}{Fu\ss note}{Fu\ss noten}%
2820   \crefname@preamble{figure}{Abbildung}{Abbildungen}%
2821   \crefname@preamble{table}{Tabelle}{Tabellen}%
2822   \crefname@preamble{theorem}{Theorem}{Theoremen}%
2823   \crefname@preamble{lemma}{Lemma}{Lemmata}%
2824   \crefname@preamble{corollary}{Korollar}{Korollaren}%
2825   \crefname@preamble{proposition}{Satz}{S\"atze}%
2826   \crefname@preamble{definition}{Definition}{Definitionen}%
2827   \crefname@preamble{result}{Ergebnis}{Ergebnisse}%
2828   \crefname@preamble{example}{Beispiel}{Beispiele}%
2829   \crefname@preamble{remark}{Bemerkung}{Bemerkungen}%
2830   \crefname@preamble{note}{Anmerkung}{Anmerkungen}%
2831 \fi%
2832 \def\cref@language{german}%

```

Next, we add the definitions to `\extras...` so that babel's `\selectlanguage` command will change the format appropriately.

```

2833 \cref@addto\extrasgerman{%
2834   \renewcommand{\crefrangeconjunction}{ bis~}%
2835   \renewcommand\crefrangepreconjunction{}%
2836   \renewcommand\crefrangepostconjunction{}%
2837   \renewcommand{\crefpairconjunction}{ und~}%
2838   \renewcommand{\crefmiddleconjunction}{, }%
2839   \renewcommand{\creflastconjunction}{ und~}%
2840   \renewcommand{\crefpairgroupconjunction}{ und~}%
2841   \renewcommand{\crefmiddlegroupconjunction}{, }%
2842   \renewcommand{\creflastgroupconjunction}{ und~}%
2843   \Crefname{equation}{Gleichung}{Gleichungen}%
2844   \Crefname{chapter}{Kapitel}{Kapitel}%
2845   \Crefname{section}{Abschnitt}{Abschnitte}%
2846   \Crefname{subsection}{Abschnitt}{Abschnitte}%
2847   \Crefname{subsubsection}{Abschnitt}{Abschnitte}%
2848   \Crefname{appendix}{Anhang}{Anh\"ange}%

```

```

2849 \Crefname{subappendix}{Anhang}{Anh\"ange}%
2850 \Crefname{subsubappendix}{Anhang}{Anh\"ange}%
2851 \Crefname{subsubsubappendix}{Anhang}{Anh\"ange}%
2852 \Crefname{enumi}{Punkt}{Punkte}%
2853 \Crefname{enumii}{Punkt}{Punkte}%
2854 \Crefname{enumiii}{Punkt}{Punkte}%
2855 \Crefname{enumiv}{Punkt}{Punkte}%
2856 \Crefname{enumv}{Punkt}{Punkte}%
2857 \Crefname{footnote}{Fu\ss note}{Fu\ss noten}%
2858 \Crefname{figure}{Abbildung}{Abbildungen}%
2859 \Crefname{subfigure}{Abbildung}{Abbildungen}%
2860 \Crefname{table}{Tabelle}{Tabellen}%
2861 \Crefname{subtable}{Tabelle}{Tabellen}%
2862 \Crefname{theorem}{Theorem}{Theoremen}%
2863 \Crefname{lemma}{Lemma}{Lemmata}%
2864 \Crefname{corollary}{Korollar}{Korollaren}%
2865 \Crefname{proposition}{Satz}{S\"atze}%
2866 \Crefname{definition}{Definition}{Definitionen}%
2867 \Crefname{result}{Ergebnis}{Ergebnisse}%
2868 \Crefname{example}{Beispiel}{Beispiele}%
2869 \Crefname{remark}{Bemerkung}{Bemerkungen}%
2870 \Crefname{note}{Anmerkung}{Anmerkungen}%
2871 \if@ref@capitalise%
2872   \crefname{equation}{Gleichung}{Gleichungen}%
2873   \crefname{chapter}{Kapitel}{Kapitel}%
2874   \crefname{section}{Abschnitt}{Abschnitte}%
2875   \crefname{subsection}{Abschnitt}{Abschnitte}%
2876   \crefname{subsubsection}{Abschnitt}{Abschnitte}%
2877   \crefname{appendix}{Anhang}{Anh\"ange}%
2878   \crefname{subappendix}{Anhang}{Anh\"ange}%
2879   \crefname{subsubappendix}{Anhang}{Anh\"ange}%
2880   \crefname{subsubsubappendix}{Anhang}{Anh\"ange}%
2881   \crefname{enumi}{Punkt}{Punkte}%
2882   \crefname{enumii}{Punkt}{Punkte}%
2883   \crefname{enumiii}{Punkt}{Punkte}%
2884   \crefname{enumiv}{Punkt}{Punkte}%
2885   \crefname{enumv}{Punkt}{Punkte}%
2886   \crefname{footnote}{Fu\ss note}{Fu\ss noten}%
2887   \crefname{figure}{Abbildung}{Abbildungen}%
2888   \crefname{subfigure}{Abbildung}{Abbildungen}%
2889   \crefname{table}{Tabelle}{Tabellen}%
2890   \crefname{subtable}{Tabelle}{Tabellen}%
2891   \crefname{theorem}{Theorem}{Theoremen}%
2892   \crefname{lemma}{Lemma}{Lemmata}%
2893   \crefname{corollary}{Korollar}{Korollaren}%
2894   \crefname{proposition}{Satz}{S\"atze}%
2895   \crefname{definition}{Definition}{Definitionen}%
2896   \crefname{result}{Ergebnis}{Ergebnisse}%
2897   \crefname{example}{Beispiel}{Beispiele}%
2898   \crefname{remark}{Bemerkung}{Bemerkungen}%

```

```

2899     \crefname{note}{Anmerkung}{Anmerkungen}%
2900 \else%
2901     \crefname{equation}{Gleichung}{Gleichungen}%
2902     \crefname{chapter}{Kapitel}{Kapitel}%
2903     \crefname{section}{Abschnitt}{Abschnitte}%
2904     \crefname{subsection}{Abschnitt}{Abschnitte}%
2905     \crefname{subsubsection}{Abschnitt}{Abschnitte}%
2906     \crefname{appendix}{Anhang}{Anh\ "ange}%
2907     \crefname{subappendix}{Anhang}{Anh\ "ange}%
2908     \crefname{subsubappendix}{Anhang}{Anh\ "ange}%
2909     \crefname{subsubsubappendix}{Anhang}{Anh\ "ange}%
2910     \crefname{enumi}{Punkt}{Punkte}%
2911     \crefname{enumii}{Punkt}{Punkte}%
2912     \crefname{enumiii}{Punkt}{Punkte}%
2913     \crefname{enumiv}{Punkt}{Punkte}%
2914     \crefname{enumv}{Punkt}{Punkte}%
2915     \crefname{footnote}{Fu\ss note}{Fu\ss noten}%
2916     \crefname{figure}{Abbildung}{Abbildungen}%
2917     \crefname{subfigure}{Abbildung}{Abbildungen}%
2918     \crefname{table}{Tabelle}{Tabellen}%
2919     \crefname{subtable}{Tabelle}{Tabellen}%
2920     \crefname{theorem}{Theorem}{Theoremen}%
2921     \crefname{lemma}{Lemma}{Lemmata}%
2922     \crefname{corollary}{Korollar}{Korollaren}%
2923     \crefname{proposition}{Satz}{S\ "atze}%
2924     \crefname{definition}{Definition}{Definitionen}%
2925     \crefname{result}{Ergebnis}{Ergebnisse}%
2926     \crefname{example}{Beispiel}{Beispiele}%
2927     \crefname{remark}{Bemerkung}{Bemerkungen}%
2928     \crefname{note}{Anmerkung}{Anmerkungen}%
2929   \fi%
2930 \}}}

```

ngerman It so happens that none of the cross-reference names differ in the “Neuerechtschreibung”, so we make `ngerman` execute `german`. However, we still need to add the definitions to `\extrasngerman` (note the “n”) so that `\selectlanguage` etc. will work.

```

2931 \DeclareOption{ngerman}{%
2932   \PackageInfo{cleveref}{loaded 'ngerman' language definitions}
2933   \ExecuteOptions{german}
2934   \def\cref@language{ngerman}
2935   \AtBeginDocument{%
2936     \cref@addto\extrasngerman{%
2937       \renewcommand{\crefrangeconjunction}{ bis\textsuperscript{\textasciicircum}}%
2938       \renewcommand\crefrangepreconjunction{}%
2939       \renewcommand\crefrangepostconjunction{}%
2940       \renewcommand{\crefpairconjunction}{ und\textsuperscript{\textasciicircum}}%
2941       \renewcommand{\crefmiddleconjunction}{, }%
2942       \renewcommand{\creflastconjunction}{ und\textsuperscript{\textasciicircum}}%

```

```

2943 \renewcommand{\crefpairgroupconjunction}{ und~}%
2944 \renewcommand{\crefmiddlegroupconjunction}{, }%
2945 \renewcommand{\creflastgroupconjunction}{ und~}%
2946 \Crefname{equation}{Gleichung}{Gleichungen}%
2947 \Crefname{chapter}{Kapitel}{Kapitel}%
2948 \Crefname{section}{Abschnitt}{Abschnitte}%
2949 \Crefname{subsection}{Abschnitt}{Abschnitte}%
2950 \Crefname{subsubsection}{Abschnitt}{Abschnitte}%
2951 \Crefname{appendix}{Anhang}{Anh\"ange}%
2952 \Crefname{subappendix}{Anhang}{Anh\"ange}%
2953 \Crefname{subsubappendix}{Anhang}{Anh\"ange}%
2954 \Crefname{subsubsubappendix}{Anhang}{Anh\"ange}%
2955 \Crefname{enumi}{Punkt}{Punkte}%
2956 \Crefname{enumii}{Punkt}{Punkte}%
2957 \Crefname{enumiii}{Punkt}{Punkte}%
2958 \Crefname{enumiv}{Punkt}{Punkte}%
2959 \Crefname{enumv}{Punkt}{Punkte}%
2960 \Crefname{footnote}{Fu\ss note}{Fu\ss noten}%
2961 \Crefname{figure}{Abbildung}{Abbildungen}%
2962 \Crefname{subfigure}{Abbildung}{Abbildungen}%
2963 \Crefname{table}{Tabelle}{Tabellen}%
2964 \Crefname{subtable}{Tabelle}{Tabellen}%
2965 \Crefname{theorem}{Theorem}{Theoremen}%
2966 \Crefname{lemma}{Lemma}{Lemmata}%
2967 \Crefname{corollary}{Korollar}{Korollaren}%
2968 \Crefname{proposition}{Satz}{S\"atze}%
2969 \Crefname{definition}{Definition}{Definitionen}%
2970 \Crefname{result}{Ergebnis}{Ergebnisse}%
2971 \Crefname{example}{Beispiel}{Beispiele}%
2972 \Crefname{remark}{Bemerkung}{Bemerkungen}%
2973 \Crefname{note}{Anmerkung}{Anmerkungen}%
2974 \if@ref@capitalise%
2975   \crefname{equation}{Gleichung}{Gleichungen}%
2976   \crefname{chapter}{Kapitel}{Kapitel}%
2977   \crefname{section}{Abschnitt}{Abschnitte}%
2978   \crefname{subsection}{Abschnitt}{Abschnitte}%
2979   \crefname{subsubsection}{Abschnitt}{Abschnitte}%
2980   \crefname{appendix}{Anhang}{Anh\"ange}%
2981   \crefname{subappendix}{Anhang}{Anh\"ange}%
2982   \crefname{subsubappendix}{Anhang}{Anh\"ange}%
2983   \crefname{subsubsubappendix}{Anhang}{Anh\"ange}%
2984   \crefname{enumi}{Punkt}{Punkte}%
2985   \crefname{enumii}{Punkt}{Punkte}%
2986   \crefname{enumiii}{Punkt}{Punkte}%
2987   \crefname{enumiv}{Punkt}{Punkte}%
2988   \crefname{enumv}{Punkt}{Punkte}%
2989   \crefname{footnote}{Fu\ss note}{Fu\ss noten}%
2990   \crefname{figure}{Abbildung}{Abbildungen}%
2991   \crefname{subfigure}{Abbildung}{Abbildungen}%
2992   \crefname{table}{Tabelle}{Tabellen}%

```

```

2993     \crefname{subtable}{Tabelle}{Tabellen}%
2994     \crefname{theorem}{Theorem}{Theoremen}%
2995     \crefname{lemma}{Lemma}{Lemmata}%
2996     \crefname{corollary}{Korollar}{Korollaren}%
2997     \crefname{proposition}{Satz}{S\"atze}%
2998     \crefname{definition}{Definition}{Definitionen}%
2999     \crefname{result}{Ergebnis}{Ergebnisse}%
3000     \crefname{example}{Beispiel}{Beispiele}%
3001     \crefname{remark}{Bemerkung}{Bemerkungen}%
3002     \crefname{note}{Anmerkung}{Anmerkungen}%
3003 \else%
3004     \crefname{equation}{Gleichung}{Gleichungen}%
3005     \crefname{chapter}{Kapitel}{Kapitel}%
3006     \crefname{section}{Abschnitt}{Abschnitte}%
3007     \crefname{subsection}{Abschnitt}{Abschnitte}%
3008     \crefname{subsubsection}{Abschnitt}{Abschnitte}%
3009     \crefname{appendix}{Anhang}{Anh\"ange}%
3010     \crefname{subappendix}{Anhang}{Anh\"ange}%
3011     \crefname{subsubappendix}{Anhang}{Anh\"ange}%
3012     \crefname{subsubsubappendix}{Anhang}{Anh\"ange}%
3013     \crefname{enumi}{Punkt}{Punkte}%
3014     \crefname{enumii}{Punkt}{Punkte}%
3015     \crefname{enumiii}{Punkt}{Punkte}%
3016     \crefname{enumiv}{Punkt}{Punkte}%
3017     \crefname{enumv}{Punkt}{Punkte}%
3018     \crefname{footnote}{Fu\ss note}{Fu\ss noten}%
3019     \crefname{figure}{Abbildung}{Abbildungen}%
3020     \crefname{subfigure}{Abbildung}{Abbildungen}%
3021     \crefname{table}{Tabelle}{Tabellen}%
3022     \crefname{subtable}{Tabelle}{Tabellen}%
3023     \crefname{theorem}{Theorem}{Theoremen}%
3024     \crefname{lemma}{Lemma}{Lemmata}%
3025     \crefname{corollary}{Korollar}{Korollaren}%
3026     \crefname{proposition}{Satz}{S\"atze}%
3027     \crefname{definition}{Definition}{Definitionen}%
3028     \crefname{result}{Ergebnis}{Ergebnisse}%
3029     \crefname{example}{Beispiel}{Beispiele}%
3030     \crefname{remark}{Bemerkung}{Bemerkungen}%
3031     \crefname{note}{Anmerkung}{Anmerkungen}%
3032   \fi%
3033 \}}}

```

dutch Dutch translations kindly contributed by Philip Hölzenspies.

```

3034 \DeclareOption{dutch}{%
3035   \PackageInfo{cleveref}{loaded 'dutch' language definitions}}

```

First, we set up the definitions used at the beginning of the document to define the formats created by the document preamble.

```

3036 \AtBeginDocument{%

```

```

3037 \def\crefrangeconjunction@preamble{ tot~}%
3038 \def\crefrangepreconjunction@preamble{}%
3039 \def\crefrangepostconjunction@preamble{}%
3040 \def\crefpairconjunction@preamble{ en~}%
3041 \def\crefmiddleconjunction@preamble{, }%
3042 \def\creflastconjunction@preamble{ en~}%

```

As in German, we don't want the extra comma before "en" that would be added by the default fall-back definitions in terms of the above conjunctions, so we define `\crefpairgroupconjunction` explicitly. In fact, we have to define the other group conjunctions explicitly too here, in case any other language option defines them explicitly and we need to override them.

```

3043 \def\crefpairgroupconjunction@preamble{ en~}%
3044 \def\crefmiddlegroupconjunction@preamble{, }%
3045 \def\creflastgroupconjunction@preamble{ en~}%
3046 \Crefname@preamble{equation}{Vergelijking}{Vergelijkingen}%
3047 \Crefname@preamble{chapter}{Hoofdstuk}{Hoofdstukken}%
3048 \Crefname@preamble{section}{Paragraaf}{Paragrafen}%
3049 \Crefname@preamble{appendix}{Appendix}{Appendices}%
3050 \Crefname@preamble{figure}{Figuur}{Figuren}%
3051 \Crefname@preamble{table}{Tabel}{Tabellen}%
3052 \Crefname@preamble{enumi}{Punt}{Punten}%
3053 \Crefname@preamble{footnote}{Voetnote}{Voetnoten}%
3054 \Crefname@preamble{lemma}{Lemma}{Lemma's}%
3055 \Crefname@preamble{corollary}{Corollarium}{Corollaria}%
3056 \Crefname@preamble{proposition}{Bewering}{Beweringen}%
3057 \Crefname@preamble{definition}{Definitie}{Definities}%
3058 \Crefname@preamble{result}{Resultaat}{Resultaten}%
3059 \Crefname@preamble{example}{Voorbeeld}{Voorbeelden}%
3060 \Crefname@preamble{remark}{Opmerking}{Opmerkingen}%
3061 \Crefname@preamble{note}{Aantekening}{Aantekeningen}%
3062 \if@cref@capitalise%
3063   \crefname@preamble{equation}{Verg.}{Verg.'s.}%
3064   \crefname@preamble{chapter}{Hoofdstuk}{Hoofdstukken}%
3065   \crefname@preamble{section}{Paragraaf}{Paragrafen}%
3066   \crefname@preamble{appendix}{Appendix}{Appendices}%
3067   \crefname@preamble{enumi}{Punt}{Punten}%
3068   \crefname@preamble{footnote}{Voetnote}{Voetnoten}%
3069   \crefname@preamble{figure}{Fig.}{Fig.'s.}%
3070   \crefname@preamble{table}{Tabel}{Tabellen}%
3071   \crefname@preamble{theorem}{Theorema}{Theorema's}%
3072   \crefname@preamble{lemma}{Lemma}{Lemma's}%
3073   \crefname@preamble{corollary}{Corollarium}{Corollaria}%
3074   \crefname@preamble{proposition}{Bewering}{Beweringen}%
3075   \crefname@preamble{definition}{Definitie}{Definities}%
3076   \crefname@preamble{result}{Resultaat}{Resultaten}%
3077   \crefname@preamble{example}{Voorbeeld}{Voorbeelden}%
3078   \crefname@preamble{remark}{Opmerking}{Opmerkingen}%
3079   \crefname@preamble{note}{Aantekening}{Aantekeningen}%
3080 \else%

```

```

3081   \crefname@preamble{equation}{verg.}{verg's.}%
3082   \crefname@preamble{chapter}{hoofdstuk}{hoofdstukken}%
3083   \crefname@preamble{section}{paragraaf}{paragrafen}%
3084   \crefname@preamble{appendix}{appendix}{appendices}%
3085   \crefname@preamble{enumi}{punt}{punten}%
3086   \crefname@preamble{footnote}{voetnote}{voetnoten}%
3087   \crefname@preamble{figure}{fig.}{fig's.}%
3088   \crefname@preamble{table}{tabel}{tabellen}%
3089   \crefname@preamble{theorem}{theorema}{theorema's}%
3090   \crefname@preamble{lemma}{lemma}{lemma's}%
3091   \crefname@preamble{corollary}{corollarium}{corollaria}%
3092   \crefname@preamble{proposition}{bewering}{beweringen}%
3093   \crefname@preamble{definition}{definitie}{definities}%
3094   \crefname@preamble{result}{resultaat}{resultaten}%
3095   \crefname@preamble{example}{voorbeeld}{voorbeelden}%
3096   \crefname@preamble{remark}{opmerking}{opmerkingen}%
3097   \crefname@preamble{note}{aantekening}{aantekeningen}%
3098 \fi%
3099 \def\cref@language{dutch}%

```

Next, we add the definitions to `\extras...` so that babel's `\selectlanguage` command will change the format appropriately.

```

3100 \cref@addto\extrasdutch{%
3101   \renewcommand{\crefrangeconjunction}{ tot~}%
3102   \renewcommand\crefrangepreconjunction{}%
3103   \renewcommand\crefrangepostconjunction{}%
3104   \renewcommand{\crefpairconjunction}{ en~}%
3105   \renewcommand{\crefmiddleconjunction}{, }%
3106   \renewcommand{\creflastconjunction}{ en~}%
3107   \renewcommand{\crefpairgroupconjunction}{ en~}%
3108   \renewcommand{\crefmiddlegroupconjunction}{, }%
3109   \renewcommand{\creflastgroupconjunction}{ en~}%
3110   \Crefname{equation}{Vergel\ij{}king}{Vergel\ij{}ingen}%
3111   \Crefname{chapter}{Hoofdstuk}{Hoofdstukken}%
3112   \Crefname{section}{Paragraaf}{Paragrafen}%
3113   \Crefname{subsection}{Paragraaf}{Paragrafen}%
3114   \Crefname{subsubsection}{Paragraaf}{Paragrafen}%
3115   \Crefname{appendix}{Appendix}{Appendices}%
3116   \Crefname{subappendix}{Appendix}{Appendices}%
3117   \Crefname{subsubappendix}{Appendix}{Appendices}%
3118   \Crefname{subsubsubappendix}{Appendix}{Appendices}%
3119   \Crefname{enumi}{Punt}{Punten}%
3120   \Crefname{enumii}{Punt}{Punten}%
3121   \Crefname{enumiii}{Punt}{Punten}%
3122   \Crefname{enumiv}{Punt}{Punten}%
3123   \Crefname{enumv}{Punt}{Punten}%
3124   \Crefname{footnote}{Voetnote}{Voetnoten}%
3125   \Crefname{figure}{Figuur}{Figuren}%
3126   \Crefname{subfigure}{Figuur}{Figuren}%
3127   \Crefname{table}{Tabel}{Tabellen}%

```

```

3128     \Crefname{subtable}{Tabel}{Tabellen}%
3129     \Crefname{theorem}{Theorema}{Theorema's}%
3130     \Crefname{lemma}{Lemma}{Lemma's}%
3131     \Crefname{corollary}{Corollarium}{Corollaria}%
3132     \Crefname{proposition}{Bewering}{Beweringen}%
3133     \Crefname{definition}{Definitie}{Definities}%
3134     \Crefname{result}{Resultaat}{Resultaten}%
3135     \Crefname{example}{Voorbeeld}{Voorbeelden}%
3136     \Crefname{remark}{Opmerking}{Opmerkingen}%
3137     \Crefname{note}{Aantekening}{Aantekeningen}%
3138     \if@cref@capitalise%
3139         \crefname{equation}{Verg.}{Verg's.}%
3140         \crefname{chapter}{Hoofdstuk}{Hoofdstukken}%
3141         \crefname{section}{Paragraaf}{Paragrafen}%
3142         \crefname{appendix}{Appendix}{Appendices}%
3143         \crefname{enumi}{Punt}{Punten}%
3144         \crefname{footnote}{Voetnote}{Voetnoten}%
3145         \crefname{figure}{Fig.}{Fig's.}%
3146         \crefname{table}{Tabel}{Tabellen}%
3147         \crefname{theorem}{Theorema}{Theorema's}%
3148         \crefname{lemma}{Lemma}{Lemma's}%
3149         \crefname{corollary}{Corollarium}{Corollaria}%
3150         \crefname{proposition}{Bewering}{Beweringen}%
3151         \crefname{definition}{Definitie}{Definities}%
3152         \crefname{result}{Resultaat}{Resultaten}%
3153         \crefname{example}{Voorbeeld}{Voorbeelden}%
3154         \crefname{remark}{Opmerking}{Opmerkingen}%
3155         \crefname{note}{Aantekening}{Aantekeningen}%
3156     \else%
3157         \crefname{equation}{verg.}{verg's.}%
3158         \crefname{chapter}{hoofdstuk}{hoofdstukken}%
3159         \crefname{section}{paragraaf}{paragrafen}%
3160         \crefname{appendix}{appendix}{appendices}%
3161         \crefname{enumi}{punt}{punten}%
3162         \crefname{footnote}{voetnote}{voetnoten}%
3163         \crefname{figure}{fig.}{fig's.}%
3164         \crefname{table}{tabel}{tabellen}%
3165         \crefname{theorem}{theorema}{theorema's}%
3166         \crefname{lemma}{lemma}{lemma's}%
3167         \crefname{corollary}{corollarium}{corollaria}%
3168         \crefname{proposition}{bewering}{beweringen}%
3169         \crefname{definition}{definitie}{definities}%
3170         \crefname{result}{resultaat}{resultaten}%
3171         \crefname{example}{voorbeeld}{voorbeelden}%
3172         \crefname{remark}{opmerking}{opmerkingen}%
3173         \crefname{note}{aantekening}{aantekeningen}%
3174     \fi%
3175 }}}}

```

french French translations attempted by the package author (please report any correc-

tions that might be needed!).

```
3176 \DeclareOption{french}{%
3177   \PackageInfo{cleveref}{loaded 'french' language definitions}}
```

First, we set up the definitions used at the beginning of the document to define the formats created by the document preamble.

```
3178 \AtBeginDocument{%
3179   \def\crefrangeconjunction@preamble{ `a`}%
3180   \def\crefrangepreconjunction@preamble{}%
3181   \def\crefrangepostconjunction@preamble{}%
3182   \def\crefpairconjunction@preamble{ et`}%
3183   \def\crefmiddleconjunction@preamble{, }%
3184   \def\creflastconjunction@preamble{ et`}%
```

Erring on the side of caution, I've left off the extra comma before "et" between groups, pending more knowledgeable input on punctuation rules from a native French speaker.

```
3185 \def\crefpairgroupconjunction@preamble{ et`}%
3186 \def\crefmiddlegroupconjunction@preamble{, }%
3187 \def\creflastgroupconjunction@preamble{, et`}%
3188 \Crefname@preamble{equation}{\E{equation}}{\E{equations}}%
3189 \Crefname@preamble{chapter}{Chapitre}{Chapitres}%
3190 \Crefname@preamble{section}{Section}{Sections}%
3191 \Crefname@preamble{appendix}{Appendice}{Appendices}%
3192 \Crefname@preamble{enumi}{Point}{Points}%
3193 \Crefname@preamble{footnote}{Note}{Notes}%
3194 \Crefname@preamble{figure}{Figure}{Figures}%
3195 \Crefname@preamble{table}{Tableau}{Tableaux}%
3196 \Crefname@preamble{theorem}{Th\eor\eme}{Th\eor\emes}%
3197 \Crefname@preamble{lemma}{Lemme}{Lemmes}%
3198 \Crefname@preamble{corollary}{Corollaire}{Corollaires}%
3199 \Crefname@preamble{proposition}{Proposition}{Propositions}%
3200 \Crefname@preamble{definition}{D\efinition}{D\efinitions}%
3201 \Crefname@preamble{result}{R\esultat}{R\esultats}%
3202 \Crefname@preamble{example}{Exemple}{Exemples}%
3203 \Crefname@preamble{remark}{Remarque}{Remarques}%
3204 \if@ cref@capitalise%
3205   \crefname@preamble{equation}{\E{equation}}{\E{equations}}%
3206   \crefname@preamble{chapter}{Chapitre}{Chapitres}%
3207   \crefname@preamble{section}{Section}{Sections}%
3208   \crefname@preamble{appendix}{Appendice}{Appendices}%
3209   \crefname@preamble{enumi}{Point}{Points}%
3210   \crefname@preamble{footnote}{Note}{Notes}%
3211   \crefname@preamble{figure}{Figure}{Figures}%
3212   \crefname@preamble{table}{Tableau}{Tableaux}%
3213   \crefname@preamble{theorem}{Th\eor\eme}{Th\eor\emes}%
3214   \crefname@preamble{lemma}{Lemme}{Lemmes}%
3215   \crefname@preamble{corollary}{Corollaire}{Corollaires}%
3216   \crefname@preamble{proposition}{Proposition}{Propositions}%

```

```

3217   \crefname@preamble{definition}{D\efinition}{D\efinitions}%
3218   \crefname@preamble{result}{R\esultat}{R\esultats}%
3219   \crefname@preamble{example}{Exemple}{Exemples}%
3220   \crefname@preamble{remark}{Remarque}{Remarques}%
3221   \crefname@preamble{note}{Commentaire}{Commentaires}%
3222 \else%
3223   \crefname@preamble{equation}{{\text{\`e}}quation}{{\text{\`e}}quations}%
3224   \crefname@preamble{chapter}{chapitre}{chapitres}%
3225   \crefname@preamble{section}{section}{sections}%
3226   \crefname@preamble{appendix}{appendice}{appendices}%
3227   \crefname@preamble{enumi}{point}{points}%
3228   \crefname@preamble{footnote}{note}{notes}%
3229   \crefname@preamble{figure}{figure}{figures}%
3230   \crefname@preamble{table}{tableau}{tableaux}%
3231   \crefname@preamble{theorem}{th\eor\eme}{th\eor\emes}%
3232   \crefname@preamble{lemma}{lemme}{lemmes}%
3233   \crefname@preamble{corollary}{corollaire}{corollaires}%
3234   \crefname@preamble{proposition}{proposition}{propositions}%
3235   \crefname@preamble{definition}{d\efinition}{d\efinitions}%
3236   \crefname@preamble{result}{r\esultat}{r\esultats}%
3237   \crefname@preamble{example}{exemple}{exemples}%
3238   \crefname@preamble{remark}{remarque}{remarques}%
3239   \crefname@preamble{note}{commentaire}{commentaires}%
3240 \fi%
3241 \def\cref@language{french}%

```

Next, we add the definitions to `\extras...` so that `babel`'s `\selectlanguage` command will change the format appropriately.

```

3242 \cref@addto\extrasfrench{%
3243   \renewcommand{\crefrangeconjunction}{ \text{`}\text{~}}%
3244   \renewcommand{\crefrangepreconjunction}{ }%
3245   \renewcommand{\crefrangepostconjunction}{ }%
3246   \renewcommand{\crefpairconjunction}{ \text{et}\text{~}}%
3247   \renewcommand{\crefmiddleconjunction}{, }%
3248   \renewcommand{\creflastconjunction}{ \text{et}\text{~}}%
3249   \renewcommand{\crefpairgroupconjunction}{ \text{et}\text{~}}%
3250   \renewcommand{\crefmiddlegroupconjunction}{, }%
3251   \renewcommand{\creflastgroupconjunction}{ \text{et}\text{~}}%
3252   \Crefname{equation}{{\text{\`E}}quation}{{\text{\`E}}quations}%
3253   \Crefname{chapter}{Chapitre}{Chapitres}%
3254   \Crefname{section}{Section}{Sections}%
3255   \Crefname{subsection}{Section}{Sections}%
3256   \Crefname{subsubsection}{Section}{Sections}%
3257   \Crefname{appendix}{Appendice}{Appendices}%
3258   \Crefname{subappendix}{Appendice}{Appendices}%
3259   \Crefname{subsubappendix}{Appendice}{Appendices}%
3260   \Crefname{subsubsubappendix}{Appendice}{Appendices}%
3261   \Crefname{enumi}{Point}{Points}%
3262   \Crefname{enumii}{Point}{Points}%
3263   \Crefname{enumiii}{Point}{Points}%

```

```

3264   \Crefname{enumiv}{Point}{Points}%
3265   \Crefname{enumv}{Point}{Points}%
3266   \Crefname{footnote}{Note}{Notes}%
3267   \Crefname{figure}{Figure}{Figures}%
3268   \Crefname{subfigure}{Figure}{Figures}%
3269   \Crefname{table}{Tableau}{Tableaux}%
3270   \Crefname{subtable}{Tableau}{Tableaux}%
3271   \Crefname{theorem}{Th\`eor\`eme}{Th\`eor\`emes}%
3272   \Crefname{lemma}{Lemme}{Lemmes}%
3273   \Crefname{corollary}{Corollaire}{Corollaires}%
3274   \Crefname{proposition}{Proposition}{Propositions}%
3275   \Crefname{definition}{D\efinition}{D\efinitions}%
3276   \Crefname{result}{R\esultat}{R\esultats}%
3277   \Crefname{example}{Exemple}{Exemples}%
3278   \Crefname{remark}{Remarque}{Remarques}%
3279   \Crefname{note}{Commentaire}{Commentaires}%
3280 \if@cref@capitalise%
3281   \crefname{equation}{{\E}quation}{{\E}quations}%
3282   \crefname{chapter}{Chapitre}{Chapitres}%
3283   \crefname{section}{Section}{Sections}%
3284   \crefname{subsection}{Section}{Sections}%
3285   \crefname{subsubsection}{Section}{Sections}%
3286   \crefname{appendix}{Appendice}{Appendices}%
3287   \crefname{subappendix}{Appendice}{Appendices}%
3288   \crefname{subsubappendix}{Appendice}{Appendices}%
3289   \crefname{subsubsubappendix}{Appendice}{Appendices}%
3290   \crefname{enumi}{Point}{Points}%
3291   \crefname{enumii}{Point}{Points}%
3292   \crefname{enumiii}{Point}{Points}%
3293   \crefname{enumiv}{Point}{Points}%
3294   \crefname{enumv}{Point}{Points}%
3295   \crefname{footnote}{Note}{Notes}%
3296   \crefname{figure}{Figure}{Figures}%
3297   \crefname{subfigure}{Figure}{Figures}%
3298   \crefname{table}{Tableau}{Tableaux}%
3299   \crefname{subtable}{Tableau}{Tableaux}%
3300   \Crefname{theorem}{Th\`eor\`eme}{Th\`eor\`emes}%
3301   \Crefname{lemma}{Lemme}{Lemmes}%
3302   \Crefname{corollary}{Corollaire}{Corollaires}%
3303   \Crefname{proposition}{Proposition}{Propositions}%
3304   \Crefname{definition}{D\efinition}{D\efinitions}%
3305   \Crefname{result}{R\esultat}{R\esultats}%
3306   \Crefname{example}{Exemple}{Exemples}%
3307   \Crefname{remark}{Remarque}{Remarques}%
3308   \Crefname{note}{Commentaire}{Commentaires}%
3309 \else%
3310   \crefname{equation}{{\e}quation}{{\e}quations}%
3311   \crefname{chapter}{chapitre}{chapitres}%
3312   \crefname{section}{section}{sections}%
3313   \crefname{subsection}{section}{sections}%

```

```

3314     \crefname{subsubsection}{section}{sections}%
3315     \crefname{appendix}{appendice}{appendices}%
3316     \crefname{subappendix}{appendice}{appendices}%
3317     \crefname{subsubappendix}{appendice}{appendices}%
3318     \crefname{subsubsubappendix}{appendice}{appendices}%
3319     \crefname{enumi}{point}{points}%
3320     \crefname{enumii}{point}{points}%
3321     \crefname{enumiii}{point}{points}%
3322     \crefname{enumiv}{point}{points}%
3323     \crefname{enumv}{point}{points}%
3324     \crefname{footnote}{note}{notes}%
3325     \crefname{figure}{figure}{figures}%
3326     \crefname{subfigure}{figure}{figures}%
3327     \crefname{table}{tableau}{tableaux}%
3328     \crefname{subtable}{tableau}{tableaux}%
3329     \crefname{theorem}{th\`eor\`eme}{th\`eor\`emes}%
3330     \crefname{lemma}{lemme}{lemmes}%
3331     \crefname{corollary}{corollaire}{corollaires}%
3332     \crefname{proposition}{proposition}{propositions}%
3333     \crefname{definition}{d\`efinition}{d\`efinitions}%
3334     \crefname{result}{r\`esultat}{r\`esultats}%
3335     \crefname{example}{exemple}{exemples}%
3336     \crefname{remark}{remarque}{remarques}%
3337     \crefname{note}{commentaire}{commentaires}%
3338     \fi%
3339   }}}}

```

`spanish` Spanish translations generously contributed by Gonzalo Medina.

```

3340 \DeclareOption{spanish}{%
3341   \PackageInfo{cleveref}{loaded 'spanish' language definitions}}

```

First, we set up the definitions used at the beginning of the document to define the formats created by the document preamble.

```

3342 \AtBeginDocument{%
3343   \def\crefrangeconjunction@preamble{ a`}%
3344   \def\crefrangepreconjunction@preamble{}%
3345   \def\crefrangepostconjunction@preamble{}%
3346   \def\crefpairconjunction@preamble{ y`}%
3347   \def\crefmiddleconjunction@preamble{, }%
3348   \def\creflastconjunction@preamble{ y`}%
3349   \def\crefpairgroupconjunction@preamble{ y`}%
3350   \def\crefmiddlegroupconjunction@preamble{, }%
3351   \def\creflastgroupconjunction@preamble{ y`}%
3352   \Crefname@preamble{equation}{Ecuaci\`on}{Ecuaciones}%
3353   \Crefname@preamble{chapter}{Cap\`itulo}{Cap\`itulos}%
3354   \Crefname@preamble{section}{Secci\`on}{Secciones}%
3355   \Crefname@preamble{appendix}{Ap\`endice}{Ap\`endices}%
3356   \Crefname@preamble{enumi}{Punto}{Puntos}%
3357   \Crefname@preamble{footnote}{Nota}{Notas}%

```

```

3358 \Crefname@preamble{figure}{Figura}{Figuras}%
3359 \Crefname@preamble{table}{Cuadro}{Cuadros}%
3360 \Crefname@preamble{theorem}{Teorema}{Teoremas}%
3361 \Crefname@preamble{lemma}{Lema}{Lemas}%
3362 \Crefname@preamble{corollary}{Corolario}{Corolarios}%
3363 \Crefname@preamble{proposition}{Proposici\'on}{Proposiciones}%
3364 \Crefname@preamble{definition}{Definici\'on}{Definiciones}%
3365 \Crefname@preamble{result}{Resultado}{Resultados}%
3366 \Crefname@preamble{example}{Ejemplo}{Ejemplos}%
3367 \Crefname@preamble{remark}{Observaci\'on}{Observaciones}%
3368 \Crefname@preamble{note}{Nota}{Notas}%
3369 \if@cref@capitalise%
3370   \crefname@preamble{equation}{Ecuaci\'on}{ecuaciones}%
3371   \crefname@preamble{chapter}{Cap\'itulo}{cap\'itulos}%
3372   \crefname@preamble{section}{Secci\'on}{secciones}%
3373   \crefname@preamble{appendix}{Ap\'endice}{ap\'endices}%
3374   \crefname@preamble{enumi}{Punto}{puntos}%
3375   \crefname@preamble{footnote}{Nota}{Notas}%
3376   \crefname@preamble{figure}{Figura}{figuras}%
3377   \crefname@preamble{table}{Cuadro}{cuadros}%
3378   \crefname@preamble{theorem}{Teorema}{teoremas}%
3379   \crefname@preamble{lemma}{Lema}{lemas}%
3380   \crefname@preamble{corollary}{Corolario}{corolarios}%
3381   \crefname@preamble{proposition}{Proposici\'on}{proposiciones}%
3382   \crefname@preamble{definition}{Definici\'on}{definiciones}%
3383   \crefname@preamble{result}{Resultado}{resultados}%
3384   \crefname@preamble{example}{Ejemplo}{ejemplos}%
3385   \crefname@preamble{remark}{Observaci\'on}{observaciones}%
3386   \crefname@preamble{note}{Nota}{notas}%
3387 \else%
3388   \crefname@preamble{equation}{ecuaci\'on}{ecuaciones}%
3389   \crefname@preamble{chapter}{cap\'itulo}{cap\'itulos}%
3390   \crefname@preamble{section}{secci\'on}{secciones}%
3391   \crefname@preamble{appendix}{ap\'endice}{ap\'endices}%
3392   \crefname@preamble{enumi}{punto}{puntos}%
3393   \crefname@preamble{footnote}{nota}{notas}%
3394   \crefname@preamble{figure}{figura}{figuras}%
3395   \crefname@preamble{table}{cuadro}{cuadros}%
3396   \crefname@preamble{theorem}{teorema}{teoremas}%
3397   \crefname@preamble{lemma}{lema}{lemas}%
3398   \crefname@preamble{corollary}{corolario}{corolarios}%
3399   \crefname@preamble{proposition}{Proposici\'on}{proposiciones}%
3400   \crefname@preamble{definition}{Definici\'on}{definiciones}%
3401   \crefname@preamble{result}{Resultado}{resultados}%
3402   \crefname@preamble{example}{Ejemplo}{ejemplos}%
3403   \crefname@preamble{remark}{Observaci\'on}{observaciones}%
3404   \crefname@preamble{note}{Nota}{notas}%
3405 \fi%
3406 \def\cref@language{spanish}%

```

Next, we add the definitions to `\extras...` so that babel's `\selectlanguage` command will change the format appropriately.

```

3407   \cref@addto\extrasspanish{%
3408     \renewcommand{\crefrangeconjunction}{ a~}%
3409     \renewcommand{\crefrangepreconjunction}{ }%
3410     \renewcommand{\crefrangepostconjunction}{ }%
3411     \renewcommand{\crefpairconjunction}{ y~}%
3412     \renewcommand{\crefmiddleconjunction}{, }%
3413     \renewcommand{\creflastconjunction}{ y~}%
3414     \renewcommand{\crefpairgroupconjunction}{ y~}%
3415     \renewcommand{\crefmiddlegroupconjunction}{, }%
3416     \renewcommand{\creflastgroupconjunction}{ y~}%
3417     \Crefname{equation}{Ecuaci\'on}{Ecuaciones}%
3418     \Crefname{chapter}{Cap\'itulo}{Cap\'itulos}%
3419     \Crefname{section}{Secci\'on}{Secciones}%
3420     \Crefname{subsection}{Secci\'on}{Secciones}%
3421     \Crefname{subsubsection}{Secci\'on}{Secciones}%
3422     \Crefname{appendix}{Ap\'endice}{Ap\'endices}%
3423     \Crefname{subappendix}{Ap\'endice}{Ap\'endices}%
3424     \Crefname{subsubappendix}{Ap\'endice}{Ap\'endices}%
3425     \Crefname{subsubsubappendix}{Ap\'endice}{Ap\'endices}%
3426     \Crefname{enumi}{Punto}{Puntos}%
3427     \Crefname{enumii}{Punto}{Puntos}%
3428     \Crefname{enumiii}{Punto}{Puntos}%
3429     \Crefname{enumiv}{Punto}{Puntos}%
3430     \Crefname{enumv}{Punto}{Puntos}%
3431     \Crefname{footnote}{Nota}{Notas}%
3432     \Crefname{figure}{Figura}{Figuras}%
3433     \Crefname{subfigure}{Figura}{Figuras}%
3434     \Crefname{table}{Cuadro}{Cuadros}%
3435     \Crefname{subtable}{Cuadro}{Cuadros}%
3436     \Crefname{theorem}{Teorema}{Teoremas}%
3437     \Crefname{lemma}{Lema}{Lemas}%
3438     \Crefname{corollary}{Corolario}{Corolarios}%
3439     \Crefname{proposition}{Proposici\'on}{Proposiciones}%
3440     \Crefname{definition}{Definici\'on}{Definiciones}%
3441     \Crefname{result}{Resultado}{Resultados}%
3442     \Crefname{example}{Ejemplo}{Ejemplos}%
3443     \Crefname{remark}{Observaci\'on}{Observaci\'on}%
3444     \Crefname{note}{Nota}{Notas}%
3445     \if@cref@capitalise%
3446       \crefname{equation}{Ecuaci\'on}{Ecuaciones}%
3447       \crefname{chapter}{Cap\'itulo}{Cap\'itulos}%
3448       \crefname{section}{Secci\'on}{Secciones}%
3449       \crefname{subsection}{Secci\'on}{Secciones}%
3450       \crefname{subsubsection}{Secci\'on}{Secciones}%
3451       \crefname{appendix}{Ap\'endice}{Ap\'endices}%
3452       \crefname{subappendix}{Ap\'endice}{Ap\'endices}%
3453       \crefname{subsubappendix}{Ap\'endice}{Ap\'endices}%

```

```

3454 \crefname{subsubsubappendix}{Ap\'endice}{Ap\'endices}%
3455 \crefname{enumi}{Punto}{Puntos}%
3456 \crefname{enumii}{Punto}{Puntos}%
3457 \crefname{enumiii}{Punto}{Puntos}%
3458 \crefname{enumiv}{Punto}{Puntos}%
3459 \crefname{enumv}{Punto}{Puntos}%
3460 \crefname{footnote}{Nota}{Notas}%
3461 \crefname{figure}{Figura}{Figuras}%
3462 \crefname{subfigure}{Figura}{Figuras}%
3463 \crefname{table}{Cuadro}{Cuadros}%
3464 \crefname{subtable}{Cuadro}{Cuadros}%
3465 \crefname{theorem}{Teorema}{Teoremas}%
3466 \crefname{lemma}{Lema}{Lemas}%
3467 \crefname{corollary}{Corolario}{Corolarios}%
3468 \crefname{proposition}{Proposici\'on}{Proposiciones}%
3469 \crefname{definition}{Definici\'on}{Definiciones}%
3470 \crefname{result}{Resultado}{Resultados}%
3471 \crefname{example}{Ejemplo}{Ejemplos}%
3472 \crefname{remark}{Observaci\'on}{Observaci\'ones}%
3473 \crefname{note}{Nota}{Notas}%
3474 \else%
3475   \crefname{equation}{ecuaci\'on}{ecuaciones}%
3476   \crefname{chapter}{cap\'itulo}{cap\'itulos}%
3477   \crefname{section}{secci\'on}{secciones}%
3478   \crefname{subsection}{secci\'on}{secciones}%
3479   \crefname{subsubsection}{secci\'on}{secciones}%
3480   \crefname{appendix}{ap\'endice}{ap\'endices}%
3481   \crefname{subappendix}{ap\'endice}{ap\'endices}%
3482   \crefname{subsubappendix}{ap\'endice}{ap\'endices}%
3483   \crefname{subsubsubappendix}{ap\'endice}{ap\'endices}%
3484   \crefname{enumi}{punto}{puntos}%
3485   \crefname{enumii}{punto}{puntos}%
3486   \crefname{enumiii}{punto}{puntos}%
3487   \crefname{enumiv}{punto}{puntos}%
3488   \crefname{enumv}{punto}{puntos}%
3489   \crefname{footnote}{nota}{notas}%
3490   \crefname{figure}{figura}{figuras}%
3491   \crefname{subfigure}{figura}{figuras}%
3492   \crefname{table}{cuadro}{cuadros}%
3493   \crefname{subtable}{cuadro}{cuadros}%
3494   \crefname{theorem}{teorema}{teoremas}%
3495   \crefname{lemma}{lema}{lemas}%
3496   \crefname{corollary}{corolario}{corolarios}%
3497   \crefname{proposition}{proposici\'on}{proposiciones}%
3498   \crefname{definition}{definici\'on}{definiciones}%
3499   \crefname{result}{resultado}{resultados}%
3500   \crefname{example}{ejemplo}{ejemplos}%
3501   \crefname{remark}{observaci\'on}{observaci\'ones}%
3502   \crefname{note}{nota}{notas}%
3503 \fi%

```

```
3504     }}}
```

italian Italian translations kindly contributed by Massimo Redaelli.

```
3505 \DeclareOption{italian}{%
3506   \PackageInfo{cleveref}{loaded 'italian' language definitions}}
```

First, we set up the definitions used at the beginning of the document to define the formats created by the document preamble. (Note that Italian makes use of `\crefrangepreconjunction`.)

```
3507 \AtBeginDocument{%
3508   \def\crefrangeconjunction@preamble{ a`}%
3509   \def\crefrangepreconjunction@preamble{da`}%
3510   \def\crefrangepostconjunction@preamble{}%
3511   \def\crefpairconjunction@preamble{ e`}%
3512   \def\crefmiddleconjunction@preamble{, }%
3513   \def\creflastconjunction@preamble{ e`}%
```

We have to define the group conjunctions explicitly here, rather than relying on fall-back definitions in terms of the above conjunctions (see Section 12.13.1), in case any other language option defines them explicitly and we need to override those.

```
3514 \def\crefpairgroupconjunction@preamble{ e`}%
3515 \def\crefmiddlegroupconjunction@preamble{, }%
3516 \def\creflastgroupconjunction@preamble{ e`}%
3517 \Crefname@preamble{equation}{Equazione}{Equazioni}%
3518 \Crefname@preamble{chapter}{Capitolo}{Capitoli}%
3519 \Crefname@preamble{section}{Sezione}{Sezioni}%
3520 \Crefname@preamble{appendix}{Appendice}{Appendici}%
3521 \Crefname@preamble{enumi}{Voce}{Voci}%
3522 \Crefname@preamble{footnote}{Nota}{Note}%
3523 \Crefname@preamble{figure}{Figura}{Figure}%
3524 \Crefname@preamble{table}{Tabella}{Tabelle}%
3525 \Crefname@preamble{theorem}{Teorema}{Teoremi}%
3526 \Crefname@preamble{lemma}{Lemma}{Lemmi}%
3527 \Crefname@preamble{corollary}{Corollario}{Corollari}%
3528 \Crefname@preamble{proposition}{Proposizione}{Proposizioni}%
3529 \Crefname@preamble{definition}{Definizione}{Definizioni}%
3530 \Crefname@preamble{result}{Risultato}{Risultati}%
3531 \Crefname@preamble{example}{esempio}{esempi}%
3532 \Crefname@preamble{remark}{Osservazione}{Osservazioni}%
3533 \Crefname@preamble{note}{Nota}{Note}%
3534 \if@cref@capitalise%
3535   \crefname@preamble{equation}{Eq.}{Eq.}%
3536   \crefname@preamble{chapter}{Capitolo}{Capitoli}%
3537   \crefname@preamble{section}{Sezione}{Sezioni}%
3538   \crefname@preamble{appendix}{Appendice}{Appendici}%
3539   \crefname@preamble{enumi}{Voce}{Voci}%
3540   \crefname@preamble{footnote}{Nota}{Note}%
3541   \crefname@preamble{figure}{Fig.}{Fig.}%

```

```

3542   \crefname@preamble{table}{Tabella}{Tabelle}%
3543   \crefname@preamble{theorem}{Teorema}{Teoremi}%
3544   \crefname@preamble{lemma}{Lemma}{Lemmi}%
3545   \crefname@preamble{corollary}{Corollario}{Corollari}%
3546   \crefname@preamble{proposition}{Proposizione}{Proposizioni}%
3547   \crefname@preamble{definition}{Definizione}{Definizioni}%
3548   \crefname@preamble{result}{Risultato}{Risultati}%
3549   \crefname@preamble{example}{Esempio}{Esempi}%
3550   \crefname@preamble{remark}{Osservazione}{Osservazioni}%
3551   \crefname@preamble{note}{Nota}{Note}%
3552 \else%
3553   \crefname@preamble{equation}{eq.}{eq.}%
3554   \crefname@preamble{chapter}{capitolo}{capitoli}%
3555   \crefname@preamble{section}{sezione}{sezioni}%
3556   \crefname@preamble{appendix}{appendice}{appendici}%
3557   \crefname@preamble{enumi}{voce}{voci}%
3558   \crefname@preamble{footnote}{nota}{note}%
3559   \crefname@preamble{figure}{fig.}{fig.}%
3560   \crefname@preamble{table}{tabella}{tabelle}%
3561   \crefname@preamble{theorem}{teorema}{teoremi}%
3562   \crefname@preamble{lemma}{lemma}{lemmi}%
3563   \crefname@preamble{corollary}{corollario}{corollari}%
3564   \crefname@preamble{proposition}{proposizione}{proposizioni}%
3565   \crefname@preamble{definition}{definizione}{definizioni}%
3566   \crefname@preamble{result}{risultato}{risultati}%
3567   \crefname@preamble{example}{esempio}{esempi}%
3568   \crefname@preamble{remark}{osservazione}{osservazioni}%
3569   \crefname@preamble{note}{nota}{note}%
3570 \fi%
3571 \def\cref@language{italian}%

```

Next, we add the definitions to `\extras...` so that babel's `\selectlanguage` command will change the format appropriately.

```

3572 \cref@addto\extrasitalian{%
3573   \renewcommand{\crefrangeconjunction}{ a`}%
3574   \renewcommand\crefrangeconjunciton{da`}%
3575   \renewcommand\crefrangepostconjunction{}%
3576   \renewcommand{\crefpairconjunction}{ e`}%
3577   \renewcommand{\crefmiddleconjunction}{, }%
3578   \renewcommand{\creflastconjunction}{ e`}%
3579   \renewcommand{\crefpairgroupconjunction}{ e`}%
3580   \renewcommand{\crefmiddlegroupconjunction}{, }%
3581   \renewcommand{\creflastgroupconjunction}{ e`}%
3582   \Crefname{equation}{Equazione}{Equazioni}%
3583   \Crefname{chapter}{Capitolo}{Capitoli}%
3584   \Crefname{section}{Sezione}{Sezioni}%
3585   \Crefname{subsection}{Sezione}{Sezioni}%
3586   \Crefname{subsubsection}{Sezione}{Sezioni}%
3587   \Crefname{appendix}{Appendice}{Appendici}%
3588   \Crefname{subappendix}{Appendice}{Appendici}%

```

```

3589 \Crefname{subsubappendix}{Appendice}{Appendici}%
3590 \Crefname{subsubsubappendix}{Appendice}{Appendici}%
3591 \Crefname{enumi}{Voce}{Voci}%
3592 \Crefname{enumii}{Voce}{Voci}%
3593 \Crefname{enumiii}{Voce}{Voci}%
3594 \Crefname{enumiv}{Voce}{Voci}%
3595 \Crefname{enumv}{Voce}{Voci}%
3596 \Crefname{footnote}{Nota}{Note}%
3597 \Crefname{figure}{Figura}{Figure}%
3598 \Crefname{subfigure}{Figura}{Figure}%
3599 \Crefname{table}{Tabella}{Tabelle}%
3600 \Crefname{subtable}{Tabella}{Tabelle}%
3601 \Crefname{theorem}{Teorema}{Teoremi}%
3602 \Crefname{lemma}{Lemma}{Lemmi}%
3603 \Crefname{corollary}{Corollario}{Corollari}%
3604 \Crefname{proposition}{Proposizione}{Proposizioni}%
3605 \Crefname{definition}{Definizione}{Definizione}%
3606 \Crefname{result}{Risultato}{Risultati}%
3607 \Crefname{example}{esempio}{esempi}%
3608 \Crefname{remark}{Osservazione}{Osservazioni}%
3609 \Crefname{note}{Nota}{Note}%
3610 \if@cref@capitalise%
3611   \crefname{equation}{Eq.}{Eq.}%
3612   \crefname{chapter}{Capitolo}{Capitoli}%
3613   \crefname{section}{Sezione}{Sezioni}%
3614   \crefname{subsection}{Sezione}{Sezioni}%
3615   \crefname{subsubsection}{Sezione}{Sezioni}%
3616   \crefname{appendix}{Appendice}{Appendici}%
3617   \crefname{subappendix}{Appendice}{Appendici}%
3618   \crefname{subsubappendix}{Appendice}{Appendici}%
3619   \crefname{subsubsubappendix}{Appendice}{Appendici}%
3620   \crefname{enumi}{Voce}{Voci}%
3621   \crefname{enumii}{Voce}{Voci}%
3622   \crefname{enumiii}{Voce}{Voci}%
3623   \crefname{enumiv}{Voce}{Voci}%
3624   \crefname{enumv}{Voce}{Voci}%
3625   \crefname{footnote}{Nota}{Note}%
3626   \crefname{figure}{Fig.}{Fig.}%
3627   \crefname{subfigure}{Fig.}{Fig.}%
3628   \crefname{table}{Tabella}{Tabelle}%
3629   \crefname{subtable}{Tabella}{Tabelle}%
3630   \crefname{theorem}{Teorema}{Teoremi}%
3631   \crefname{lemma}{Lemma}{Lemmi}%
3632   \crefname{corollary}{Corollario}{Corollari}%
3633   \crefname{proposition}{Proposizione}{Proposizioni}%
3634   \crefname{definition}{Definizione}{Definizione}%
3635   \crefname{result}{Risultato}{Risultati}%
3636   \crefname{example}{Esempio}{Esempi}%
3637   \crefname{remark}{Osservazione}{Osservazioni}%
3638   \crefname{note}{Nota}{Note}%

```

```

3639     \else%
3640         \crefname{equation}{eq.}{eq.}%
3641         \crefname{chapter}{capitolo}{capitoli}%
3642         \crefname{section}{sezione}{sezioni}%
3643         \crefname{subsection}{sezione}{sezioni}%
3644         \crefname{subsubsection}{sezione}{sezioni}%
3645         \crefname{appendix}{appendice}{appendici}%
3646         \crefname{subappendix}{appendice}{appendici}%
3647         \crefname{subsubappendix}{appendice}{appendici}%
3648         \crefname{subsubsubappendix}{appendice}{appendici}%
3649         \crefname{enumi}{voce}{voci}%
3650         \crefname{enumii}{voce}{voci}%
3651         \crefname{enumiii}{voce}{voci}%
3652         \crefname{enumiv}{voce}{voci}%
3653         \crefname{enumv}{voce}{voci}%
3654         \crefname{footnote}{nota}{note}%
3655         \crefname{figure}{fig.}{fig.}%
3656         \crefname{subfigure}{fig.}{fig.}%
3657         \crefname{table}{tabella}{tabelle}%
3658         \crefname{subtable}{tabella}{tabelle}%
3659         \crefname{theorem}{teorema}{teoremi}%
3660         \crefname{lemma}{lemma}{lemmi}%
3661         \crefname{corollary}{corollario}{corollari}%
3662         \crefname{proposition}{proposizione}{proposizioni}%
3663         \crefname{definition}{definizione}{definizioni}%
3664         \crefname{result}{risultato}{risultati}%
3665         \crefname{example}{esempio}{esempi}%
3666         \crefname{remark}{osservazione}{osservazioni}%
3667         \crefname{note}{nota}{note}%
3668     \fi%
3669 }

```

russian Russian translations generously contributed by Aleksander Gorohovski.

```

3670 \DeclareOption{russian}{%
3671   \PackageInfo{cleveref}{loaded 'russian' language definitions}

```

First, we set up the definitions used at the beginning of the document to define the formats created by the document preamble.

```

3672 \AtBeginDocument{%
3673   \def\crefrangeconjunction@preamble{--}%
3674   \def\crefrangepreconjunction@preamble{}%
3675   \def\crefrangepostconjunction@preamble{}%
3676   \def\crefpairconjunction@preamble{\text{cyri}^{\text{-}}}%
3677   \def\crefmiddleconjunction@preamble{, }%
3678   \def\creflastconjunction@preamble{\text{cyri}^{\text{-}}}%

```

We have to define the group conjunctions explicitly here, rather than relying on fall-back definitions in terms of the above conjunctions (see Section 12.13.1), in case any other language option defines them explicitly and we need to override those.


```

3729   {\CYRP\cyrr\cyri\cyrm\cyre\cyrch\cyra\cyrn\cyri\cyre}%
3730   {\CYRP\cyrr\cyri\cyrm\cyre\cyrch\cyra\cyrn\cyri\cyrya}%
3731 \Crefname@preamble{note}%
3732   {\CYRZ\cyra\cyrm\cyre\cyrt\cyrk\cyra}%
3733   {\CYRZ\cyra\cyrm\cyre\cyrt\cyrk\cyri}%
3734 \if@cref@capitalise%
3735   \crefname@preamble{equation}%
3736     {\CYRF-\cyrl.}%
3737     {\CYRF-\cyrl.}%
3738   \crefname@preamble{chapter}%
3739     {\CYRG\cyrl\cyra\cyrv\cyra}%
3740     {\CYRG\cyrl\cyra\cyrv\cyrery}%
3741   \crefname@preamble{section}%
3742     {\CYRR\cyra\cyrz\cyrd\cyre\cyrl}%
3743     {\CYRR\cyra\cyrz\cyrd\cyre\cyrl\cyrery}%
3744   \crefname@preamble{appendix}%
3745     {\CYRP\cyrr\cyri\cyrl\cyro\cyrh\cyre\cyrn\cyri\cyre}%
3746     {\CYRP\cyrr\cyri\cyrl\cyro\cyrh\cyre\cyrn\cyri\cyrya}%
3747 \crefname@preamble{enumi}{\CYRP.}{\CYRP.\cyrp.}%
3748 \crefname@preamble{footnote}%
3749   {\CYRS\cyrn\cyro\cyrs\cyrk\cyra}%
3750   {\CYRS\cyrn\cyro\cyrs\cyrk\cyri}%
3751 \crefname@preamble{figure}%
3752   {\CYRR\cyri\cyrs.}%
3753   {\CYRR\cyri\cyrs.}%
3754 \crefname@preamble{table}%
3755   {\CYRT\cyra\cyrb\cyrl.}%
3756   {\CYRT\cyra\cyrb\cyrl.}%
3757 \crefname@preamble{theorem}%
3758   {\CYRT\cyre\cyro\cyrr\cyre\cyrm\cyra}%
3759   {\CYRT\cyre\cyro\cyrr\cyre\cyrm\cyrery}%
3760 \crefname@preamble{lemma}%
3761   {\CYRL\cyre\cyrm\cyrm\cyra}%
3762   {\CYRL\cyre\cyrm\cyrm\cyrery}%
3763 \crefname@preamble{corollary}%
3764   {\CYRV\cyrery\cyrv\cyro\cyrd}%
3765   {\CYRV\cyrery\cyrv\cyro\cyrd\cyrery}%
3766 \crefname@preamble{proposition}%
3767   {\CYRU\cyrt\cyrv\cyre\cyrr\cyrh\cyrd\cyre\cyrn\cyri\cyre}%
3768   {\CYRU\cyrt\cyrv\cyre\cyrr\cyrh\cyrd\cyre\cyrn\cyri\cyrya}%
3769 \crefname@preamble{definition}%
3770   {\CYRO\cyrp\cyrr\cyre\cyrd\cyre\cyrl\cyre\cyrn\cyri\cyre}%
3771   {\CYRO\cyrp\cyrr\cyre\cyrd\cyre\cyrl\cyre\cyrn\cyri\cyrya}%
3772 \crefname@preamble{result}%
3773   {\CYRR\cyre\cyrz\cyru\cyrl\cyrsftsn\cyrt\cyra\cyrt}%
3774   {\CYRR\cyre\cyrz\cyru\cyrl\cyrsftsn\cyrt\cyra\cyrt\cyrery}%
3775 \crefname@preamble{example}%
3776   {\CYRP\cyrr\cyri\cyrm\cyre\cyrr}%
3777   {\CYRP\cyrr\cyri\cyrm\cyre\cyrr\cyrery}%
3778 \crefname@preamble{remark}%

```

```

3779      {\CYRP\cyrr\cyri\cyrm\cyre\cyrch\cyra\cyrn\cyri\cyre}%
3780      {\CYRP\cyrr\cyri\cyrm\cyre\cyrch\cyra\cyrn\cyri\cyrya}%
3781 \crefname@preamble{note}%
3782      {\CYRZ\cyra\cyrm\cyre\cyrt\cyrk\cyra}%
3783      {\CYRZ\cyra\cyrm\cyre\cyrt\cyrk\cyri}%
3784 \else%
3785 \crefname@preamble{equation}{\cyrf-\cyrl.}{\cyrf-\cyrl.}%
3786 \crefname@preamble{chapter}%
3787      {\cyrg\cyrl\cyra\cyrv.}%
3788      {\cyrg\cyrl\cyra\cyrv.}%
3789 \crefname@preamble{section}%
3790      {\cyrr\cyra\cyrz\cyrd.}%
3791      {\cyrr\cyra\cyrz\cyrd\cyre\cyrl.}%
3792 \crefname@preamble{appendix}%
3793      {\cyrp\cyrr\cyri\cyrl\cyro\cyrz.}%
3794      {\cyrp\cyrr\cyri\cyrl\cyro\cyrz.}%
3795 \crefname@preamble{enumi}{\cyrp.}{\cyrp.\cyrp.}%
3796 \crefname@preamble{footnote}%
3797      {\cyrs\cyrn\cyro\cyrs\cyrk.}%
3798      {\cyrs\cyrn\cyro\cyrs\cyrk.}%
3799 \crefname@preamble{figure}%
3800      {\cyrr\cyri\cyrs.}%
3801      {\cyrr\cyri\cyrs.}%
3802 \crefname@preamble{table}%
3803      {\cyrt\cyra\cyrb\cyrl.}%
3804      {\cyrt\cyra\cyrb\cyrl.}%
3805 \crefname@preamble{theorem}%
3806      {\cyrt\cyre\cyro\cyrr\cyre\cyrm.}%
3807      {\cyrt\cyre\cyro\cyrr\cyre\cyrm.}%
3808 \crefname@preamble{lemma}%
3809      {\cyrl\cyre\cyrm\cyrm.}%
3810      {\cyrl\cyre\cyrm\cyrm.}%
3811 \crefname@preamble{corollary}%
3812      {\cyrv\cyrery\cyrv\cyro\cyrd}%
3813      {\cyrv\cyrery\cyrv\cyro\cyrd.}%
3814 \crefname@preamble{proposition}%
3815      {\cyru\cyrt\cyrv\cyre\cyrr\cyrz\cyrd.}%
3816      {\cyru\cyrt\cyrv\cyre\cyrr\cyrz\cyrd.}%
3817 \crefname@preamble{definition}%
3818      {\cyro\cyrp\cyrr\cyre\cyrd\cyre\cyrl\cyre\cyrn.}%
3819      {\cyro\cyrp\cyrr\cyre\cyrd\cyre\cyrl\cyre\cyrn.}%
3820 \crefname@preamble{result}%
3821      {\cyrr\cyre\cyrz\cyru\cyrl\cyrsftsn\cyrt.}%
3822      {\cyrr\cyre\cyrz\cyru\cyrl\cyrsftsn\cyrt.}%
3823 \crefname@preamble{example}%
3824      {\cyrp\cyrr\cyri\cyrm.}%
3825      {\cyrp\cyrr\cyri\cyrm\cyre\cyrr.}%
3826 \crefname@preamble{remark}%
3827      {\cyrp\cyrr\cyri\cyrm\cyre\cyrch.}%
3828      {\cyrp\cyrr\cyri\cyrm\cyre\cyrch.}%

```

```

3829     \crefname@preamble{note}%
3830         {\cyrz\cyra\cyrm\cyre\cyrt\cyrk.}%
3831         {\cyrz\cyra\cyrm\cyre\cyrt\cyrk.}%
3832 \fi%
3833 \def\cref@language{russian}%

```

Next, we add the definitions to `\extras...` so that `babel's \selectlanguage command will change the format appropriately.`

```

3834 \cref@addto\extrasrussian{%
3835     \renewcommand{\crefrangeconjunction}{--}%
3836     \renewcommand{\crefrangepreconjunction}{ }%
3837     \renewcommand{\crefrangepostconjunction}{ }%
3838     \renewcommand{\crefpairconjunction}{ \cyri~}%
3839     \renewcommand{\crefmiddleconjunction}{, }%
3840     \renewcommand{\creflastconjunction}{ \cyri~}%
3841     \renewcommand{\crefpairgroupconjunction}{ \cyri~}%
3842     \renewcommand{\crefmiddlegroupconjunction}{, }%
3843     \renewcommand{\creflastgroupconjunction}{%
3844         {, \cyra\cyrt\cyra\cyrk\cyrzh\cyre~}%
3845     \Crefname{equation}%
3846         {\CYRF\cyro\cyrr\cyrm\cyru\cyrl\cyra}%
3847         {\CYRF\cyro\cyrr\cyrm\cyru\cyrl\cyrery}%
3848 \Crefname{chapter}%
3849     {\CYRG\cyrl\cyra\cyrv\cyra}%
3850     {\CYRG\cyrl\cyra\cyrv\cyrery}%
3851 \Crefname{section}%
3852     {\CYRR\cyra\cyrz\cyrd\cyre\cyrl}%
3853     {\CYRR\cyra\cyrz\cyrd\cyre\cyrl\cyrery}%
3854 \Crefname{subsection}%
3855     {\CYRP\cyro\cyrd\cyrr\cyra\cyrz\cyrd\cyre\cyrl}%
3856     {\CYRP\cyro\cyrd\cyrr\cyra\cyrz\cyrd\cyre\cyrl\cyrery}%
3857 \Crefname{subsubsection}%
3858     {\CYRP\cyro\cyrd\cyrp\cyro\cyrd\cyrr\cyra\cyrz\cyrd\cyre\cyrl}%
3859     {\CYRP\cyro\cyrd\cyrp\cyro\cyrd\cyrr\cyra\cyrz\cyrd\cyre\cyrl\cyrery}%
3860 \Crefname{appendix}%
3861     {\CYRP\cyrr\cyri\cyrl\cyro\cyrzh\cyre\cyrn\cyri\cyre}%
3862     {\CYRP\cyrr\cyri\cyrl\cyro\cyrzh\cyre\cyrn\cyri\cyrya}%
3863 \Crefname{subappendix}%
3864     {\CYRP\cyrr\cyri\cyrl\cyro\cyrzh\cyre\cyrn\cyri\cyre}%
3865     {\CYRP\cyrr\cyri\cyrl\cyro\cyrzh\cyre\cyrn\cyri\cyrya}%
3866 \Crefname{subsubappendix}%
3867     {\CYRP\cyrr\cyri\cyrl\cyro\cyrzh\cyre\cyrn\cyri\cyre}%
3868     {\CYRP\cyrr\cyri\cyrl\cyro\cyrzh\cyre\cyrn\cyri\cyrya}%
3869 \Crefname{subsubsubappendix}%
3870     {\CYRP\cyrr\cyri\cyrl\cyro\cyrzh\cyre\cyrn\cyri\cyre}%
3871     {\CYRP\cyrr\cyri\cyrl\cyro\cyrzh\cyre\cyrn\cyri\cyrya}%
3872 \Crefname{enumi}%
3873     {\CYRP\cyru\cyrn\cyrk\cyrt}%
3874     {\CYRP\cyru\cyrn\cyrk\cyrt\cyrery}%
3875 \Crefname{enumii}%

```

```

3876      {\CYRP\cyru\cyrn\cyrk\cyrt}%
3877      {\CYRP\cyru\cyrn\cyrk\cyrt\cyrery}%
3878 \Crefname{enumiii}%
3879      {\CYRP\cyru\cyrn\cyrk\cyrt}%
3880      {\CYRP\cyru\cyrn\cyrk\cyrt\cyrery}%
3881 \Crefname{enumiv}%
3882      {\CYRP\cyru\cyrn\cyrk\cyrt}%
3883      {\CYRP\cyru\cyrn\cyrk\cyrt\cyrery}%
3884 \Crefname{enumv}%
3885      {\CYRP\cyru\cyrn\cyrk\cyrt}%
3886      {\CYRP\cyru\cyrn\cyrk\cyrt\cyrery}%
3887 \Crefname{footnote}%
3888      {\CYRS\cyrn\cyro\crys\cyrk\cyra}%
3889      {\CYRS\cyrn\cyro\crys\cyrk\cyri}%
3890 \Crefname{figure}%
3891      {\CYRR\cyri\crys\cyru\cyrn\cyro\cyrk}%
3892      {\CYRR\cyri\crys\cyru\cyrn\cyrk\cyri}%
3893 \Crefname{subfigure}%
3894      {\CYRR\cyri\crys\cyru\cyrn\cyro\cyrk}%
3895      {\CYRR\cyri\crys\cyru\cyrn\cyrk\cyri}%
3896 \Crefname{table}%
3897      {\CYRT\cyra\cyrb\cyrl\cyri\cyrc\cyra}%
3898      {\CYRT\cyra\cyrb\cyrl\cyri\cyrc\cyrery}%
3899 \Crefname{subtable}%
3900      {\CYRT\cyra\cyrb\cyrl\cyri\cyrc\cyra}%
3901      {\CYRT\cyra\cyrb\cyrl\cyri\cyrc\cyrery}%
3902 \Crefname{theorem}%
3903      {\CYRT\cyre\cyro\cyrr\cyre\cyrm\cyra}%
3904      {\CYRT\cyre\cyro\cyrr\cyre\cyrm\cyrery}%
3905 \Crefname{lemma}%
3906      {\CYRL\cyre\cyrm\cyrm\cyra}%
3907      {\CYRL\cyre\cyrm\cyrm\cyrery}%
3908 \Crefname{corollary}%
3909      {\CYRV\cyrery\cyrv\cyro\cyrd}%
3910      {\CYRV\cyrery\cyrv\cyro\cyrd\cyrery}%
3911 \Crefname{proposition}%
3912      {\CYRU\cyrt\cyrv\cyre\cyrr\cyrh\cyrd\cyre\cyrn\cyri\cyre}%
3913      {\CYRU\cyrt\cyrv\cyre\cyrr\cyrh\cyrd\cyre\cyrn\cyri\cyra}%
3914 \Crefname{definition}%
3915      {\CYRO\cyrp\cyrr\cyre\cyrd\cyre\cyrl\cyre\cyrn\cyri\cyre}%
3916      {\CYRO\cyrp\cyrr\cyre\cyrd\cyre\cyrl\cyre\cyrn\cyri\cyra}%
3917 \Crefname{result}%
3918      {\CYRR\cyre\cyrz\cyru\cyrl\crysftsn\cyrt\cyra\cyrt}%
3919      {\CYRR\cyre\cyrz\cyru\cyrl\crysftsn\cyrt\cyra\cyrt\cyrery}%
3920 \Crefname{example}%
3921      {\CYRP\cyrr\cyri\cyrm\cyre\cyrr}%
3922      {\CYRP\cyrr\cyri\cyrm\cyre\cyrr\cyrery}%
3923 \Crefname{remark}%
3924      {\CYRP\cyrr\cyri\cyrm\cyre\cyrch\cyra\cyrn\cyri\cyre}%
3925      {\CYRP\cyrr\cyri\cyrm\cyre\cyrch\cyra\cyrn\cyri\cyra}%

```

```

3926 \Crefname{note}%
3927   {\CYRZ\cyra\cyrm\cyre\cyrt\cyrk\cyra}%
3928   {\CYRZ\cyra\cyrm\cyre\cyrt\cyrk\cyri}%
3929 \if@ cref @ capitalise %
3930   \crefname{equation}{\CYRF-\cyrl.}{\CYRF-\cyrl.}%
3931   \crefname{chapter}%
3932     {\CYRG\cyrl\cyra\cyrv\cyra}%
3933     {\CYRG\cyrl\cyra\cyrv\cyrery}%
3934   \crefname{section}%
3935     {\CYRR\cyra\cyrz\cyrd\cyre\cyrl}%
3936     {\CYRR\cyra\cyrz\cyrd\cyre\cyrl\cyrery}%
3937   \crefname{subsection}%
3938     {\CYRP\cyro\cyrd\cyrr\cyra\cyrz\cyrd\cyre\cyrl}%
3939     {\CYRP\cyro\cyrd\cyrr\cyra\cyrz\cyrd\cyre\cyrl\cyrery}%
3940   \crefname{subsubsection}%
3941     {\CYRP\cyro\cyrd\cyrp\cyro\cyrd\cyrr\cyra\cyrz\cyrd\cyre\cyrl}%
3942     {\CYRP\cyro\cyrd\cyrp\cyro\cyrd\cyrr\cyra\cyrz\cyrd\cyre\cyrl\cyrery}%
3943 \crefname{appendix}%
3944   {\CYRP\cyrr\cyri\cyrl\cyro\cyrzh\cyre\cyrn\cyri\cyre}%
3945   {\CYRP\cyrr\cyri\cyrl\cyro\cyrzh\cyre\cyrn\cyri\cyrya}%
3946 \crefname{subappendix}%
3947   {\CYRP\cyrr\cyri\cyrl\cyro\cyrzh\cyre\cyrn\cyri\cyre}%
3948   {\CYRP\cyrr\cyri\cyrl\cyro\cyrzh\cyre\cyrn\cyri\cyrya}%
3949 \crefname{subsubappendix}%
3950   {\CYRP\cyrr\cyri\cyrl\cyro\cyrzh\cyre\cyrn\cyri\cyre}%
3951   {\CYRP\cyrr\cyri\cyrl\cyro\cyrzh\cyre\cyrn\cyri\cyrya}%
3952 \crefname{subsubsubappendix}%
3953   {\CYRP\cyrr\cyri\cyrl\cyro\cyrzh\cyre\cyrn\cyri\cyre}%
3954   {\CYRP\cyrr\cyri\cyrl\cyro\cyrzh\cyre\cyrn\cyri\cyrya}%
3955 \crefname{enumi}{\CYRP.}{\CYRP.\cyrp.}%
3956 \crefname{enumii}{\CYRP.}{\CYRP.\cyrp.}%
3957 \crefname{enumiii}{\CYRP.}{\CYRP.\cyrp.}%
3958 \crefname{enumiv}{\CYRP.}{\CYRP.\cyrp.}%
3959 \crefname{enumv}{\CYRP.}{\CYRP.\cyrp.}%
3960 \crefname{footnote}%
3961   {\CYRS\cyrn\cyro\cyrs\cyrk\cyra}%
3962   {\CYRS\cyrn\cyro\cyrs\cyrk\cyri}%
3963 \crefname{figure}%
3964   {\CYRR\cyri\cyrs.}%
3965   {\CYRR\cyri\cyrs.}%
3966 \crefname{subfigure}%
3967   {\CYRR\cyri\cyrs.}%
3968   {\CYRR\cyri\cyrs.}%
3969 \crefname{table}%
3970   {\CYRT\cyra\cyrb\cyrl.}%
3971   {\CYRT\cyra\cyrb\cyrl.}%
3972 \crefname{subtable}%
3973   {\CYRT\cyra\cyrb\cyrl.}%
3974   {\CYRT\cyra\cyrb\cyrl.}%
3975 \crefname{theorem}%

```

```

3976   {\CYRT\cyre\cyro\cyrr\cyre\cyrm\cyra}%
3977   {\CYRT\cyre\cyro\cyrr\cyre\cyrm\cyrery}%
3978 \crefname{lemma}%
3979   {\CYRL\cyre\cyrm\cyrm\cyra}%
3980   {\CYRL\cyre\cyrm\cyrm\cyrery}%
3981 \crefname{corollary}%
3982   {\CYRV\cyrery\cyrv\cyro\cyrd}%
3983   {\CYRV\cyrery\cyrv\cyro\cyrd\cyrery}%
3984 \crefname{proposition}%
3985   {\CYRU\cyrt\cyrv\cyre\cyrr\cyrzh\cyrd\cyre\cyrn\cyri\cyre}%
3986   {\CYRU\cyrt\cyrv\cyre\cyrr\cyrzh\cyrd\cyre\cyrn\cyri\cyrya}%
3987 \crefname{definition}%
3988   {\CYRO\cyrp\cyrr\cyre\cyrd\cyre\cyrl\cyre\cyrn\cyri\cyre}%
3989   {\CYRO\cyrp\cyrr\cyre\cyrd\cyre\cyrl\cyre\cyrn\cyri\cyrya}%
3990 \crefname{result}%
3991   {\CYRR\cyre\cyrz\cyru\cyrl\cysts\cyrt\cyra\cyrt}%
3992   {\CYRR\cyre\cyrz\cyru\cyrl\cysts\cyrt\cyra\cyrt\cyrery}%
3993 \crefname{example}%
3994   {\CYRP\cyrr\cyri\cyrm\cyre\cyrr}%
3995   {\CYRP\cyrr\cyri\cyrm\cyre\cyrr\cyrery}%
3996 \crefname{remark}%
3997   {\CYRP\cyrr\cyri\cyrm\cyre\cyrch\cyra\cyrn\cyri\cyre}%
3998   {\CYRP\cyrr\cyri\cyrm\cyre\cyrch\cyra\cyrn\cyri\cyrya}%
3999 \crefname{note}%
4000   {\CYRZ\cyra\cyrm\cyre\cyrt\cyrk\cyra}%
4001   {\CYRZ\cyra\cyrm\cyre\cyrt\cyrk\cyri}%
4002 \else%
4003 \crefname{equation}{\cyrf-\cyrl}{\cyrf-\cyrl.}%
4004 \crefname{chapter}{\cyrg\cyrl\cyra\cyrv.}{\cyrg\cyrl\cyra\cyrv.}%
4005 \crefname{section}%
4006   {\cyrr\cyra\cyrz\cyrd.}%
4007   {\cyrr\cyra\cyrz\cyrd\cyre\cyrl.}%
4008 \crefname{subsection}%
4009   {\cyrp\cyro\cyrd\cyrr\cyra\cyrz\cyrd.}%
4010   {\cyrp\cyro\cyrd\cyrr\cyra\cyrz\cyrd\cyre\cyrl.}%
4011 \crefname{subsubsection}%
4012   {\cyrp\cyro\cyrd\cyrp\cyro\cyrd\cyrr\cyra\cyrz\cyrd.}%
4013   {\cyrp\cyro\cyrd\cyrp\cyro\cyrd\cyrr\cyra\cyrd\cyre\cyrl.}%
4014 \crefname{appendix}%
4015   {\cyrp\cyrr\cyri\cyrl\cyro\cyrzh.}%
4016   {\cyrp\cyrr\cyri\cyrl\cyro\cyrzh.}%
4017 \crefname{subappendix}%
4018   {\cyrp\cyrr\cyri\cyrl\cyro\cyrzh.}%
4019   {\cyrp\cyrr\cyri\cyrl\cyro\cyrzh.}%
4020 \crefname{subsubappendix}%
4021   {\cyrp\cyrr\cyri\cyrl\cyro\cyrzh.}%
4022   {\cyrp\cyrr\cyri\cyrl\cyro\cyrzh.}%
4023 \crefname{subsubsubappendix}%
4024   {\cyrp\cyrr\cyri\cyrl\cyro\cyrzh.}%
4025   {\cyrp\cyrr\cyri\cyrl\cyro\cyrzh.}%

```

```

4026 \crefname{enumi}{\cyrp.\cyrp.}%
4027 \crefname{enumii}{\cyrp.\cyrp.}%
4028 \crefname{enumiii}{\cyrp.\cyrp.}%
4029 \crefname{enumiv}{\cyrp.\cyrp.}%
4030 \crefname{enumv}{\cyrp.\cyrp.}%
4031 \crefname{footnote}%
4032 {\cyrs\cyrn\cyro\cyrs\cyrk.}%
4033 {\cyrs\cyrn\cyro\cyrs\cyrk.}%
4034 \crefname{figure}%
4035 {\cyrr\cyri\cyrs.}%
4036 {\cyrr\cyri\cyrs.}%
4037 \crefname{subfigure}%
4038 {\cyrr\cyri\cyrs.}%
4039 {\cyrr\cyri\cyrs.}%
4040 \crefname{table}%
4041 {\cyrt\cyra\cyrb\cyrl.}%
4042 {\cyrt\cyra\cyrb\cyrl.}%
4043 \crefname{subtable}%
4044 {\cyrt\cyra\cyrb\cyrl.}%
4045 {\cyrt\cyra\cyrb\cyrl.}%
4046 \crefname{theorem}%
4047 {\cyrt\cyre\cyro\cyrr\cyre\cyrm.}%
4048 {\cyrt\cyre\cyro\cyrr\cyre\cyrm.}%
4049 \crefname{lemma}%
4050 {\cyrl\cyre\cyrm\cyrm.}%
4051 {\cyrl\cyre\cyrm\cyrm.}%
4052 \crefname{corollary}%
4053 {\cyrv\cyrery\cyrv\cyro\cyrd}%
4054 {\cyrv\cyrery\cyrv\cyro\cyrd.}%
4055 \crefname{proposition}%
4056 {\cyru\cyrt\cyrv\cyre\cyrr\cyrzh\cyrd.}%
4057 {\cyru\cyrt\cyrv\cyre\cyrr\cyrzh\cyrd.}%
4058 \crefname{definition}%
4059 {\cyro\cyrp\cyrr\cyre\cyrd\cyre\cyrl\cyre\cyrn.}%
4060 {\cyro\cyrp\cyrr\cyre\cyrd\cyre\cyrl\cyre\cyrn.}%
4061 \crefname{result}%
4062 {\cyrr\cyre\cyrz\cyru\cyrl\crysftsn\cyrt.}%
4063 {\cyrr\cyre\cyrz\cyru\cyrl\crysftsn\cyrt.}%
4064 \crefname{example}%
4065 {\cyrp\cyrr\cyri\cyrm.}%
4066 {\cyrp\cyrr\cyri\cyrm\cyre\cyrr.}%
4067 \crefname{remark}%
4068 {\cyrp\cyrr\cyri\cyrm\cyre\cyrch.}%
4069 {\cyrp\cyrr\cyri\cyrm\cyre\cyrch.}%
4070 \crefname{note}%
4071 {\cyrz\cyra\cyrm\cyre\cyrt\cyrk.}%
4072 {\cyrz\cyra\cyrm\cyre\cyrt\cyrk.}%
4073 \fi%
4074 }}}

```

ukrainian Ukrainian translations courtesy of Aleksander Gorohovski.

```
4075 \DeclareOption{ukrainian}{%
4076   \PackageInfo{cleveref}{loaded 'ukrainian' language definitions}}
```

First, we set up the definitions used at the beginning of the document to define the formats created by the document preamble.

```
4077 \AtBeginDocument{%
4078   \def\crefrangeconjunction@preamble{--}%
4079   \def\crefrangepreconjunction@preamble{}%
4080   \def\crefrangepostconjunction@preamble{}%
4081   \def\crefpairconjunction@preamble{\cyrii~}%
4082   \def\crefmiddleconjunction@preamble{, }%
4083   \def\creflastconjunction@preamble{\cyrii~}%
}
```

We have to define the group conjunctions explicitly here, rather than relying on fall-back definitions in terms of the above conjunctions (see Section 12.13.1), in case any other language option defines them explicitly and we need to override those.

```
4084 \def\crefpairgroupconjunction@preamble{\cyrt\cyra~}%
4085 \def\crefmiddlegroupconjunction@preamble{, }%
4086 \def\creflastgroupconjunction@preamble{%
4087   \cyra\ \cyrt\cyra\cyrk\cyro\cyrzh~}%
4088 \Crefname@preamble{equation}%
4089   {\CYRF\cyro\cyrr\cyrm\cyru\cyrl\cyra}%
4090   {\CYRF\cyro\cyrr\cyrm\cyru\cyrl\cyri}%
4091 \Crefname@preamble{chapter}%
4092   {\CYRG\cyrl\cyra\cyrv\cyra}%
4093   {\CYRG\cyrl\cyra\cyrv\cyri}%
4094 \Crefname@preamble{section}%
4095   {\CYRR\cyro\cyrz\cyrd\cyrii\cyrl}%
4096   {\CYRR\cyro\cyrz\cyrd\cyrii\cyrl\cyri}%
4097 \Crefname@preamble{appendix}%
4098   {\CYRD\cyro\cyrd\cyra\cyrt\cyro\cyrk}%
4099   {\CYRD\cyro\cyrd\cyra\cyrt\cyrk\cyri}%
4100 \Crefname@preamble{enumi}%
4101   {\CYRP\cyru\cyrn\cyrk\cyrt}%
4102   {\CYRP\cyru\cyrn\cyrk\cyrt\cyri}%
4103 \Crefname@preamble{footnote}%
4104   {\CYRV\cyri\cyrn\cyro\crys\cyrk\cyra}%
4105   {\CYRV\cyri\cyrn\cyro\crys\cyrk\cyri}%
4106 \Crefname@preamble{figure}%
4107   {\CYRR\cyri\crys\cyru\cyrn\cyro\cyrk}%
4108   {\CYRR\cyri\crys\cyru\cyrn\cyrk\cyri}%
4109 \Crefname@preamble{table}%
4110   {\CYRT\cyra\cyrb\cyrl\cyri\cyrc\cyra}%
4111   {\CYRT\cyra\cyrb\cyrl\cyri\cyrc\cyrii}%
4112 \Crefname@preamble{theorem}%
4113   {\CYRT\cyre\cyro\cyrr\cyre\cyrn\cyra}%
4114   {\CYRT\cyre\cyro\cyrr\cyre\cyrn\cyri}%
}
```

```

4115  \Crefname@preamble{lemma}%
4116  {\CYRL\cyre\cyrm\cyrm\cyra}%
4117  {\CYRL\cyre\cyrm\cyrm\cyri}%
4118  \Crefname@preamble{corollary}%
4119  {\CYRV\cyri\cyrs\cyrn\cyro\cyrv\cyro\cyrk}%
4120  {\CYRV\cyri\cyrs\cyrn\cyro\cyrv\cyrk\cyri}%
4121  \Crefname@preamble{proposition}%
4122  {\CYRT\cyrv\cyre\cyrr\cyrd\cyrzh\cyre\cyrn\cyrn\cyrya}%
4123  {\CYRT\cyrv\cyre\cyrr\cyrd\cyrzh\cyre\cyrn\cyrn\cyrya}%
4124  \Crefname@preamble{definition}%
4125  {\CYRV\cyri\cyrz\cyrn\cyra\cyrch\cyre\cyrn\cyrn\cyrya}%
4126  {\CYRV\cyri\cyrz\cyrn\cyra\cyrch\cyre\cyrn\cyrn\cyrya}%
4127  \Crefname@preamble{result}%
4128  {\CYRR\cyre\cyrz\cyru\cyrl\crysftsn\cyrt\cyra\cyrt}%
4129  {\CYRR\cyre\cyrz\cyru\cyrl\crysftsn\cyrt\cyra\cyrt\cyri}%
4130  \Crefname@preamble{example}%
4131  {\CYRP\cyrr\cyri\cyrk\cyrl\cyra\cyrd}%
4132  {\CYRP\cyrr\cyri\cyrk\cyrl\cyra\cyrd\cyri}%
4133  \Crefname@preamble{remark}%
4134  {\CYRP\cyrr\cyri\cyrm\cyrii\cyrt\cyrk\cyra}%
4135  {\CYRP\cyrr\cyri\cyrm\cyrii\cyrt\cyrk\cyri}%
4136  \Crefname@preamble{note}%
4137  {\CYRZ\cyra\cyrm\cyrii\cyrt\cyrk\cyra}%
4138  {\CYRZ\cyra\cyrm\cyrii\cyrt\cyrk\cyri}%
4139  \if@cref@capitalise%
4140  \crefname@preamble{equation}{\CYRF-\cyrl.}{\CYRF-\cyrl.}%
4141  \crefname@preamble{chapter}%
4142  {\CYRG\cyrl\cyra\cyrv\cyra}%
4143  {\CYRG\cyrl\cyra\cyrv\cyri}%
4144  \crefname@preamble{section}%
4145  {\CYRR\cyro\cyrz\cyrd\cyrii\cyrl}%
4146  {\CYRR\cyro\cyrz\cyrd\cyrii\cyrl\cyri}%
4147  \crefname@preamble{appendix}%
4148  {\CYRD\cyro\cyrd\cyra\cyrt\cyro\cyrk}%
4149  {\CYRD\cyro\cyrd\cyra\cyrt\cyrk\cyri}%
4150  \crefname@preamble{enumi}{\CYRP.}{\CYRP.\cyrp.}%
4151  \crefname@preamble{footnote}%
4152  {\CYRV\cyri\cyrn\cyro\crys\cyrk\cyra}%
4153  {\CYRV\cyri\cyrn\cyro\crys\cyrk\cyri}%
4154  \crefname@preamble{figure}%
4155  {\CYRR\cyri\crys.}%
4156  {\CYRR\cyri\crys.}%
4157  \crefname@preamble{table}%
4158  {\CYRT\cyra\cyrb\cyrl.}%
4159  {\CYRT\cyra\cyrb\cyrl.}%
4160  \crefname@preamble{theorem}%
4161  {\CYRT\cyre\cyro\cyrr\cyre\cyrm\cyra}%
4162  {\CYRT\cyre\cyro\cyrr\cyre\cyrm\cyri}%
4163  \crefname@preamble{lemma}%
4164  {\CYRL\cyre\cyrm\cyrm\cyra}%

```



```

4215   {\cyrv\cyri\cyrs\cyrn\cyro\cyrv.}%
4216   {\cyrv\cyri\cyrs\cyrn\cyro\cyrv\cyrk.}%
4217 \crefname@preamble{proposition}%
4218   {\cyrt\cyrv\cyre\cyrr\cyrd\cyrzh\cyre\cyrn\cyrn.}%
4219   {\cyrt\cyrv\cyre\cyrr\cyrd\cyrzh\cyre\cyrn\cyrn.}%
4220 \crefname@preamble{definition}%
4221   {\cyrv\cyri\cyrz\cyrn\cyra\cyrch\cyre\cyrn\cyrn.}%
4222   {\cyrv\cyri\cyrz\cyrn\cyra\cyrch\cyre\cyrn\cyrn.}%
4223 \crefname@preamble{result}%
4224   {\cyrr\cyre\cyrz\cyru\cyrl\crysftsn\cyrt.}%
4225   {\cyrr\cyre\cyrz\cyru\cyrl\crysftsn\cyrt\cyra\cyrt.}%
4226 \crefname@preamble{example}%
4227   {\cyrp\cyrr\cyri\cyrk\cyrl.}%
4228   {\cyrp\cyrr\cyri\cyrk\cyrl\cyra\cyrd.}%
4229 \crefname@preamble{remark}%
4230   {\cyrp\cyrr\cyri\cyrm\cyrii\cyrt.}%
4231   {\cyrp\cyrr\cyri\cyrm\cyrii\cyrt.}%
4232 \crefname@preamble{note}%
4233   {\cyrz\cyra\cyrm\cyrii\cyrt.}%
4234   {\cyrz\cyra\cyrm\cyrii\cyrt.}%
4235 \fi%
4236 \def\cref@language{ukrainian}%

```

Next, we add the definitions to `\extras...` so that babel's `\selectlanguage` command will change the format appropriately.

```

4237 \cref@addto\extrasukrainian{%
4238   \renewcommand{\crefrangeconjunction}{--}%
4239   \renewcommand{\crefrangepreconjunction}{ }%
4240   \renewcommand{\crefrangepostconjunction}{ }%
4241   \renewcommand{\crefpairconjunction}{ \cyrii~}%
4242   \renewcommand{\crefmiddleconjunction}{, }%
4243   \renewcommand{\creflastconjunction}{ \cyrii~}%
4244   \renewcommand{\crefpairgroupconjunction}{ \cyrt\cyra~}%
4245   \renewcommand{\crefmiddlegroupconjunction}{, }%
4246   \renewcommand{\creflastgroupconjunction}{%
4247     {, \cyra\ \cyrt\cyra\cyrk\cyro\cyrzh~}%
4248   \Crefname{equation}%
4249     {\CYRF\cyro\cyrr\cyrm\cyru\cyrl\cyra}%
4250     {\CYRF\cyro\cyrr\cyrm\cyru\cyrl\cyri}%
4251   \Crefname{chapter}%
4252     {\CYRG\cyrl\cyra\cyrv\cyra}%
4253     {\CYRG\cyrl\cyra\cyrv\cyri}%
4254   \Crefname{section}%
4255     {\CYRR\cyro\cyrz\cyrd\cyrii\cyrl}%
4256     {\CYRR\cyro\cyrz\cyrd\cyrii\cyrl\cyri}%
4257   \Crefname{subsection}%
4258     {\CYRP\cyrii\cyrd\cyrr\cyro\cyrz\cyrd\cyrii\cyrl}%
4259     {\CYRP\cyrii\cyrd\cyrr\cyro\cyrz\cyrd\cyrii\cyrl\cyri}%
4260   \Crefname{subsubsection}%
4261     {\CYRP\cyrii\cyrd\cyrp\cyrii\cyrd\cyrr\cyro\cyrz\cyrd\cyrii\cyrl}%

```

```

4262   {\CYRP\cyrii\cyrd\cyrp\cyrii\cyrd\cyrr\cyro\cyrz\cyrd\cyrii\cyrl\cyri}%
4263 \Crefname{appendix}%
4264   {\CYRD\cyro\cyrd\cyra\cyrt\cyro\cyrk}%
4265   {\CYRD\cyro\cyrd\cyra\cyrt\cyrk\cyri}%
4266 \Crefname{subappendix}%
4267   {\CYRD\cyro\cyrd\cyra\cyrt\cyro\cyrk}%
4268   {\CYRD\cyro\cyrd\cyra\cyrt\cyrk\cyri}%
4269 \Crefname{subsubappendix}%
4270   {\CYRD\cyro\cyrd\cyra\cyrt\cyro\cyrk}%
4271   {\CYRD\cyro\cyrd\cyra\cyrt\cyrk\cyri}%
4272 \Crefname{subsubsubappendix}%
4273   {\CYRD\cyro\cyrd\cyra\cyrt\cyro\cyrk}%
4274   {\CYRD\cyro\cyrd\cyra\cyrt\cyrk\cyri}%
4275 \Crefname{enumi}%
4276   {\CYRP\cyru\cyrn\cyrk\cyrt}%
4277   {\CYRP\cyru\cyrn\cyrk\cyrt\cyri}%
4278 \Crefname{enumii}%
4279   {\CYRP\cyru\cyrn\cyrk\cyrt}%
4280   {\CYRP\cyru\cyrn\cyrk\cyrt\cyri}%
4281 \Crefname{enumiii}%
4282   {\CYRP\cyru\cyrn\cyrk\cyrt}%
4283   {\CYRP\cyru\cyrn\cyrk\cyrt\cyri}%
4284 \Crefname{enumiv}%
4285   {\CYRP\cyru\cyrn\cyrk\cyrt}%
4286   {\CYRP\cyru\cyrn\cyrk\cyrt\cyri}%
4287 \Crefname{enumv}%
4288   {\CYRP\cyru\cyrn\cyrk\cyrt}%
4289   {\CYRP\cyru\cyrn\cyrk\cyrt\cyri}%
4290 \Crefname{footnote}%
4291   {\CYRV\cyri\cyrn\cyro\cyrs\cyrk\cyra}%
4292   {\CYRV\cyri\cyrn\cyro\cyrs\cyrk\cyri}%
4293 \Crefname{figure}%
4294   {\CYRR\cyri\cyrs\cyru\cyrn\cyro\cyrk}%
4295   {\CYRR\cyri\cyrs\cyru\cyrn\cyrk\cyri}%
4296 \Crefname{subfigure}%
4297   {\CYRR\cyri\cyrs\cyru\cyrn\cyro\cyrk}%
4298   {\CYRR\cyri\cyrs\cyru\cyrn\cyrk\cyri}%
4299 \Crefname{table}%
4300   {\CYRT\cyra\cyrb\cyrl\cyri\cyrc\cyrya}%
4301   {\CYRT\cyra\cyrb\cyrl\cyri\cyrc\cyrii}%
4302 \Crefname{subtable}%
4303   {\CYRT\cyra\cyrb\cyrl\cyri\cyrc\cyrya}%
4304   {\CYRT\cyra\cyrb\cyrl\cyri\cyrc\cyrii}%
4305 \Crefname{theorem}%
4306   {\CYRT\cyre\cyro\cyrr\cyre\cyrm\cyra}%
4307   {\CYRT\cyre\cyro\cyrr\cyre\cyrm\cyri}%
4308 \Crefname{lemma}%
4309   {\CYRL\cyre\cyrm\cyrm\cyra}%
4310   {\CYRL\cyre\cyrm\cyrm\cyri}%
4311 \Crefname{corollary}%

```

```

4312   {\CYRV\cyri\crys\cyrn\cyro\cyrv\cyro\cyrk}%
4313   {\CYRV\cyri\crys\cyrn\cyro\cyrv\cyrk\cyri}%
4314 \Crefname{proposition}%
4315   {\CYRT\cyrv\cyre\cyrr\cyrd\cyrzh\cyre\cyrn\cyrn\cyrya}%
4316   {\CYRT\cyrv\cyre\cyrr\cyrd\cyrzh\cyre\cyrn\cyrn\cyrya}%
4317 \Crefname{definition}%
4318   {\CYRV\cyri\cyrz\cyrn\cyra\cyrch\cyre\cyrn\cyrn\cyrya}%
4319   {\CYRV\cyri\cyrz\cyrn\cyra\cyrch\cyre\cyrn\cyrn\cyrya}%
4320 \Crefname{result}%
4321   {\CYRR\cyre\cyrz\cyru\cyrl\crysftsn\cyrt\cyra\cyrt}%
4322   {\CYRR\cyre\cyrz\cyru\cyrl\crysftsn\cyrt\cyra\cyrt\cyri}%
4323 \Crefname{example}%
4324   {\CYRP\cyrr\cyri\cyrk\cyrl\cyra\cyrd}%
4325   {\CYRP\cyrr\cyri\cyrk\cyrl\cyra\cyrd\cyri}%
4326 \Crefname{remark}%
4327   {\CYRP\cyrr\cyri\cyrm\cyrii\cyrt\cyrk\cyra}%
4328   {\CYRP\cyrr\cyri\cyrm\cyrii\cyrt\cyrk\cyri}%
4329 \Crefname{note}%
4330   {\CYRZ\cyra\cyrm\cyrii\cyrt\cyrk\cyra}%
4331   {\CYRZ\cyra\cyrm\cyrii\cyrt\cyrk\cyri}%
4332 \if@cref@capitalise%
4333   \crefname{equation}{\CYRF-\cyrl.}{\CYRF-\cyrl.}%
4334   \crefname{chapter}%
4335   {\CYRG\cyrl\cyra\cyrv\cyra}%
4336   {\CYRG\cyrl\cyra\cyrv\cyri}%
4337 \crefname{section}%
4338   {\CYRR\cyro\cyrz\cyrd\cyrii\cyrl}%
4339   {\CYRR\cyro\cyrz\cyrd\cyrii\cyrl\cyri}%
4340 \crefname{subsection}%
4341   {\CYRP\cyrii\cyrd\cyrr\cyro\cyrz\cyrd\cyrii\cyrl}%
4342   {\CYRP\cyrii\cyrd\cyrr\cyro\cyrz\cyrd\cyrii\cyrl\cyri}%
4343 \crefname{subsubsection}%
4344   {\CYRP\cyrii\cyrd\cyrp\cyrii\cyrd\cyrr\cyro\cyrz\cyrd\cyrii\cyrl}\blacksquare
4345   {\CYRP\cyrii\cyrd\cyrp\cyrii\cyrd\cyrr\cyro\cyrz\cyrd\cyrii\cyrl\cyri}\blacksquare
4346 \crefname{appendix}%
4347   {\CYRD\cyro\cyrd\cyra\cyrt\cyro\cyrk}%
4348   {\CYRD\cyro\cyrd\cyra\cyrt\cyrk\cyri}%
4349 \crefname{subappendix}%
4350   {\CYRD\cyro\cyrd\cyra\cyrt\cyro\cyrk}%
4351   {\CYRD\cyro\cyrd\cyra\cyrt\cyrk\cyri}%
4352 \crefname{subsubappendix}%
4353   {\CYRD\cyro\cyrd\cyra\cyrt\cyro\cyrk}%
4354   {\CYRD\cyro\cyrd\cyra\cyrt\cyrk\cyri}%
4355 \crefname{subsubsubappendix}%
4356   {\CYRD\cyro\cyrd\cyra\cyrt\cyro\cyrk}%
4357   {\CYRD\cyro\cyrd\cyra\cyrt\cyrk\cyri}%
4358 \crefname{enumi}{\CYRP.}{\CYRP.\cyrp.}%
4359 \crefname{enumii}{\CYRP.}{\CYRP.\cyrp.}%
4360 \crefname{enumiii}{\CYRP.}{\CYRP.\cyrp.}%
4361 \crefname{enumiv}{\CYRP.}{\CYRP.\cyrp.}%

```

```

4362 \crefname{enumv}{\CYRP.}{\CYRP.\cyrp.}%
4363 \crefname{footnote}%
4364 {\CYRV\cyri\cyrn\cyro\crys\cyrk\cyra}%
4365 {\CYRV\cyri\cyrn\cyro\crys\cyrk\cyri}%
4366 \crefname{figure}%
4367 {\CYRR\cyri\crys.}%
4368 {\CYRR\cyri\crys.}%
4369 \crefname{subfigure}%
4370 {\CYRR\cyri\crys.}%
4371 {\CYRR\cyri\crys.}%
4372 \crefname{table}%
4373 {\CYRT\cyra\cyrb\cyrl.}%
4374 {\CYRT\cyra\cyrb\cyrl.}%
4375 \crefname{subtable}%
4376 {\CYRT\cyra\cyrb\cyrl.}%
4377 {\CYRT\cyra\cyrb\cyrl.}%
4378 \crefname{theorem}%
4379 {\CYRT\cyre\cyro\cyrr\cyre\cyrm\cyra}%
4380 {\CYRT\cyre\cyro\cyrr\cyre\cyrm\cyri}%
4381 \crefname{lemma}%
4382 {\CYRL\cyre\cyrm\cyrn\cyra}%
4383 {\CYRL\cyre\cyrm\cyrn\cyri}%
4384 \crefname{corollary}%
4385 {\CYRV\cyri\crys\cyrn\cyro\cyrv\cyro\cyrk}%
4386 {\CYRV\cyri\crys\cyrn\cyro\cyrv\cyrk\cyri}%
4387 \crefname{proposition}%
4388 {\CYRT\cyrv\cyre\cyrr\cyrd\cyrzh\cyre\cyrn\cyrn\cyrya}%
4389 {\CYRT\cyrv\cyre\cyrr\cyrd\cyrzh\cyre\cyrn\cyrn\cyrya}%
4390 \crefname{definition}%
4391 {\CYRV\cyri\cyrz\cyrn\cyra\cyrch\cyre\cyrn\cyrn\cyrya}%
4392 {\CYRV\cyri\cyrz\cyrn\cyra\cyrch\cyre\cyrn\cyrn\cyrya}%
4393 \crefname{result}%
4394 {\CYRR\cyre\cyrz\cyru\cyrl\crysftsn\cyrt\cyra\cyrt}%
4395 {\CYRR\cyre\cyrz\cyru\cyrl\crysftsn\cyrt\cyra\cyrt\cyri}%
4396 \crefname{example}%
4397 {\CYRP\cyrr\cyri\cyrk\cyrl\cyra\cyrd}%
4398 {\CYRP\cyrr\cyri\cyrk\cyrl\cyra\cyrd\cyri}%
4399 \crefname{remark}%
4400 {\CYRP\cyrr\cyri\cyrm\cyri\cyrt\cyrk\cyra}%
4401 {\CYRP\cyrr\cyri\cyrm\cyri\cyrt\cyrk\cyri}%
4402 \crefname{note}%
4403 {\CYRZ\cyra\cyrm\cyrii\cyrt\cyrk\cyra}%
4404 {\CYRZ\cyra\cyrm\cyrii\cyrt\cyrk\cyri}%
4405 \else%
4406 \crefname{equation}{\cyrf-\cyrl.}{\cyrf-\cyrl.}%
4407 \crefname{chapter}%
4408 {\cyrg\cyrl\cyra\cyrv.}%
4409 {\cyrg\cyrl\cyra\cyrv.}%
4410 \crefname{section}%
4411 {\cyrr\cyro\cyrz\cyrd.}%

```

```

4412   {\cyrr\cyro\cyrz\cyrd\cyrii\cyrl.}%
4413 \crefname{subsection}%
4414   {\cyrp\cyrii\cyrd\cyrr\cyro\cyrz\cyrd.}%
4415   {\cyrp\cyrii\cyrd\cyrr\cyro\cyrz\cyrd\cyrii\cyrl.}%
4416 \crefname{subsubsection}%
4417   {\cyrp\cyrii\cyrd\cyrp\cyrii\cyrd\cyrr\cyro\cyrz\cyrd.}%
4418   {\cyrp\cyrii\cyrd\cyrp\cyrii\cyrd\cyrr\cyro\cyrz\cyrd\cyrii\cyrl.}%
4419 \crefname{appendix}%
4420   {\cyrd\cyro\cyrd\cyra\cyrt.}%
4421   {\cyrd\cyro\cyrd\cyra\cyrt\cyrk.}%
4422 \crefname{subappendix}%
4423   {\cyrd\cyro\cyrd\cyra\cyrt.}%
4424   {\cyrd\cyro\cyrd\cyra\cyrt\cyrk.}%
4425 \crefname{subsubappendix}%
4426   {\cyrd\cyro\cyrd\cyra\cyrt.}%
4427   {\cyrd\cyro\cyrd\cyra\cyrt\cyrk.}%
4428 \crefname{subsubsubappendix}%
4429   {\cyrd\cyro\cyrd\cyra\cyrt.}%
4430   {\cyrd\cyro\cyrd\cyra\cyrt\cyrk.}%
4431 \crefname{enumi}{\cyrp.}{\cyrp.\cyrp.}%
4432 \crefname{enumii}{\cyrp.}{\cyrp.\cyrp.}%
4433 \crefname{enumiii}{\cyrp.}{\cyrp.\cyrp.}%
4434 \crefname{enumiv}{\cyrp.}{\cyrp.\cyrp.}%
4435 \crefname{enumv}{\cyrp.}{\cyrp.\cyrp.}%
4436 \crefname{footnote}%
4437   {\cyrv\cyri\cyrn\cyro\crys\cyrk.}%
4438   {\cyrv\cyri\cyrn\cyro\crys\cyrk.}%
4439 \crefname{figure}%
4440   {\cyrr\cyri\crys.}%
4441   {\cyrr\cyri\crys.}%
4442 \crefname{subfigure}%
4443   {\cyrr\cyri\crys.}%
4444   {\cyrr\cyri\crys.}%
4445 \crefname{table}%
4446   {\cyrt\cyra\cyrb\cyrl.}%
4447   {\cyrt\cyra\cyrb\cyrl.}%
4448 \crefname{subtable}%
4449   {\cyrt\cyra\cyrb\cyrl.}%
4450   {\cyrt\cyra\cyrb\cyrl.}%
4451 \crefname{theorem}%
4452   {\cyrt\cyre\cyro\cyrr\cyre\cyrm.}%
4453   {\cyrt\cyre\cyro\cyrr\cyre\cyrm.}%
4454 \crefname{lemma}{\cyrl\cyre\cyrm\cyrm.}{\cyrl\cyre\cyrm\cyrm.}%
4455 \crefname{corollary}%
4456   {\cyrv\cyri\crys\cyrn\cyro\cyrv.}%
4457   {\cyrv\cyri\crys\cyrn\cyro\cyrv\cyrk.}%
4458 \crefname{proposition}%
4459   {\cyrt\cyrv\cyre\cyrr\cyrd\cyrz\cyre\cyrn\cyrn.}%
4460   {\cyrt\cyrv\cyre\cyrr\cyrd\cyrz\cyre\cyrn\cyrn.}%
4461 \crefname{definition}%

```

```

4462      {\cyrv\cyri\cyrz\cyrn\cyra\cyrch\cyre\cyrn\cyrn.}%
4463      {\cyrv\cyri\cyrz\cyrn\cyra\cyrch\cyre\cyrn\cyrn.}%
4464 \crefname{result}%
4465      {\cyrr\cyre\cyrz\cyr\cyr\cyr\cyr\cyr\cyr.}%
4466      {\cyrr\cyre\cyrz\cyr\cyr\cyr\cyr\cyr\cyr.}%
4467 \crefname{example}%
4468      {\cyrp\cyrr\cyri\cyrk\cyr\cyr.}%
4469      {\cyrp\cyrr\cyri\cyrk\cyr\cyr\cyr\cyr.}%
4470 \crefname{remark}%
4471      {\cyrp\cyrr\cyri\cyr\cyr\cyr\cyr.}%
4472      {\cyrp\cyrr\cyri\cyr\cyr\cyr\cyr.}%
4473 \crefname{note}%
4474      {\cyrz\cyr\cyr\cyr\cyr\cyr.}%
4475      {\cyrz\cyr\cyr\cyr\cyr\cyr.}%
4476 \fi%
4477 }}}

```

12.13.1 Default Cross-Reference Formats

Setup the default format definitions, then process options in the order they were supplied. However, the `capitalise` option must be processed before the language options, so that it takes effect in the default format definitions. Therefore, we have to manually check whether it's present, and force processing of it before the other options.

```

4478 \edef\@curroptions{\@optionlist{\@currname.\@currext}%
4479 \@expandtwoargs\in@{,capitalise,}{%
4480 ,\@classoptionslist,\@curroptions,}%
4481 \ifin@%
4482 \ExecuteOptions{capitalise}%
4483 \else%
4484 \@expandtwoargs\in@{,capitalize,}{%
4485 ,\@classoptionslist,\@curroptions,}%
4486 \ifin@%
4487 \ExecuteOptions{capitalise}%
4488 \fi%
4489 \fi%
4490 \ExecuteOptions{english}%
4491 \ProcessOptions*\relax

```

Define the component-derived formats.

```
4492 \AtBeginDocument{%
```

Use whatever's in the ...`@preamble` definitions at the beginning of the document to set up the default cross-reference names, unless overridden by explicit definitions.

```

4493 \edef\@tmpa{%
4494 \expandafter\noexpand\csname extras\cref@language\endcsname}%
4495 \ifundefined{crefrangeconjunction}{}{%
4496 \let\crefrangeconjunction\crefrangeconjunction@preamble}%
4497 }%

```

```

4498 \expandafter\def\expandafter\@tmpb\expandafter{%
4499   \expandafter\renewcommand\expandafter{%
4500     {\expandafter\crefrangeconjunction\expandafter}{%
4501       \expandafter{\crefrangeconjunction}}{%
4502         \expandafter\expandafter\expandafter\expandafter\cref@addto{%
4503           \expandafter\@tmpa\expandafter{\@tmpb}}{%
4504         }{%
4505       }{%
4506       \let\crefrangepreconjunction\crefrangepreconjunction@preamble{%
4507     }{%
4508       \expandafter\def\expandafter\@tmpb\expandafter{%
4509         \expandafter\renewcommand\expandafter{%
4510           {\expandafter\crefrangepreconjunction\expandafter}{%
4511             \expandafter{\crefrangepreconjunction}}{%
4512               \expandafter\expandafter\expandafter\expandafter\cref@addto{%
4513                 \expandafter\@tmpa\expandafter{\@tmpb}}{%
4514               }{%
4515             }{%
4516             \let\crefrangepostconjunction\crefrangepostconjunction@preamble{%
4517           }{%
4518             \expandafter\def\expandafter\@tmpb\expandafter{%
4519               \expandafter\renewcommand\expandafter{%
4520                 {\expandafter\crefrangepostconjunction\expandafter}{%
4521                   \expandafter{\crefrangepostconjunction}}{%
4522                     \expandafter\expandafter\expandafter\expandafter\cref@addto{%
4523                       \expandafter\@tmpa\expandafter{\@tmpb}}{%
4524                     }{%
4525       }{%

```

If the group conjunctions haven't been defined, but explicit definitions *have* been given for the reference list conjunctions, define the group conjunctions to be identical to the reference conjunctions.

```

4525 \@ifundefined{crefpairconjunction}{%
4526   \let\crefpairconjunction\crefpairconjunction@preamble{%
4527 }{%
4528   \expandafter\def\expandafter\@tmpb\expandafter{%
4529     \expandafter\renewcommand\expandafter{%
4530       {\expandafter\crefpairconjunction\expandafter}{%
4531         \expandafter{\crefpairconjunction}}{%
4532           \expandafter\expandafter\expandafter\expandafter\cref@addto{%
4533             \expandafter\@tmpa\expandafter{\@tmpb}}{%
4534             \ifundefined{crefpairgroupconjunction}{%
4535               \let\crefpairgroupconjunction\crefpairconjunction{}{%
4536             }{%
4537             \ifundefined{crefmiddleconjunction}{%
4538               \let\crefmiddleconjunction\crefmiddleconjunction@preamble{%
4539             }{%
4540               \expandafter\def\expandafter\@tmpb\expandafter{%
4541                 \expandafter\renewcommand\expandafter{%
4542                   {\expandafter\crefmiddleconjunction\expandafter}{%
4543                     \expandafter{\crefmiddleconjunction}}{%

```

```

4544     \expandafter\expandafter\expandafter\cref@addto%
4545     \expandafter\@tmpa\expandafter{\@tmpb}%
4546     \@ifundefined{crefmiddlegroupconjunction}{%
4547         \let\crefmiddlegroupconjunction\crefmiddleconjunction{}%
4548     }%
4549     \@ifundefined{creflastconjunction}{%
4550         \let\creflastconjunction\creflastconjunction@preamble%
4551     }%
4552     \expandafter\def\expandafter\@tmpb\expandafter{%
4553         \expandafter\renewcommand\expandafter%
4554         {\expandafter\creflastconjunction\expandafter}%
4555         \expandafter{\creflastconjunction}%
4556     \expandafter\expandafter\expandafter\cref@addto%
4557         \expandafter\@tmpa\expandafter{\@tmpb}%

```

Define the last group conjunction to include an extra comma.

```

4558     \@ifundefined{creflastgroupconjunction}{%
4559         \edef\creflastgroupconjunction{, \creflastconjunction}{}%
4560     }%
4561     \@ifundefined{crefpairgroupconjunction}{%
4562         \let\crefpairgroupconjunction%
4563         \crefpairgroupconjunction@preamble%
4564     }%
4565     \expandafter\def\expandafter\@tmpb\expandafter{%
4566         \expandafter\renewcommand\expandafter%
4567         {\expandafter\crefpairgroupconjunction\expandafter}%
4568         \expandafter{\crefpairgroupconjunction}%
4569     \expandafter\expandafter\expandafter\cref@addto%
4570         \expandafter\@tmpa\expandafter{\@tmpb}%
4571     }%
4572     \@ifundefined{crefmiddlegroupconjunction}{%
4573         \let\crefmiddlegroupconjunction%
4574         \crefmiddlegroupconjunction@preamble%
4575     }%
4576     \expandafter\def\expandafter\@tmpb\expandafter{%
4577         \expandafter\renewcommand\expandafter%
4578         {\expandafter\crefmiddlegroupconjunction\expandafter}%
4579         \expandafter{\crefmiddlegroupconjunction}%
4580     \expandafter\expandafter\expandafter\cref@addto%
4581         \expandafter\@tmpa\expandafter{\@tmpb}%
4582     }%
4583     \@ifundefined{creflastgroupconjunction}{%
4584         \let\creflastgroupconjunction%
4585         \creflastgroupconjunction@preamble%
4586     }%
4587     \expandafter\def\expandafter\@tmpb\expandafter{%
4588         \expandafter\renewcommand\expandafter%
4589         {\expandafter\creflastgroupconjunction\expandafter}%
4590         \expandafter{\creflastgroupconjunction}%
4591     \expandafter\expandafter\expandafter\cref@addto%

```

```

4592     \expandafter\@tmpa\expandafter{\@tmpb}%
4593 }%
Define any undefined formats listed in \cref@label@types using the components.
4594 \let\@tmpstack\cref@label@types%
4595 \cref@isstackfull{\@tmpstack}%
4596 \@whilesw\if@cref@stackfull\fi{%
4597   \edef\@tmpa{\cref@stack@top{\@tmpstack}}%
4598   \c@ifundefined{\cref@\@tmpa @name}{%
4599     \expandafter\def\expandafter\@tmpb\expandafter{%
4600       \csname cref@\@tmpa @name\endcsname}%
4601     \expandafter\def\expandafter\@tmpc\expandafter{%
4602       \csname cref@\@tmpa @name@preamble\endcsname}%
4603     \expandafter\expandafter\expandafter\let\expandafter\@tmpb\@tmpc%
4604     \expandafter\def\expandafter\@tmpb\expandafter{%
4605       \csname cref@\@tmpa @name@plural\endcsname}%
4606     \expandafter\def\expandafter\@tmpc\expandafter{%
4607       \csname cref@\@tmpa @name@plural@preamble\endcsname}%
4608     \expandafter\expandafter\expandafter\let\expandafter\@tmpb\@tmpc%
4609   }{%
4610     \edef\@tmpb{%
4611       \expandafter\noexpand\csname extras\cref@language\endcsname}%
4612     \expandafter\def\expandafter\@tmpc\expandafter{%
4613       \expandafter\crefname\expandafter{\@tmpa}}%
4614     \expandafter\expandafter\expandafter\cref@addto%
4615     \expandafter\expandafter\expandafter\@tmpc%
4616     \expandafter\expandafter\expandafter{%
4617       \expandafter\expandafter\expandafter{%
4618         \csname cref@\@tmpa @name\endcsname}}%
4619     \expandafter\expandafter\expandafter\cref@addto%
4620     \expandafter\expandafter\expandafter\@tmpc%
4621     \expandafter\expandafter\expandafter{%
4622       \expandafter\expandafter\expandafter{%
4623         \csname cref@\@tmpa @name@plural\endcsname}}%
4624     \expandafter\expandafter\expandafter\cref@addto%
4625     \expandafter\expandafter\expandafter{\@tmpc}%
4626   }%
4627   \c@ifundefined{\Cref@\@tmpa @name}{%
4628     \expandafter\def\expandafter\@tmpb\expandafter{%
4629       \csname Cref@\@tmpa @name\endcsname}%
4630     \expandafter\def\expandafter\@tmpc\expandafter{%
4631       \csname Cref@\@tmpa @name@preamble\endcsname}%
4632     \expandafter\expandafter\expandafter\let\expandafter\@tmpb\@tmpc%
4633     \expandafter\def\expandafter\@tmpb\expandafter{%
4634       \csname Cref@\@tmpa @name@plural\endcsname}%
4635     \expandafter\def\expandafter\@tmpc\expandafter{%
4636       \csname Cref@\@tmpa @name@plural@preamble\endcsname}%
4637     \expandafter\expandafter\expandafter\let\expandafter\@tmpb\@tmpc%
4638   }%

```

```

4639 \edef\@tmpb{%
4640   \expandafter\noexpand\csname extras\cref@language\endcsname}%
4641   \expandafter\def\expandafter\@tmpc\expandafter{%
4642     \expandafter\Crefname\expandafter{\@tmpa}}%
4643   \expandafter\expandafter\expandafter\cref@addto{%
4644     \expandafter\expandafter\expandafter\@tmpc}%
4645   \expandafter\expandafter\expandafter{%
4646     \expandafter\expandafter\expandafter\expandafter{%
4647       \csname Cref@\@tmpa @name\endcsname}%
4648     \expandafter\expandafter\expandafter\cref@addto{%
4649       \expandafter\expandafter\expandafter\expandafter\@tmpc}%
4650     \expandafter\expandafter\expandafter{%
4651       \expandafter\expandafter\expandafter\expandafter{%
4652         \csname Cref@\@tmpa @name@plural\endcsname}%
4653       \expandafter\expandafter\expandafter\cref@addto{%
4654         \expandafter\@tmpb\expandafter{\@tmpc}}%
4655   }%

```

We only define the reference-range and multi-reference formats if the plural form of the name is defined in the corresponding `\cref<type>@name@plural`. Though `\crefname` and `\Crefname` always define both the singular and plural forms together, cross-reference names can also be defined automatically by `\newtheorem`, which can only define the singular form. In this case, the singular form might be defined whilst the plural form is undefined. For symmetry, we apply the same logic to the normal cross-reference format definition (only defining it if `\cref<type>@name` is defined), though currently this should always be the case.

```

4656 \@ifundefined{cref@\@tmpa @format}{%
4657   \@ifundefined{cref@\@tmpa @name}{}{%
4658     \expandafter\@crefdefinformat\expandafter{\@tmpa}}}{%
4659   \@ifundefined{crefrange@\@tmpa @format}{}{%
4660     \@ifundefined{cref@\@tmpa @name@plural}{}{%
4661       \expandafter\@crefrangedefineformat\expandafter{\@tmpa}}}{%
4662   \@ifundefined{cref@\@tmpa @format@first}{}{%
4663     \@ifundefined{cref@\@tmpa @name@plural}{}{%
4664       \expandafter\@crefdefinemultiformat\expandafter{\@tmpa}}}{%
4665   \@ifundefined{crefrange@\@tmpa @format@first}{}{%
4666     \@ifundefined{cref@\@tmpa @name@plural}{}{%
4667       \expandafter\@crefrangedefinemultiformat\expandafter{\@tmpa}}}{%
4668   \cref@stack@pop{\@tmpstack}}%
4669   \cref@isstackfull{\@tmpstack}}%

```

If formats for subsections are undefined, define them to be identical to the formats for sections.

```

4670 \@ifundefined{cref@subsection@name}{}{%
4671   \let\cref@subsection@name\cref@section@name%
4672   \let\cref@subsection@name@plural\cref@section@name@plural}{%
4673   \@ifundefined{Cref@subsection@name}{}{%
4674     \let\Cref@subsection@name\Cref@section@name%
4675     \let\Cref@subsection@name@plural\Cref@section@name@plural}{%
4676   \@ifundefined{cref@subsection@format}{}{%

```

```

4677      \let\cref@subsection@format\cref@section@format}{}%
4678  \@ifundefined{Cref@subsection@format}{%
4679    \let\cref@subsection@format\Cref@section@format}{}%
4680  \@ifundefined{crefrange@subsection@format}{%
4681    \let\crefrange@subsection@format%
4682    \crefrange@section@format}{}%
4683  \@ifundefined{Crefrange@subsection@format}{%
4684    \let\Crefrange@subsection@format%
4685    \Crefrange@section@format}{}%
4686  \@ifundefined{cref@subsection@format@first}{%
4687    \let\cref@subsection@format@first%
4688    \cref@section@format@first}{}%
4689  \@ifundefined{Cref@subsection@format@first}{%
4690    \let\cref@subsection@format@first%
4691    \Cref@section@format@first}{}%
4692  \@ifundefined{cref@subsection@format@second}{%
4693    \let\cref@subsection@format@second%
4694    \cref@section@format@second}{}%
4695  \@ifundefined{Cref@subsection@format@second}{%
4696    \let\cref@subsection@format@second%
4697    \Cref@section@format@second}{}%
4698  \@ifundefined{cref@subsection@format@middle}{%
4699    \let\cref@subsection@format@middle%
4700    \cref@section@format@middle}{}%
4701  \@ifundefined{Cref@subsection@format@middle}{%
4702    \let\cref@subsection@format@middle%
4703    \Cref@section@format@middle}{}%
4704  \@ifundefined{cref@subsection@format@last}{%
4705    \let\cref@subsection@format@last%
4706    \cref@section@format@last}{}%
4707  \@ifundefined{Cref@subsection@format@last}{%
4708    \let\cref@subsection@format@last%
4709    \Cref@section@format@last}{}%
4710  \@ifundefined{crefrange@subsection@format@first}{%
4711    \let\crefrange@subsection@format@first%
4712    \crefrange@section@format@first}{}%
4713  \@ifundefined{Crefrange@subsection@format@first}{%
4714    \let\Crefrange@subsection@format@first%
4715    \Crefrange@section@format@first}{}%
4716  \@ifundefined{crefrange@subsection@format@second}{%
4717    \let\crefrange@subsection@format@second%
4718    \crefrange@section@format@second}{}%
4719  \@ifundefined{Crefrange@subsection@format@second}{%
4720    \let\Crefrange@subsection@format@second%
4721    \Crefrange@section@format@second}{}%
4722  \@ifundefined{crefrange@subsection@format@middle}{%
4723    \let\crefrange@subsection@format@middle%
4724    \crefrange@section@format@middle}{}%
4725  \@ifundefined{Crefrange@subsection@format@middle}{%
4726    \let\Crefrange@subsection@format@middle%

```

```

4727     \Crefrange@section@format@middle}{}%
4728     \@ifundefined{crefrange@subsection@format@last}{%
4729         \let\crefrange@subsection@format@last%
4730             \crefrange@section@format@last}{}%
4731     \@ifundefined{Crefrange@subsection@format@last}{%
4732         \let\Crefrange@subsection@format@last%
4733             \Crefrange@section@format@last}{}%
4734 %
4735     \@ifundefined{cref@subsubsection@name}{%
4736         \let\cref@subsubsection@name\cref@section@name%
4737         \let\cref@subsubsection@name@plural\cref@section@name@plural}{}%
4738     \@ifundefined{Cref@subsection@name}{%
4739         \let\Cref@subsection@name\Cref@section@name%
4740         \let\cref@subsection@name@plural\Cref@section@name@plural}{}%
4741     \@ifundefined{cref@subsubsection@format}{%
4742         \let\cref@subsubsection@format%
4743             \cref@subsection@format}{}%
4744     \@ifundefined{Cref@subsubsection@format}{%
4745         \let\Cref@subsubsection@format%
4746             \Cref@subsection@format}{}%
4747     \@ifundefined{crefrange@subsubsection@format}{%
4748         \let\crefrange@subsubsection@format%
4749             \crefrange@subsection@format}{}%
4750     \@ifundefined{Crefrange@subsubsection@format}{%
4751         \let\Crefrange@subsubsection@format%
4752             \Crefrange@subsection@format}{}%
4753     \@ifundefined{cref@subsubsection@format@first}{%
4754         \let\cref@subsubsection@format@first%
4755             \cref@subsection@format@first}{}%
4756     \@ifundefined{Cref@subsubsection@format@first}{%
4757         \let\Cref@subsubsection@format@first%
4758             \Cref@subsection@format@first}{}%
4759     \@ifundefined{cref@subsubsection@format@second}{%
4760         \let\cref@subsubsection@format@second%
4761             \cref@subsection@format@second}{}%
4762     \@ifundefined{Cref@subsubsection@format@second}{%
4763         \let\Cref@subsubsection@format@second%
4764             \Cref@subsection@format@second}{}%
4765     \@ifundefined{cref@subsubsection@format@middle}{%
4766         \let\cref@subsubsection@format@middle%
4767             \cref@subsection@format@middle}{}%
4768     \@ifundefined{Cref@subsubsection@format@middle}{%
4769         \let\Cref@subsubsection@format@middle%
4770             \Cref@subsection@format@middle}{}%
4771     \@ifundefined{cref@subsubsection@format@last}{%
4772         \let\cref@subsubsection@format@last%
4773             \cref@subsection@format@last}{}%
4774     \@ifundefined{Cref@subsubsection@format@last}{%
4775         \let\Cref@subsubsection@format@last%
4776             \Cref@subsection@format@last}{}%

```

```

4777  \@ifundefined{crefrange@subsubsection@format@first}{%
4778    \let\crefrange@subsubsection@format@first%
4779    \crefrange@subsection@format@first}{}
4780  \@ifundefined{Crefrange@subsubsection@format@first}{%
4781    \let\Crefrange@subsubsection@format@first%
4782    \Crefrange@subsection@format@first}{}
4783  \@ifundefined{crefrange@subsubsection@format@second}{%
4784    \let\crefrange@subsubsection@format@second%
4785    \crefrange@subsection@format@second}{}
4786  \@ifundefined{Crefrange@subsubsection@format@second}{%
4787    \let\Crefrange@subsubsection@format@second%
4788    \Crefrange@subsection@format@second}{}
4789  \@ifundefined{crefrange@subsubsection@format@middle}{%
4790    \let\crefrange@subsubsection@format@middle%
4791    \crefrange@subsection@format@middle}{}
4792  \@ifundefined{Crefrange@subsubsection@format@middle}{%
4793    \let\Crefrange@subsubsection@format@middle%
4794    \Crefrange@subsection@format@middle}{}
4795  \@ifundefined{crefrange@subsubsection@format@last}{%
4796    \let\crefrange@subsubsection@format@last%
4797    \crefrange@subsection@format@last}{}
4798  \@ifundefined{Crefrange@subsubsection@format@last}{%
4799    \let\Crefrange@subsubsection@format@last%
5000    \Crefrange@subsection@format@last}{}

```

Similarly for subsections within appendices.

```

5001  \@ifundefined{cref@subappendix@name}{%
5002    \let\cref@subappendix@name\cref@appendix@name%
5003    \let\cref@subappendix@name@plural%
5004    \cref@appendix@name@plural}{}
5005  \@ifundefined{Cref@subappendix@name}{%
5006    \let\Cref@subappendix@name\Cref@section@name%
5007    \let\Cref@subappendix@name@plural%
5008    \Cref@appendix@name@plural}{}
5009  \@ifundefined{cref@subappendix@format}{%
5010    \let\cref@subappendix@format\cref@appendix@format}{}
5011  \@ifundefined{Cref@subappendix@format}{%
5012    \let\Cref@subappendix@format\Cref@appendix@format}{}
5013  \@ifundefined{crefrange@subappendix@format}{%
5014    \let\crefrange@subappendix@format%
5015    \crefrange@appendix@format}{}
5016  \@ifundefined{Crefrange@subappendix@format}{%
5017    \let\Crefrange@subappendix@format%
5018    \Crefrange@appendix@format}{}
5019  \@ifundefined{cref@subappendix@format@first}{%
5020    \let\cref@subappendix@format@first%
5021    \cref@appendix@format@first}{}
5022  \@ifundefined{Cref@subappendix@format@first}{%
5023    \let\Cref@subappendix@format@first%
5024    \Cref@appendix@format@first}{}

```

```

4825  \@ifundefined{cref@subappendix@format@second}{%
4826    \let\cref@subappendix@format@second%
4827    \cref@appendix@format@second}{}}%
4828  \@ifundefined{Cref@subappendix@format@second}{%
4829    \let\cRef@subappendix@format@second%
4830    \Cref@appendix@format@second}{}}%
4831  \@ifundefined{cref@subappendix@format@middle}{%
4832    \let\cref@subappendix@format@middle%
4833    \cref@appendix@format@middle}{}}%
4834  \@ifundefined{Cref@subappendix@format@middle}{%
4835    \let\cRef@subappendix@format@middle%
4836    \Cref@appendix@format@middle}{}}%
4837  \@ifundefined{cref@subappendix@format@last}{%
4838    \let\cref@subappendix@format@last%
4839    \cref@appendix@format@last}{}}%
4840  \@ifundefined{Cref@subappendix@format@last}{%
4841    \let\cRef@subappendix@format@last%
4842    \Cref@appendix@format@last}{}}%
4843  \@ifundefined{crefrange@subappendix@format@first}{%
4844    \let\crefrange@subappendix@format@first%
4845    \crefrange@appendix@format@first}{}}%
4846  \@ifundefined{Crefrange@subappendix@format@first}{%
4847    \let\cRefrange@subappendix@format@first%
4848    \Crefrange@appendix@format@first}{}}%
4849  \@ifundefined{crefrange@subappendix@format@second}{%
4850    \let\crefrange@subappendix@format@second%
4851    \crefrange@appendix@format@second}{}}%
4852  \@ifundefined{Crefrange@subappendix@format@second}{%
4853    \let\cRefrange@subappendix@format@second%
4854    \Crefrange@appendix@format@second}{}}%
4855  \@ifundefined{crefrange@subappendix@format@middle}{%
4856    \let\crefrange@subappendix@format@middle%
4857    \crefrange@appendix@format@middle}{}}%
4858  \@ifundefined{Crefrange@subappendix@format@middle}{%
4859    \let\cRefrange@subappendix@format@middle%
4860    \Crefrange@appendix@format@middle}{}}%
4861  \@ifundefined{crefrange@subappendix@format@last}{%
4862    \let\crefrange@subappendix@format@last%
4863    \crefrange@appendix@format@last}{}}%
4864  \@ifundefined{Crefrange@subappendix@format@last}{%
4865    \let\cRefrange@subappendix@format@last%
4866    \Crefrange@appendix@format@last}{}}%
4867 %
4868  \@ifundefined{cref@subsubappendix@name}{%
4869    \let\cref@subsubappendix@name\cref@appendix@name%
4870    \let\cref@subsubappendix@name@plural%
4871    \cref@appendix@name@plural}{}}%
4872  \@ifundefined{Cref@subsubappendix@name}{%
4873    \let\cRef@subsubappendix@name\cRef@section@name%
4874    \let\cRef@subsubappendix@name@plural%
```

```

4875      \Cref@appendix@name@plural}{}%
4876  \@ifundefined{cref@subsubappendix@format}{%
4877      \let\cref@subsubappendix@format%
4878      \cref@subappendix@format}{}%
4879  \@ifundefined{Cref@subsubappendix@format}{%
4880      \let\Cref@subsubappendix@format%
4881      \Cref@subappendix@format}{}%
4882  \@ifundefined{crefrange@subsubappendix@format}{%
4883      \let\crefrange@subsubappendix@format%
4884      \crefrange@subappendix@format}{}%
4885  \@ifundefined{Crefrange@subsubappendix@format}{%
4886      \let\Crefrange@subsubappendix@format%
4887      \Crefrange@subappendix@format}{}%
4888  \@ifundefined{cref@subsubappendix@format@first}{%
4889      \let\cref@subsubappendix@format@first%
4890      \cref@subappendix@format@first}{}%
4891  \@ifundefined{Cref@subsubappendix@format@first}{%
4892      \let\Cref@subsubappendix@format@first%
4893      \Cref@subappendix@format@first}{}%
4894  \@ifundefined{cref@subsubappendix@format@second}{%
4895      \let\cref@subsubappendix@format@second%
4896      \cref@subappendix@format@second}{}%
4897  \@ifundefined{Cref@subsubappendix@format@second}{%
4898      \let\Cref@subsubappendix@format@second%
4899      \Cref@subappendix@format@second}{}%
4900  \@ifundefined{cref@subsubappendix@format@middle}{%
4901      \let\cref@subsubappendix@format@middle%
4902      \cref@subappendix@format@middle}{}%
4903  \@ifundefined{Cref@subsubappendix@format@middle}{%
4904      \let\Cref@subsubappendix@format@middle%
4905      \Cref@subappendix@format@middle}{}%
4906  \@ifundefined{cref@subsubappendix@format@last}{%
4907      \let\cref@subsubappendix@format@last%
4908      \cref@subappendix@format@last}{}%
4909  \@ifundefined{Cref@subsubappendix@format@last}{%
4910      \let\Cref@subsubappendix@format@last%
4911      \Cref@subappendix@format@last}{}%
4912  \@ifundefined{crefrange@subsubappendix@format@first}{%
4913      \let\crefrange@subsubappendix@format@first%
4914      \crefrange@subappendix@format@first}{}%
4915  \@ifundefined{Crefrange@subsubappendix@format@first}{%
4916      \let\Crefrange@subsubappendix@format@first%
4917      \Crefrange@subappendix@format@first}{}%
4918  \@ifundefined{crefrange@subsubappendix@format@second}{%
4919      \let\crefrange@subsubappendix@format@second%
4920      \crefrange@subappendix@format@second}{}%
4921  \@ifundefined{Crefrange@subsubappendix@format@second}{%
4922      \let\Crefrange@subsubappendix@format@second%
4923      \Crefrange@subappendix@format@second}{}%
4924  \@ifundefined{crefrange@subsubappendix@format@middle}{%

```

```

4925      \let\crefrange@subsubappendix@format@middle%
4926      \crefrange@subappendix@format@middle}{}}%
4927 \@ifundefined{\crefrange@subsubappendix@format@middle}{%
4928     \let\Crefrange@subsubappendix@format@middle%
4929     \Crefrange@subappendix@format@middle}{}}%
4930 \@ifundefined{\crefrange@subsubappendix@format@last}{%
4931     \let\crefrange@subsubappendix@format@last%
4932     \crefrange@subappendix@format@last}{}}%
4933 \@ifundefined{\crefrange@subsubappendix@format@last}{%
4934     \let\Crefrange@subsubappendix@format@last%
4935     \Crefrange@subappendix@format@last}{}}%
4936 %
4937 \@ifundefined{\cref@subsubsubappendix@format}{%
4938     \let\cref@subsubsubappendix@format%
4939     \cref@subsubappendix@format}{}}%
4940 \@ifundefined{\Cref@subsubsubappendix@format}{%
4941     \let\Cref@subsubsubappendix@format%
4942     \Cref@subsubappendix@format}{}}%
4943 \@ifundefined{\crefrange@subsubsubappendix@format}{%
4944     \let\crefrange@subsubsubappendix@format%
4945     \crefrange@subsubappendix@format}{}}%
4946 \@ifundefined{\crefrange@subsubsubappendix@format}{%
4947     \let\Crefrange@subsubsubappendix@format%
4948     \Crefrange@subsubappendix@format}{}}%
4949 \@ifundefined{\cref@subsubsubappendix@format@first}{%
4950     \let\cref@subsubsubappendix@format@first%
4951     \cref@subsubappendix@format@first}{}}%
4952 \@ifundefined{\Cref@subsubsubappendix@format@first}{%
4953     \let\Cref@subsubsubappendix@format@first%
4954     \Cref@subsubappendix@format@first}{}}%
4955 \@ifundefined{\cref@subsubsubappendix@format@second}{%
4956     \let\cref@subsubsubappendix@format@second%
4957     \cref@subsubappendix@format@second}{}}%
4958 \@ifundefined{\Cref@subsubsubappendix@format@second}{%
4959     \let\Cref@subsubsubappendix@format@second%
4960     \Cref@subsubappendix@format@second}{}}%
4961 \@ifundefined{\cref@subsubsubappendix@format@middle}{%
4962     \let\cref@subsubsubappendix@format@middle%
4963     \cref@subsubappendix@format@middle}{}}%
4964 \@ifundefined{\Cref@subsubsubappendix@format@middle}{%
4965     \let\Cref@subsubsubappendix@format@middle%
4966     \Cref@subsubappendix@format@middle}{}}%
4967 \@ifundefined{\cref@subsubsubappendix@format@last}{%
4968     \let\cref@subsubsubappendix@format@last%
4969     \cref@subsubappendix@format@last}{}}%
4970 \@ifundefined{\Cref@subsubsubappendix@format@last}{%
4971     \let\Cref@subsubsubappendix@format@last%
4972     \Cref@subsubappendix@format@last}{}}%
4973 \@ifundefined{\crefrange@subsubsubappendix@format@first}{%
4974     \let\crefrange@subsubsubappendix@format@first%

```

```

4975      \crefrange@subsubappendix@format@first}{}%
4976  \@ifundefined{Crefrange@subsubsubappendix@format@first}{%
4977      \let\Crefrange@subsubsubappendix@format@first%
4978      \Crefrange@subsubappendix@format@first}{}%
4979  \@ifundefined{crefrange@subsubsubappendix@format@second}{%
4980      \let\crefrange@subsubsubappendix@format@second%
4981      \crefrange@subsubappendix@format@second}{}%
4982  \@ifundefined{Crefrange@subsubsubappendix@format@second}{%
4983      \let\Crefrange@subsubsubappendix@format@second%
4984      \Crefrange@subsubappendix@format@second}{}%
4985  \@ifundefined{crefrange@subsubsubappendix@format@middle}{%
4986      \let\crefrange@subsubsubappendix@format@middle%
4987      \crefrange@subsubappendix@format@middle}{}%
4988  \@ifundefined{Crefrange@subsubsubappendix@format@middle}{%
4989      \let\Crefrange@subsubsubappendix@format@middle%
4990      \Crefrange@subsubappendix@format@middle}{}%
4991  \@ifundefined{crefrange@subsubsubappendix@format@last}{%
4992      \let\crefrange@subsubsubappendix@format@last%
4993      \crefrange@subsubappendix@format@last}{}%
4994  \@ifundefined{Crefrange@subsubsubappendix@format@last}{%
4995      \let\Crefrange@subsubsubappendix@format@last%
4996      \Crefrange@subsubappendix@format@last}{}%

```

Ditto for subfigures and subtables.

```

4997  \@ifundefined{cref@subfigure@format}{%
4998      \let\cref@subfigure@format%
4999      \cref@figure@format}{}%
5000  \@ifundefined{Cref@subfigure@format}{%
5001      \let\Creff@subfigure@format%
5002      \Cref@figure@format}{}%
5003  \@ifundefined{crefrange@subfigure@format}{%
5004      \let\crefrange@subfigure@format%
5005      \crefrange@figure@format}{}%
5006  \@ifundefined{Crefrange@subfigure@format}{%
5007      \let\Crefrange@subfigure@format%
5008      \Crefrange@figure@format}{}%
5009  \@ifundefined{cref@subfigure@format@first}{%
5010      \let\cref@subfigure@format@first%
5011      \cref@figure@format@first}{}%
5012  \@ifundefined{Cref@subfigure@format@first}{%
5013      \let\Creff@subfigure@format@first%
5014      \Cref@figure@format@first}{}%
5015  \@ifundefined{cref@subfigure@format@second}{%
5016      \let\cref@subfigure@format@second%
5017      \cref@figure@format@second}{}%
5018  \@ifundefined{Cref@subfigure@format@second}{%
5019      \let\Creff@subfigure@format@second%
5020      \Cref@figure@format@second}{}%
5021  \@ifundefined{cref@subfigure@format@middle}{%
5022      \let\cref@subfigure@format@middle%

```

```

5023     \cref@figure@format@middle}{}%
5024     \@ifundefined{Cref@subfigure@format@middle}{}%
5025         \let\cref@subfigure@format@middle%
5026             \Cref@figure@format@middle}{}%
5027     \@ifundefined{\cref@subfigure@format@last}{}%
5028         \let\cref@subfigure@format@last%
5029             \cref@figure@format@last}{}%
5030     \@ifundefined{Cref@subfigure@format@last}{}%
5031         \let\cref@subfigure@format@last%
5032             \Cref@figure@format@last}{}%
5033     \@ifundefined{\crefrange@subfigure@format@first}{}%
5034         \let\crefrange@subfigure@format@first%
5035             \crefrange@figure@format@first}{}%
5036     \@ifundefined{\crefrange@subfigure@format@first}{}%
5037         \let\crefrange@subfigure@format@first%
5038             \Crefrange@figure@format@first}{}%
5039     \@ifundefined{\crefrange@subfigure@format@second}{}%
5040         \let\crefrange@subfigure@format@second%
5041             \crefrange@figure@format@second}{}%
5042     \@ifundefined{\crefrange@subfigure@format@second}{}%
5043         \let\crefrange@subfigure@format@second%
5044             \Crefrange@figure@format@second}{}%
5045     \@ifundefined{\crefrange@subfigure@format@middle}{}%
5046         \let\crefrange@subfigure@format@middle%
5047             \crefrange@figure@format@middle}{}%
5048     \@ifundefined{\crefrange@subfigure@format@middle}{}%
5049         \let\crefrange@subfigure@format@middle%
5050             \Crefrange@figure@format@middle}{}%
5051     \@ifundefined{\crefrange@subfigure@format@last}{}%
5052         \let\crefrange@subfigure@format@last%
5053             \crefrange@figure@format@last}{}%
5054     \@ifundefined{\crefrange@subfigure@format@last}{}%
5055         \let\crefrange@subfigure@format@last%
5056             \Crefrange@figure@format@last}{}%
5057 %
5058     \@ifundefined{\cref@subtable@format}{}%
5059         \let\cref@subtable@format%
5060             \cref@table@format}{}%
5061     \@ifundefined{Cref@subtable@format}{}%
5062         \let\cref@subtable@format%
5063             \Cref@table@format}{}%
5064     \@ifundefined{\crefrange@subtable@format}{}%
5065         \let\crefrange@subtable@format%
5066             \crefrange@table@format}{}%
5067     \@ifundefined{\crefrange@subtable@format}{}%
5068         \let\crefrange@subtable@format%
5069             \Crefrange@table@format}{}%
5070     \@ifundefined{\cref@subtable@format@first}{}%
5071         \let\cref@subtable@format@first%
5072             \cref@table@format@first}{}%

```

```

5073  \@ifundefined{Cref@subtable@format@first}{%
5074    \let\cref@subtable@format@first%
5075    \Cref@table@format@first}{}
5076  \@ifundefined{cref@subtable@format@second}{%
5077    \let\cref@subtable@format@second%
5078    \cref@table@format@second}{}
5079  \@ifundefined{Cref@subtable@format@second}{%
5080    \let\cref@subtable@format@second%
5081    \Cref@table@format@second}{}
5082  \@ifundefined{cref@subtable@format@middle}{%
5083    \let\cref@subtable@format@middle%
5084    \cref@table@format@middle}{}
5085  \@ifundefined{Cref@subtable@format@middle}{%
5086    \let\cref@subtable@format@middle%
5087    \Cref@table@format@middle}{}
5088  \@ifundefined{cref@subtable@format@last}{%
5089    \let\cref@subtable@format@last%
5090    \cref@table@format@last}{}
5091  \@ifundefined{Cref@subtable@format@last}{%
5092    \let\cref@subtable@format@last%
5093    \Cref@table@format@last}{}
5094  \@ifundefined{crefrange@subtable@format@first}{%
5095    \let\crefrange@subtable@format@first%
5096    \crefrange@table@format@first}{}
5097  \@ifundefined{Crefrange@subtable@format@first}{%
5098    \let\Crefrange@subtable@format@first%
5099    \Crefrange@table@format@first}{}
5100  \@ifundefined{crefrange@subtable@format@second}{%
5101    \let\crefrange@subtable@format@second%
5102    \crefrange@table@format@second}{}
5103  \@ifundefined{Crefrange@subtable@format@second}{%
5104    \let\Crefrange@subtable@format@second%
5105    \Crefrange@table@format@second}{}
5106  \@ifundefined{crefrange@subtable@format@middle}{%
5107    \let\crefrange@subtable@format@middle%
5108    \crefrange@table@format@middle}{}
5109  \@ifundefined{Crefrange@subtable@format@middle}{%
5110    \let\Crefrange@subtable@format@middle%
5111    \Crefrange@table@format@middle}{}
5112  \@ifundefined{crefrange@subtable@format@last}{%
5113    \let\crefrange@subtable@format@last%
5114    \crefrange@table@format@last}{}
5115  \@ifundefined{Crefrange@subtable@format@last}{%
5116    \let\Crefrange@subtable@format@last%
5117    \Crefrange@table@format@last}{}

```

Ditto for enums.

```

5118  \@ifundefined{ceref@enumii@format}{%
5119    \let\ceref@enumii@format%
5120    \ceref@enumi@format}{}

```

```

5121  \@ifundefined{Cref@enumii@format}{%
5122    \let\cref@enumii@format%
5123    \Cref@enumii@format}{}}%
5124  \@ifundefined{crefrange@enumii@format}{%
5125    \let\crefrange@enumii@format%
5126    \crefrange@enumii@format}{}}%
5127  \@ifundefined{Crefrange@enumii@format}{%
5128    \let\Crefrange@enumii@format%
5129    \Crefrange@enumii@format}{}}%
5130  \@ifundefined{cref@enumii@format@first}{%
5131    \let\cref@enumii@format@first%
5132    \cref@enumii@format@first}{}}%
5133  \@ifundefined{Cref@enumii@format@first}{%
5134    \let\cref@enumii@format@first%
5135    \Cref@enumii@format@first}{}}%
5136  \@ifundefined{cref@enumii@format@second}{%
5137    \let\cref@enumii@format@second%
5138    \cref@enumii@format@second}{}}%
5139  \@ifundefined{Cref@enumii@format@second}{%
5140    \let\cref@enumii@format@second%
5141    \Cref@enumii@format@second}{}}%
5142  \@ifundefined{cref@enumii@format@middle}{%
5143    \let\cref@enumii@format@middle%
5144    \cref@enumii@format@middle}{}}%
5145  \@ifundefined{Cref@enumii@format@middle}{%
5146    \let\cref@enumii@format@middle%
5147    \Cref@enumii@format@middle}{}}%
5148  \@ifundefined{cref@enumii@format@last}{%
5149    \let\cref@enumii@format@last%
5150    \cref@enumii@format@last}{}}%
5151  \@ifundefined{Cref@enumii@format@last}{%
5152    \let\cref@enumii@format@last%
5153    \Cref@enumii@format@last}{}}%
5154  \@ifundefined{crefrange@enumii@format@first}{%
5155    \let\crefrange@enumii@format@first%
5156    \crefrange@enumii@format@first}{}}%
5157  \@ifundefined{Crefrange@enumii@format@first}{%
5158    \let\Crefrange@enumii@format@first%
5159    \Crefrange@enumii@format@first}{}}%
5160  \@ifundefined{crefrange@enumii@format@second}{%
5161    \let\crefrange@enumii@format@second%
5162    \crefrange@enumii@format@second}{}}%
5163  \@ifundefined{Crefrange@enumii@format@second}{%
5164    \let\Crefrange@enumii@format@second%
5165    \Crefrange@enumii@format@second}{}}%
5166  \@ifundefined{crefrange@enumii@format@middle}{%
5167    \let\crefrange@enumii@format@middle%
5168    \crefrange@enumii@format@middle}{}}%
5169  \@ifundefined{Crefrange@enumii@format@middle}{%
5170    \let\Crefrange@enumii@format@middle%

```

```

5171      \Crefrange@enumi@format@middle}{}%
5172  \@ifundefined{crefrange@enumi@format@last}{}%
5173      \let\crefrange@enumi@format@last%
5174      \crefrange@enumi@format@last}{}%
5175  \@ifundefined{Crefrange@enumi@format@last}{}%
5176      \let\Crefrange@enumi@format@last%
5177      \Crefrange@enumi@format@last}{}%
5178 %
5179  \@ifundefined{cref@enumiii@format}{}%
5180      \let\cref@enumiii@format%
5181      \cref@enumi@format}{}%
5182  \@ifundefined{Cref@enumiii@format}{}%
5183      \let\Cref@enumiii@format%
5184      \Cref@enumi@format}{}%
5185  \@ifundefined{crefrange@enumiii@format}{}%
5186      \let\crefrange@enumiii@format%
5187      \crefrange@enumi@format}{}%
5188  \@ifundefined{Crefrange@enumiii@format}{}%
5189      \let\Crefrange@enumiii@format%
5190      \Crefrange@enumi@format}{}%
5191  \@ifundefined{cref@enumiii@format@first}{}%
5192      \let\cref@enumiii@format@first%
5193      \cref@enumi@format@first}{}%
5194  \@ifundefined{Cref@enumiii@format@first}{}%
5195      \let\Cref@enumiii@format@first%
5196      \Cref@enumi@format@first}{}%
5197  \@ifundefined{cref@enumiii@format@second}{}%
5198      \let\cref@enumiii@format@second%
5199      \cref@enumi@format@second}{}%
5200  \@ifundefined{Cref@enumiii@format@second}{}%
5201      \let\Cref@enumiii@format@second%
5202      \Cref@enumi@format@second}{}%
5203  \@ifundefined{cref@enumi@format@middle}{}%
5204      \let\cref@enumi@format@middle%
5205      \cref@enumi@format@middle}{}%
5206  \@ifundefined{Cref@enumi@format@middle}{}%
5207      \let\Cref@enumi@format@middle%
5208      \Cref@enumi@format@middle}{}%
5209  \@ifundefined{cref@enumi@format@last}{}%
5210      \let\cref@enumi@format@last%
5211      \cref@enumi@format@last}{}%
5212  \@ifundefined{Cref@enumi@format@last}{}%
5213      \let\Cref@enumi@format@last%
5214      \Cref@enumi@format@last}{}%
5215  \@ifundefined{crefrange@enumi@format@first}{}%
5216      \let\crefrange@enumi@format@first%
5217      \crefrange@enumi@format@first}{}%
5218  \@ifundefined{Crefrange@enumi@format@first}{}%
5219      \let\Crefrange@enumi@format@first%
5220      \Crefrange@enumi@format@first}{}%

```

```

5221   \@ifundefined{crefrange@enumiii@format@second}{%
5222     \let\crefrange@enumiii@format@second%
5223     \crefrange@enumiii@format@second}{}
5224   \@ifundefined{Crefrange@enumiii@format@second}{%
5225     \let\Crefrange@enumiii@format@second%
5226     \Crefrange@enumiii@format@second}{}
5227   \@ifundefined{crefrange@enumiii@format@middle}{%
5228     \let\crefrange@enumiii@format@middle%
5229     \crefrange@enumiii@format@middle}{}
5230   \@ifundefined{Crefrange@enumiii@format@middle}{%
5231     \let\Crefrange@enumiii@format@middle%
5232     \Crefrange@enumiii@format@middle}{}
5233   \@ifundefined{crefrange@enumiii@format@last}{%
5234     \let\crefrange@enumiii@format@last%
5235     \crefrange@enumiii@format@last}{}
5236   \@ifundefined{Crefrange@enumiii@format@last}{%
5237     \let\Crefrange@enumiii@format@last%
5238     \Crefrange@enumiii@format@last}{}
5239 %
5240   \@ifundefined{cref@enumiv@format}{%
5241     \let\cref@enumiv@format%
5242     \cref@enumiii@format}{}
5243   \@ifundefined{Cref@enumiv@format}{%
5244     \let\Cref@enumiv@format%
5245     \Cref@enumiii@format}{}
5246   \@ifundefined{crefrange@enumiv@format}{%
5247     \let\crefrange@enumiv@format%
5248     \crefrange@enumiii@format}{}
5249   \@ifundefined{Crefrange@enumiv@format}{%
5250     \let\Crefrange@enumiv@format%
5251     \Crefrange@enumiii@format}{}
5252   \@ifundefined{cref@enumiv@format@first}{%
5253     \let\cref@enumiv@format@first%
5254     \cref@enumiii@format@first}{}
5255   \@ifundefined{Cref@enumiv@format@first}{%
5256     \let\Cref@enumiv@format@first%
5257     \Cref@enumiii@format@first}{}
5258   \@ifundefined{cref@enumiv@format@second}{%
5259     \let\cref@enumiv@format@second%
5260     \cref@enumiii@format@second}{}
5261   \@ifundefined{Cref@enumiv@format@second}{%
5262     \let\Cref@enumiv@format@second%
5263     \Cref@enumiii@format@second}{}
5264   \@ifundefined{cref@enumiv@format@middle}{%
5265     \let\cref@enumiv@format@middle%
5266     \cref@enumiii@format@middle}{}
5267   \@ifundefined{Cref@enumiv@format@middle}{%
5268     \let\Cref@enumiv@format@middle%
5269     \Cref@enumiii@format@middle}{}
5270   \@ifundefined{cref@enumiv@format@last}{%

```

```

5271      \let\cref@enumiv@format@last%
5272      \cref@enumiii@format@last}{}}%
5273 \@ifundefined{Cref@enumiv@format@last}{%
5274   \let\cref@enumiv@format@last%
5275   \Cref@enumiii@format@last}{}}%
5276 \@ifundefined{crefrange@enumiv@format@first}{%
5277   \let\crefrange@enumiv@format@first%
5278   \crefrange@enumiii@format@first}{}}%
5279 \@ifundefined{Crefrange@enumiv@format@first}{%
5280   \let\Crefrange@enumiv@format@first%
5281   \Crefrange@enumiii@format@first}{}}%
5282 \@ifundefined{crefrange@enumiv@format@second}{%
5283   \let\crefrange@enumiv@format@second%
5284   \crefrange@enumiii@format@second}{}}%
5285 \@ifundefined{Crefrange@enumiv@format@second}{%
5286   \let\Crefrange@enumiv@format@second%
5287   \Crefrange@enumiii@format@second}{}}%
5288 \@ifundefined{crefrange@enumiv@format@middle}{%
5289   \let\crefrange@enumiv@format@middle%
5290   \crefrange@enumiii@format@middle}{}}%
5291 \@ifundefined{Crefrange@enumiv@format@middle}{%
5292   \let\Crefrange@enumiv@format@middle%
5293   \Crefrange@enumiii@format@middle}{}}%
5294 \@ifundefined{crefrange@enumiv@format@last}{%
5295   \let\crefrange@enumiv@format@last%
5296   \crefrange@enumiii@format@last}{}}%
5297 \@ifundefined{Crefrange@enumiv@format@last}{%
5298   \let\Crefrange@enumiv@format@last%
5299   \Crefrange@enumiii@format@last}{}}%
5300 %
5301 \@ifdefined{cref@enumv@format}{%
5302   \let\cref@enumv@format%
5303   \cref@enumiv@format}{}}%
5304 \@ifdefined{Cref@enumv@format}{%
5305   \let\cref@enumv@format%
5306   \Cref@enumiv@format}{}}%
5307 \@ifdefined{crefrange@enumv@format}{%
5308   \let\crefrange@enumv@format%
5309   \crefrange@enumiv@format}{}}%
5310 \@ifdefined{Crefrange@enumv@format}{%
5311   \let\Crefrange@enumv@format%
5312   \Crefrange@enumiv@format}{}}%
5313 \@ifdefined{cref@enumv@format@first}{%
5314   \let\cref@enumv@format@first%
5315   \cref@enumiv@format@first}{}}%
5316 \@ifdefined{Cref@enumv@format@first}{%
5317   \let\cref@enumv@format@first%
5318   \Cref@enumiv@format@first}{}}%
5319 \@ifdefined{cref@enumv@format@second}{%
5320   \let\cref@enumv@format@second%

```

```

5321      \cref@enumiv@format@second}{}}%
5322  \@ifundefined{Cref@enumv@format@second}{%
5323      \let\cref@enumv@format@second%
5324      \Cref@enumiv@format@second}{}}%
5325  \@ifundefined{\cref@enumv@format@middle}{%
5326      \let\cref@enumv@format@middle%
5327      \cref@enumiv@format@middle}{}}%
5328  \@ifundefined{\Cref@enumv@format@middle}{%
5329      \let\cref@enumv@format@middle%
5330      \Cref@enumiv@format@middle}{}}%
5331  \@ifundefined{\cref@enumv@format@last}{%
5332      \let\cref@enumv@format@last%
5333      \cref@enumiv@format@last}{}}%
5334  \@ifundefined{\Cref@enumv@format@last}{%
5335      \let\cref@enumv@format@last%
5336      \Cref@enumiv@format@last}{}}%
5337  \@ifundefined{\crefrange@enumv@format@first}{%
5338      \let\crefrange@enumv@format@first%
5339      \crefrange@enumiv@format@first}{}}%
5340  \@ifundefined{\crefrange@enumv@format@first}{%
5341      \let\crefrange@enumv@format@first%
5342      \crefrange@enumiv@format@first}{}}%
5343  \@ifundefined{\crefrange@enumv@format@second}{%
5344      \let\crefrange@enumv@format@second%
5345      \crefrange@enumiv@format@second}{}}%
5346  \@ifundefined{\crefrange@enumv@format@second}{%
5347      \let\crefrange@enumv@format@second%
5348      \crefrange@enumiv@format@second}{}}%
5349  \@ifundefined{\crefrange@enumv@format@middle}{%
5350      \let\crefrange@enumv@format@middle%
5351      \crefrange@enumiv@format@middle}{}}%
5352  \@ifundefined{\crefrange@enumv@format@middle}{%
5353      \let\crefrange@enumv@format@middle%
5354      \crefrange@enumiv@format@middle}{}}%
5355  \@ifundefined{\crefrange@enumv@format@last}{%
5356      \let\crefrange@enumv@format@last%
5357      \crefrange@enumiv@format@last}{}}%
5358  \@ifundefined{\crefrange@enumv@format@last}{%
5359      \let\crefrange@enumv@format@last%
5360      \crefrange@enumiv@format@last}{}}%
5361 %
5362 \let\cref@language\relax%
5363 }% end of \AtBeginDocument

```

Change History

v0.01		v0.11	
	General: Initial version	1	General: Made referencing aware of appendices.
v0.02		v0.11.1	
	General: Complete rewrite	1	General: Bug fixes.
v0.03		v0.12	
	General: Added reference ranges . .	1	General: Restore working <code>\ref*</code> when hyperref is loaded – first release mirrored on www.drbubit.org
v0.04		v0.13	
	General: Renamed "cleveref" – first public release	1	General: Finally implemented <code>sort</code> and <code>compress</code> package options. Support <code>amsmath</code> <code>\tag</code> command. Added <code>babel</code> support for English, German and French. Added <code>varioref</code> support.
v0.05		v0.13.1	
	General: Added <code>poorman</code> option . .	1	General: Bug fix to <code>\cref@get*</code> commands to allow fragile and non-expandable commands in label tags.
v0.06		v0.13.2	
	General: <code>poorman</code> no longer writes extra <code>.tmp</code> file	1	General: Added <code>\crefrangepreconjunction</code> and <code>\crefrangepostconjunction</code> commands, needed by some languages (such as Italian). Added <code>babel</code> support for Spanish and Italian. Added notes about <code>memoir</code> (in)compatibility.
v0.07		v0.14	
	General: Allow prevention of reference range collapsing	1	General: Fixed bug that caused labels containing components with values of 10 or higher to be sorted incorrectly. Fixed <code>\Cref</code> to no longer capitalise all cross-reference names in a multi-reference, just the first one. Added <code>capitalise</code> option to force capitalisation everywhere.
v0.08		v0.14.1	
	General: Made referencing commands robust, improved default formats, made starred versions of referencing commands for hyperref, allowed multiple consecutive empty references in list to prevent range collapsing, and fixed bugs. Phew.	1	General: Added support for <code>amsmath</code> 's <code>subequations</code> environment
v0.08.1			1
	General: Bug fixes.	1	
v0.09			
	General: Added an extra conjunction and format component, used when a list only contains a single pair of references or reference sub-lists. Formats are now constructed from customisable components, unless overridden using the old format definition commands.	1	
v0.10			
	General: Allow optional argument to <code>\label</code> to override reference type. Removed <code>hyperref</code> and <code>ntheorem</code> options; support for these and <code>amsmath</code> is enabled automatically if those packages are loaded.	1	

v0.14.2	General: Fixed subequations sorting bug. Fixed bug in <code>poorman</code> when used without <code>babel</code> . <code>capitalise</code> option no longer uses <code>\Cref</code> variant everywhere; it now redefines the <code>\cref</code> variants instead.	1
v0.14.3	General: Bug-fix in <code>\appendix</code> code.	1
v0.15	General: Added <code>amsthm</code> support, contributed by Michael Ummels. Added <code>\leavevmode</code> before <code>\begingroup</code> in <code>\@cref</code> to avoid subtle bug that caused page count to be reset if the output routine was triggered within <code>\@cref</code>	1
v0.15.1	General: Fixed regression introduced in v0.13 in non- <code>hyperref</code> <code>poorman</code> code. Fixed bug in <code>varioref</code> support that caused <code>\vref</code> to print <code>\ref{textcurrent}</code> string for references on the current page, breaking <code>varioref</code> backwards-compatibility. Added <code>babel</code> support for Dutch.	1
v0.15.2	General: Fixed bug in <code>\appendix</code> that produced badly formed prefix data for labels that aren't reset by other counters (e.g. tables and figures in most document classes). Fixed bug in <code>hyperref</code> <code>poorman</code> code	
	that caused all label names to be lower-cased in the sed script. Fixed spacing bugs in the <code>cleveref</code> versions of the <code>varioref</code> commands.	1
v0.15.3	General: Fixed bug in <code>varioref</code> support. Changed <code>poorman</code> <code>\usepackage</code> sed substitution rule to use POSIX regexp syntax.	1
v0.16	General: Major changes to the low-level implementation <code>cleveref</code> now stores the extra information it requires in its own <code>\cref@currentlabel</code> and its own parallel series of labels in the aux file, staying out of the way of the standard cross-reference mechanism and <code>\ref</code> command. Also added <code>\namecref</code> and <code>\nameCref</code> commands, fixed a serious bug in the <code>amsmath</code> support affecting spacing of multi-line equation environments, added support for footnotes, and made <code>\newtheorem</code> automatically define the singular form of the cross-reference name for new theorem-like environments.	1
v0.16.1	General: Fixed bugs in <code>amsmath</code> spacing fix and <code>amsthm</code> support.	1
v0.16.2	General: Fixed bugs in <code>\appendix</code> version used with <code>hyperref</code> , and in <code>\footnote</code> support.	1

Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols	
\@csetcref	<u>1141</u> , <u>1820</u> , <u>2503</u>
\@csetcrefrange	<u>1191</u> , <u>1820</u> , <u>2503</u>
\@cref	<u>996</u>
\@cref@stack@insert	<u>563</u>
\@crefconstructcomponents	<u>1312</u>
\@crefdefineallformats	<u>1500</u>
\@crefdefineformat	<u>1358</u>
\@crefdefinemultiformat	<u>1392</u>
\@crefformat	<u>1517</u>
\@crefmultiformat	<u>1584</u>
\@crefname	<u>1268</u>
\@crefnostar	<u>2317</u>
\@crefrangedefineformat	<u>1375</u>
\@crefrangedefinemultiformat	<u>1446</u>
\@crefrangeformat	<u>1550</u>
\@crefrangemultiformat	<u>1642</u>
\@crefrangenostar	<u>1806</u> , <u>2317</u>
\@crefrangestar	<u>1806</u> , <u>2317</u>
\@crefstar	<u>1806</u> , <u>2317</u>
\@footnotetext	<u>18</u>
\@gobble@optarg	<u>388</u>
\@mpfootnotetext	<u>18</u>
\@othm	<u>1870</u>
\@setcref	<u>1123</u>
\@setcrefrange	<u>1142</u>
\@thm	<u>1848</u> , <u>1908</u>
\@xnthm	<u>1870</u> , <u>1958</u>
\@ynthm	<u>1870</u> , <u>1930</u>
A	
\amsmath	<u>48</u>
\amsthm	<u>1906</u>
\appendix	<u>303</u> , <u>1722</u>
C	
\capitalise	<u>7</u> , <u>2580</u>
\compress	<u>2560</u>
\Cref	<u>5</u> , <u>990</u> , <u>2317</u>
\cref	<u>5</u> , <u>990</u> , <u>2317</u>
\Cref*	<u>5</u> , <u>1806</u>
\cref*	<u>5</u> , <u>1806</u>
\cref@addto	<u>2590</u>
\cref@append@toks	<u>449</u>
\cref@constructprefix	<u>432</u>
\cref@countercmp	<u>582</u> , <u>627</u>
\cref@currentlabel	<u>1</u>
\cref@getcounter	<u>391</u>
\cref@getlabel	<u>391</u>
\cref@getprefix	<u>391</u>
\cref@gettype	<u>391</u>
\cref@hyperref	<u>1707</u>
\cref@isinresetlist	<u>658</u>
\cref@isrefconsecutive	<u>795</u>
\cref@isstackempty	<u>505</u>
\cref@isstackfull	<u>505</u>
\cref@label@types	<u>1250</u>
\cref@old@appendix	<u>303</u>
\cref@old@refstepcounter	<u>1</u>
\cref@Override@label@type	<u>431</u>
\cref@poorman@text	<u>2061</u>
\cref@processconsecutive	<u>925</u>
\cref@processgroup	<u>818</u>
\cref@processgroupall	<u>867</u>
\cref@resetby	<u>658</u>
\cref@stack@add	<u>452</u>
\cref@stack@init	<u>452</u>
\cref@stack@insert	<u>559</u>
\cref@stack@pop	<u>452</u>
\cref@stack@push	<u>452</u>
\cref@stack@sort	<u>515</u>
\cref@stack@to@list	<u>452</u>
\cref@stack@top	<u>452</u>
\cref@stack@topandbottom	<u>452</u>
\cref@writelanguagerules	<u>2084</u>
\cref@writescript	<u>2312</u>
\crefdefaultlabelformat	<u>8</u> , <u>1251</u> , <u>2588</u>
\Creformat	<u>13</u> , <u>1505</u>
\crefformat	<u>13</u> , <u>1505</u>
\creflabelformat	<u>11</u> , <u>1251</u> , <u>2588</u>
\creflastconjunction	<u>9</u>
\creflastgroupconjunction	<u>10</u>
\crefmiddleconjunction	<u>9</u>
\crefmiddlegroupconjunction	<u>10</u>
\Crefmultiformat	<u>14</u> , <u>1505</u>
\crefmultiformat	<u>14</u> , <u>1505</u>
\Crefname	<u>10</u> , <u>1251</u>

\crefname	10, 1251	\legacyvarioref	19
\Crefname@preamble	1264	M	
\crefname@preamble	1264		
\crefpairconjunction	9		
\crefpairgroupconjunction	10		
\Crefrange	5, 990, 2317	\make@df@tag@@	294
\crefrange	5, 990, 2317	\make@df@tag@@@	294
\Crefrange*	5, 1806	\measure@	57
\crefrange*	5, 1806	\multiline@	57
\crefrangeconjunction	9	N	
\Crefrangeformat	14, 1505	\nameCref	6, 1198
\crefrangeformat	14, 1505	\namecref	6, 1198
\crefrangelabelformat	11, 1251	\nameCrefs	6, 1198
\Crefrangemultiformat	14, 1505	\namecrefs	6, 1198
\crefrangemultiformat	14, 1505	\newtheorem	12, 1870
\crefrangepostconjunction	9	\ngerman	2931
\crefrangepreconjunction	9	\nosort	2560
		\ntheorem	1841
D	P		
\dutch	3034	\poorman	2059
E	R		
\english	2601	\ref	5
F		\refstepcounter	1
\forforeign@language	2065	\refstepcounter@noarg	1716
\french	3176	\refstepcounter@optarg	1716
\Fullref	18, 2011, 2383	\russian	3670
\fullref	18, 2005, 2011, 2383	S	
\Fullref*	19, 2011, 2383	\select@language	2065
\fullref*	19, 2011, 2383	\sort	2560
G		\spanish	3340
\german	2766	\subequations	280
\gmeasure@	57	T	
H		\theorem@prework	1847
\H@refstepcounter	1709	\thref	18, 1841
\hyperref	1705	U	
I	V		
\if@ cref@capitalise	2580	\varioref	1960
\if@ cref@compress	2560	\Vr@f	2005
\if@ cref@inresetlist	658	\vr@f	2005
\if@ cref@refconsecutive	795	\Vref	18, 2011, 2383
\if@ cref@sort	2560	\vref	18, 2005, 2011, 2383
\if@ cref@stackempty	505	\Vref*	19, 2011, 2383
\if@ cref@stackfull	505	\vref*	19, 2005, 2011, 2383
\if@ crefstarred	994	\Vrefrange	18, 2011, 2383
\italian	3505	\vrefrange	18, 2005, 2011, 2383
L		\Vrefrange*	19, 2011, 2383
\label	16, 30, 48	\vrefrange*	19, 2011, 2383
\label@in@display	48		